

LED tube ECO T8 glass 600 230V 9W 1440lm G13 220° IP20 840

Product code 17574

Brand ECO
Supply voltage 230V
Power factor 0.90
Output 9W
Maximum output 9W/1m
Luminous flux 1440lumens
Luminaire's efficiency lm79 160W
Correlated colour temperature pure white 4000K
Lens angle 220
Socket G13
Cri 80
Sdcm - macadam ellipses 5
Protection class IP20
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Length 602.0mm
Diameter 26.0mm
In package 1pc
In box 25pcs
Casing material aluminum + glass
Work environment indoor use
Operation temperature -20° - +45°C
Certificates CE, RoHS, ErP
Warranty 3 years



LED tube to replace an old fluorescent tube with a more efficient light source. The LED tube casing is made of glass.

LED tube EMOS PROFI PLUS T8 GLASS 120cm 230V 14W 2100lm 260° IP20 840

Product code 16482

Brand [EMOS](#)
Supply voltage 230V
Power factor 0.96
Output 14W
Maximum output 14W/1m
Luminous flux 2100lumens
Luminaire's efficiency lm79 150W
Correlated colour temperature pure white 4000K
Lens angle 260
Cri 80
Protection class IP20
Lifespan 50000h
Length 1213.0mm
Diameter 27.0mm
In package 1pc
In box 10pcs
Casing material glass
No. of switches 25000pcs
Operation temperature -25°C~40°C
Certificates CE
Warranty 5 years



LED tube EMOS PROFI PLUS T8 GLASS 150cm 230V 20.6W 3100lm 260° IP20 840

Product code 16574

Brand [EMOS](#)
Supply voltage 230V
Power factor 0.96
Output 20.6W
Maximum output 20.6W/1m
Luminous flux 3100lumens
Luminaire's efficiency lm79 150W
Correlated colour temperature pure white 4000K
Lens angle 260
Cri 80
Protection class IP20
Lifespan 50000h
Length 1514.0mm
Diameter 27.0mm
In package 1pc
In box 10pcs
Casing material glass
No. of switches 25000pcs
Operation temperature -25°C~40°C
Certificates CE
Warranty 5 years



LED tube EMOS PROFI PLUS T8 GLASS 150cm 230V 20.6W 3100lm 260° IP20 865

Product code 17962

Brand [EMOS](#)
Supply voltage 230V
Power factor 0.96
Output 20.6W
Maximum output 20.6W/1m
Luminous flux 3100lumens
Luminaire's efficiency lm79 150W
Correlated colour temperature cold
white 6500K
Lens angle 260
Cri 80
Protection class IP20
Lifespan 50000h
Length 1514.0mm
Diameter 27.0mm
In package 1pc
In box 10pcs
Casing material glass
No. of switches 25000pcs
Operation temperature -25°C~40°C
Certificates CE
Warranty 5 years



LED tube EMOS PROFI PLUS T8 GLASS 60cm 230V 7.3W 1100lm 260° IP20 840

Product code 16575

Brand [EMOS](#)
Supply voltage 230V
Power factor 0.96
Output 7.3W
Maximum output 7.3W/1m
Luminous flux 1100lumens
Luminaire's efficiency lm79 151W
Correlated colour temperature pure
white 4000K
Lens angle 260
Cri 80
Protection class IP20
Lifespan 50000h
Length 603.0mm
Diameter 27.0mm
In package 1pc
In box 10pcs
Casing material glass
No. of switches 25000pcs
Operation temperature -25°C~40°C
Certificates CE
Warranty 5 years



LED tube Prolumen T5 STRONG 1148 230V 18W 2880lm 140° 840

Product code 16677

Brand [Prolumen](#)
 Supply voltage 230V
 Output 18W
 Maximum output 18W/1m
 Luminous flux 2880lumens
 Luminaire's efficiency lm79 160W
 Correlated colour temperature pure white 4000K
 Lens angle 140
 Source of light [EPISTAR LED](#)
 Cri 80
 Lifespan 50000h
 Llmf tm21 L70B50 @25°C 50.000h
 Length 1148.0mm
 Diameter 22.0mm
 In package 1pc
 In box 25pcs
 Work environment indoor / outdoor use
 Operation temperature -20 - +40°C
 Certificates CE, RoHS
 Warranty 5 years



LED tube Prolumen T5 STRONG 1449 230V 25W 4000lm 140° 840

Product code 16678

Brand [Prolumen](#)
 Supply voltage 230V
 Output 25W
 Maximum output 25W/1m
 Luminous flux 4000lumens
 Luminaire's efficiency lm79 160W
 Correlated colour temperature pure white 4000K
 Lens angle 140
 Source of light [EPISTAR LED](#)
 Cri 80
 Lifespan 50000h
 Llmf tm21 L70B50 @25°C 50.000h
 Length 1449.0mm
 Diameter 22.0mm
 In package 1pc
 In box 25pcs
 Work environment indoor / outdoor use
 Operation temperature -20 - +40°C
 Certificates CE, RoHS
 Warranty 5 years



LED tube Prolumen T5 STRONG 1449 230V 25W 4000lm 140° 860

Product code 14663

Brand [Prolumen](#)
 Supply voltage 230V
 Output 25W
 Maximum output 25W/1m
 Luminous flux 4000lumens
 Luminaire's efficiency lm79 160W
 Correlated colour temperature cold white 6000K
 Lens angle 140
 Source of light [EPISTAR LED](#)
 Cri 80
 Lifespan 50000h
 Llmf tm21 L70B50 @25°C 50.000h
 Length 1449.0mm
 Diameter 22.0mm
 In package 1pc
 In box 25pcs
 Work environment indoor / outdoor use
 Operation temperature -20 - +40°C
 Certificates CE, RoHS
 Warranty 5 years



LED tube Prolumen T5 STRONG 549 230V 9W 1440lm 140° 840

Product code 15367

Brand [Prolumen](#)
 Supply voltage 230V
 Output 9W
 Maximum output 9W/1m
 Luminous flux 1440lumens
 Luminaire's efficiency lm79 160W
 Correlated colour temperature pure white 4000K
 Lens angle 140
 Source of light [EPISTAR LED](#)
 Cri 80
 Lifespan 50000h
 Length 549.0mm
 Diameter 22.0mm
 In package 1pc
 In box 25pcs
 Work environment indoor use
 Operation temperature -20 - +40°C
 Certificates CE, RoHS
 Warranty 5 years



LED tube Prolumen T8 STRONG 120cm 230V 18W 2600lm 120° 840

Product code 13410

Brand [Prolumen](#)
Supply voltage 230V
Power factor 0.95
Output 18W
Maximum output 18W/1m
Luminous flux 2600lumens
Luminaire's efficiency lm79 144W
Correlated colour temperature pure
white 4000K
Lens angle 120
Source of light [EPISTAR LED](#)
Cri 80
Sdcm - macadam ellipses 6
Lifespan 50000h
Height 26.0mm
Width 26.0mm
Length 1200.0mm
Diameter 26.0mm
In package 1pc
In box 25pcs
Casing material aluminium + plastic
Certificates CE, RoHS
Warranty 5 years



LED tube Prolumen T8 STRONG 120cm with adjustable power 230V 10/15W 3000lm 120° IP20 850

Product code 19702

Brand [Prolumen](#)
Supply voltage 230V
Power factor 0.95
Output 10/15W
Maximum output 15W/1m
Luminous flux 3000lumens
Correlated colour temperature pure
white 5000K
Lens angle 120
Source of light [EPISTAR LED](#)
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 1200.0mm
Diameter 26.0mm
In package 1pc
In box 50pcs
Casing material aluminium + plastic
Certificates CE, RoHS
Warranty 5 years



LED tube Prolumen T8 STRONG 150cm 230V 25W 4000lm 120° 840

Product code 13408

Brand [Prolumen](#)
Supply voltage 230V
Power factor 0.95
Output 25W
Maximum output 25W/1m
Luminous flux 4000lumens
Luminaire's efficiency lm79 160W
Correlated colour temperature pure
white 4000K
Lens angle 120
Source of light [EPISTAR LED](#)
Cri 80
Sdcm - macadam ellipses 6
Lifespan 50000h
Height 26.0mm
Width 26.0mm
Length 1500.0mm
Diameter 26.0mm
In box 25pcs
Casing material aluminium + plastic
Certificates CE
Warranty 5 years



LED tube Prolumen T8 STRONG 60cm 230V 9W 1440lm 120° 840

Product code 16663

Brand [Prolumen](#)
Supply voltage 230V
Power factor 0.95
Output 9W
Maximum output 9W/1m
Luminous flux 1440lumens
Luminaire's efficiency lm79 160W
Correlated colour temperature pure white 4000K
Lens angle 120
Source of light [EPISTAR LED](#)
Cri 80
Sdcm - macadam ellipses 6
Lifespan 50000h
Height 26.0mm
Width 26.0mm
Length 600.0mm
Diameter 26.0mm
In package 1pc
Casing material aluminium + plastic
Certificates CE, RoHS
Warranty 5 years



LED tube T8 ALU+PC 120cm 18W 1440lm G13 190° IP20 830

Product code 14659

Output 18W
Maximum output 18W/1m
Luminous flux 1440lumens
Luminaire's efficiency lm79 80W
Correlated colour temperature warm white 3000K
Lens angle 190
Socket G13
Cri 80
Protection class IP20
Length 1200.0mm
Diameter 28.5mm
In package 1pc
In box 20pcs



LED tube T8 ALU+PC 120cm 230V 20W 1700lm 170° IP20 840

Product code 13130

Supply voltage 230V
Output 20W
Maximum output 20W/1m
Luminous flux 1700lumens
Luminaire's efficiency lm79 85W
Correlated colour temperature pure white 4000K
Lens angle 170
Cri 80
Protection class IP20
Lifespan 25000h
Length 1200.0mm
Diameter 30.0mm
In package 1pc
In box 20pcs
Casing material aluminium + plastic
No. of switches 30000pcs
Operation temperature -25°C~40°C
Certificates CE



LED tube T8 ALU+PC 150cm 230V 24W 2040lm 170° IP20 840

Product code 13160

Supply voltage 230V
Output 24W
Maximum output 24W/1m
Luminous flux 2040lumens
Luminaire's efficiency lm79 85W
Correlated colour temperature pure white 4000K
Lens angle 170
Cri 80
Protection class IP20
Lifespan 25000h
Length 1500.0mm
Diameter 30.0mm
In package 1pc
In box 20pcs
Casing material aluminium + plastic
No. of switches 30000pcs
Operation temperature -25°C~40°C
Certificates CE



LED tube T8 T8 ALU+PC 60cm white 230V 10W 720lm 190° 830

Product code 16159

Supply voltage 230V
Output 10W
Maximum output 10W/1m
Luminous flux 720lumens
Luminaire's efficiency lm79 72W
Correlated colour temperature warm
white 3000K
Lens angle 190
Cri 80
Lifespan 25000h
Length 589.0mm
Diameter 30.0mm
In package 1pc
In box 20pcs
Casing colour white
Casing material aluminium + plastic
No. of switches 30000pcs
Work environment indoor use
Operation temperature -10~+40°C

