

## LED tube ECO T8 glass 600 230V 9W 1440lm G13 220° IP20 840

### Product code 17574

---

Brand ECO  
Supply voltage 230V  
Power factor 0.90  
Output 9W  
Maximum output 9W/1m  
Luminous flux 1440lumens  
Luminaire's efficiency lm79 160W  
Correlated colour temperature pure white 4000K  
Lens angle 220  
Socket G13  
Cri 80  
Sdcm - macadam ellipses 5  
Protection class IP20  
Lifespan 50000h  
Llmf tm21 L80B10 @25°C 50.000h  
Length 602.0mm  
Diameter 26.0mm  
In package 1pc  
In box 25pcs  
Casing material aluminum + glass  
Work environment indoor use  
Operation temperature -20° - +45°C  
Certificates CE, RoHS, ErP  
Warranty 3 years



LED tube to replace an old fluorescent tube with a more efficient light source. The LED tube casing is made of glass.

## **LED tube EMOS PROFI PLUS T8 GLASS 120cm 230V 15W 2550lm G13 260° IP20 840**

**Product code 22789**

Brand [EMOS](#)

Supply voltage 230V

Power factor 0.96

Output 15W

Maximum output 15W/1m

Luminous flux 2550lumens

Luminaire's efficiency lm79 170W

Correlated colour temperature pure  
white 4000K

Lens angle 260

Socket G13

Cri 80

Protection class IP20

Lifespan 50000h

Length 1213.0mm

Diameter 27.0mm

In package 1pc

In box 10pcs

Casing material glass

No. of switches 25000pcs

Operation temperature -25°C~40°C

Certificates CE

Warranty 5 years



## LED tube EMOS PROFI PLUS T8 GLASS 150cm 230V 20.6W 3100lm 260° IP20 840

**Product code 16574**

Brand [EMOS](#)  
Supply voltage 230V  
Power factor 0.96  
Output 20.6W  
Maximum output 20.6W/1m  
Luminous flux 3100lumens  
Luminaire's efficiency lm79 150W  
Correlated colour temperature pure white 4000K  
Lens angle 260  
Cri 80  
Protection class IP20  
Lifespan 50000h  
Length 1514.0mm  
Diameter 27.0mm  
In package 1pc  
In box 10pcs  
Casing material glass  
No. of switches 25000pcs  
Operation temperature -25°C~40°C  
Certificates CE  
Warranty 5 years



## LED tube EMOS PROFI PLUS T8 GLASS 150cm 230V 20.6W 3100lm 260° IP20 865

**Product code 17962**

Brand [EMOS](#)  
Supply voltage 230V  
Power factor 0.96  
Output 20.6W  
Maximum output 20.6W/1m  
Luminous flux 3100lumens  
Luminaire's efficiency lm79 150W  
Correlated colour temperature cold white 6500K  
Lens angle 260  
Cri 80  
Protection class IP20  
Lifespan 50000h  
Length 1514.0mm  
Diameter 27.0mm  
In package 1pc  
In box 10pcs  
Casing material glass  
No. of switches 25000pcs  
Operation temperature -25°C~40°C  
Certificates CE  
Warranty 5 years



## LED tube EMOS PROFI PLUS T8 GLASS 60cm 230V 7.3W 1100lm 260° IP20 840

**Product code 16575**

Brand [EMOS](#)  
Supply voltage 230V  
Power factor 0.96  
Output 7.3W  
Maximum output 7.3W/1m  
Luminous flux 1100lumens  
Luminaire's efficiency lm79 151W  
Correlated colour temperature pure white 4000K  
Lens angle 260  
Cri 80  
Protection class IP20  
Lifespan 50000h  
Length 603.0mm  
Diameter 27.0mm  
In package 1pc  
In box 10pcs  
Casing material glass  
No. of switches 25000pcs  
Operation temperature -25°C~40°C  
Certificates CE  
Warranty 5 years



## LED tube PHILIPS LED HF T5 230V 7W 1050lm 200° IP20 840

**Product code 22657**

Brand [PHILIPS](#)  
Supply voltage 230V  
Power factor 0.96  
Output 7W  
Maximum output 7W/1m  
Luminous flux 1050lumens  
Luminaire's efficiency lm79 150W  
Correlated colour temperature pure white 4000K  
Lens angle 200  
Cri 80  
Protection class IP20  
Lifespan 35000h  
Length 563.0mm  
Diameter 19.0mm  
Casing material glass  
No. of switches 50000pcs  
Operation temperature -25°C~40°C  
Certificates CE  
Warranty 5 years



## LED tube Prolumen T5 STRONG 1148 230V 18W 2880lm 140° 840

**Product code 16677**

Brand [Prolumen](#)  
 Supply voltage 230V  
 Output 18W  
 Maximum output 18W/1m  
 Luminous flux 2880lumens  
 Luminaire's efficiency lm79 160W  
 Correlated colour temperature pure white 4000K  
 Lens angle 140  
 Source of light [EPISTAR LED](#)  
 Cri 80  
 Lifespan 50000h  
 Llmf tm21 L70B50 @25°C 50.000h  
 Length 1148.0mm  
 Diameter 22.0mm  
 In package 1pc  
 In box 25pcs  
 Work environment indoor / outdoor use  
 Operation temperature -20 - +40°C  
 Certificates CE, RoHS  
 Warranty 5 years



## LED tube Prolumen T5 STRONG 1449 230V 25W 4000lm 140° 840

**Product code 16678**

Brand [Prolumen](#)  
 Supply voltage 230V  
 Output 25W  
 Maximum output 25W/1m  
 Luminous flux 4000lumens  
 Luminaire's efficiency lm79 160W  
 Correlated colour temperature pure white 4000K  
 Lens angle 140  
 Source of light [EPISTAR LED](#)  
 Cri 80  
 Lifespan 50000h  
 Llmf tm21 L70B50 @25°C 50.000h  
 Length 1449.0mm  
 Diameter 22.0mm  
 In package 1pc  
 In box 25pcs  
 Work environment indoor / outdoor use  
 Operation temperature -20 - +40°C  
 Certificates CE, RoHS  
 Warranty 5 years



## LED tube Prolumen T5 STRONG 1449 230V 25W 4000lm 140° 860

**Product code 14663**

Brand [Prolumen](#)  
 Supply voltage 230V  
 Output 25W  
 Maximum output 25W/1m  
 Luminous flux 4000lumens  
 Luminaire's efficiency lm79 160W  
 Correlated colour temperature cold white 6000K  
 Lens angle 140  
 Source of light [EPISTAR LED](#)  
 Cri 80  
 Lifespan 50000h  
 Llmf tm21 L70B50 @25°C 50.000h  
 Length 1449.0mm  
 Diameter 22.0mm  
 In package 1pc  
 In box 25pcs  
 Work environment indoor / outdoor use  
 Operation temperature -20 - +40°C  
 Certificates CE, RoHS  
 Warranty 5 years



## LED tube Prolumen T5 STRONG 549 230V 9W 1440lm 140° 840

**Product code 15367**

Brand [Prolumen](#)  
 Supply voltage 230V  
 Output 9W  
 Maximum output 9W/1m  
 Luminous flux 1440lumens  
 Luminaire's efficiency lm79 160W  
 Correlated colour temperature pure white 4000K  
 Lens angle 140  
 Source of light [EPISTAR LED](#)  
 Cri 80  
 Lifespan 50000h  
 Length 549.0mm  
 Diameter 22.0mm  
 In package 1pc  
 In box 25pcs  
 Work environment indoor use  
 Operation temperature -20 - +40°C  
 Certificates CE, RoHS  
 Warranty 5 years



## **LED tube Prolumen T8 STRONG 120cm 230V 18W 2600lm 120° 840**

**Product code 13410**

---

Brand [Prolumen](#)  
Supply voltage 230V  
Power factor 0.95  
Output 18W  
Maximum output 18W/1m  
Luminous flux 2600lumens  
Luminaire's efficiency lm79 144W  
Correlated colour temperature pure  
white 4000K  
Lens angle 120  
Source of light [EPISTAR LED](#)  
Cri 80  
Sdcm - macadam ellipses 6  
Lifespan 50000h  
Height 26.0mm  
Width 26.0mm  
Length 1200.0mm  
Diameter 26.0mm  
In package 1pc  
In box 25pcs  
Casing material aluminium + plastic  
Certificates CE, RoHS  
Warranty 5 years



## LED tube Prolumen T8 STRONG 120cm with adjustable power 230V 10/15W 3000lm 120° IP20 850

**Product code 19702**

Brand [Prolumen](#)  
Supply voltage 230V  
Power factor 0.95  
Output 10/15W  
Maximum output 15W/1m  
Luminous flux 3000lumens  
Correlated colour temperature pure white 5000K  
Lens angle 120  
Source of light [EPISTAR LED](#)  
Cri 80  
Sdcm - macadam ellipses 6  
Protection class IP20  
Lifespan 50000h  
Llmf tm21 L80B10 @25°C 50.000h  
Height 1200.0mm  
Diameter 26.0mm  
In package 1pc  
In box 50pcs  
Casing material aluminium + plastic  
Certificates CE, RoHS  
Warranty 5 years



## LED tube Prolumen T8 STRONG 150cm 230V 25W 4000lm 120° 840

**Product code 13408**

Brand [Prolumen](#)  
Supply voltage 230V  
Power factor 0.95  
Output 25W  
Maximum output 25W/1m  
Luminous flux 4000lumens  
Luminaire's efficiency lm79 160W  
Correlated colour temperature pure white 4000K  
Lens angle 120  
Source of light [EPISTAR LED](#)  
Cri 80  
Sdcm - macadam ellipses 6  
Lifespan 50000h  
Height 26.0mm  
Width 26.0mm  
Length 1500.0mm  
Diameter 26.0mm  
In box 25pcs  
Casing material aluminium + plastic  
Certificates CE  
Warranty 5 years



## LED tube Prolumen T8 STRONG 60cm 230V 9W 1440lm 120° 840

**Product code 16663**

---

Brand [Prolumen](#)  
Supply voltage 230V  
Power factor 0.95  
Output 9W  
Maximum output 9W/1m  
Luminous flux 1440lumens  
Luminaire's efficiency lm79 160W  
Correlated colour temperature pure white 4000K  
Lens angle 120  
Source of light [EPISTAR LED](#)  
Cri 80  
Sdcm - macadam ellipses 6  
Lifespan 50000h  
Height 26.0mm  
Width 26.0mm  
Length 600.0mm  
Diameter 26.0mm  
In package 1pc  
Casing material aluminium + plastic  
Certificates CE, RoHS  
Warranty 5 years



## LED tube T8 ALU+PC 120cm 18W 1440lm G13 190° IP20 830

**Product code 14659**

---

Output 18W  
Maximum output 18W/1m  
Luminous flux 1440lumens  
Luminaire's efficiency lm79 80W  
Correlated colour temperature warm white 3000K  
Lens angle 190  
Socket G13  
Cri 80  
Protection class IP20  
Length 1200.0mm  
Diameter 28.5mm  
In package 1pc  
In box 20pcs



## LED tube T8 ALU+PC 120cm 230V 20W 1700lm 170° IP20 840

### Product code 13130

---

Supply voltage 230V  
Output 20W  
Maximum output 20W/1m  
Luminous flux 1700lumens  
Luminaire's efficiency lm79 85W  
Correlated colour temperature pure white 4000K  
Lens angle 170  
Cri 80  
Protection class IP20  
Lifespan 25000h  
Length 1200.0mm  
Diameter 30.0mm  
In package 1pc  
In box 20pcs  
Casing material aluminium + plastic  
No. of switches 30000pcs  
Operation temperature -25°C~40°C  
Certificates CE



## LED tube T8 ALU+PC 150cm 230V 24W 2040lm 170° IP20 840

### Product code 13160

---

Supply voltage 230V  
Output 24W  
Maximum output 24W/1m  
Luminous flux 2040lumens  
Luminaire's efficiency lm79 85W  
Correlated colour temperature pure white 4000K  
Lens angle 170  
Cri 80  
Protection class IP20  
Lifespan 25000h  
Length 1500.0mm  
Diameter 30.0mm  
In package 1pc  
In box 20pcs  
Casing material aluminium + plastic  
No. of switches 30000pcs  
Operation temperature -25°C~40°C  
Certificates CE



## **LED tube T8 T8 ALU+PC 60cm white 230V 10W 720lm 190° 830**

### **Product code 16159**

---

Supply voltage 230V  
Output 10W  
Maximum output 10W/1m  
Luminous flux 720lumens  
Luminaire's efficiency lm79 72W  
Correlated colour temperature warm  
white 3000K  
Lens angle 190  
Cri 80  
Lifespan 25000h  
Length 589.0mm  
Diameter 30.0mm  
In package 1pc  
In box 20pcs  
Casing colour white  
Casing material aluminium + plastic  
No. of switches 30000pcs  
Work environment indoor use  
Operation temperature -10~+40°C

