Battery device EMconverter LED BASIC 204 MH/LiFePO4 50-250V + Battery LiFePO4 3,0Ah 3,2V 2B CON

Product code 15389

Weight 163 g
In package 1pc
Warranty 5 years



Battery device EMconverter LED BASIC 204 NiCd/NiMH 10-50V + Battery Ni-Cd 4A 55 4,8V , 4,5Ah

Product code 15480

Weight 607 g
Package weight 615 g
Warranty 5 years



Battery INTELIGHT LiFePO4 2x18650 6,4V 1600mAh, pak.1S2P, przew

Product code 23842

Brand INTELIGHT
In package 1pc

INTELIGHT battery for connecting to emergency lighting.



Battery INTELIGHT LifePO4 6,4V 1600mAh

Product code 19596



Brand INTELIGHT
In package 1pc

INTELIGHT battery for connecting to emergency lighting.

Battery INTELIGHT LiFePO4 battery pack 6.4V 600mAh

Product code 23602



Brand INTELIGHT
Rated current 600mA
Height 15.0mm
Width 29.0mm
Length 52.5mm
In package 1pc

INTELIGHT battery for connecting to emergency lighting.

Battery device INTELIGHT PRIMUS LED A9/A 2h MT + NiCd 3xC 3,6V 2,5Ah 230V IP20

Product code 16641



Brand INTELIGHT
Supply voltage 230V
Output voltage 230V
Protection class IP20
Height 36.0mm
Width 42.0mm
Length 180.0mm
Weight 432 g
Package weight 485 g
In package 1pc
Work environment indoor use
Operation temperature +5 ~ +50°C
Warranty 1 years

Battery device INTELIGHT PRIMUS LED A9/A 3h MT + NiCd 3xC 3,6V 4,0Ah 230V IP20

Product code 17955

Brand INTELIGHT
Supply voltage 230V
Output voltage 230V
Protection class IP20
Height 36.0mm
Width 42.0mm
Length 180.0mm
Weight 432 g
Package weight 485 g
In package 1pc
Work environment indoor use
Operation temperature +5 ~ +50°C
Warranty 1 years



Battery device INTELIGHT Primus LED D10.180/G 2h + NiCd 3xC 3,6V 2500mAh 230V IP20

Product code 21975

Brand INTELIGHT
Supply voltage 230V
Output voltage 230V
Protection class IP20
Height 36.0mm
Width 42.0mm
Length 180.0mm
Weight 432 g
Package weight 485 g
In package 1pc
Work environment indoor use
Operation temperature +5 ~ +50°C
Warranty 1 years



Battery device INTELIGHT Primus LED D2/A 2h MT + NiCd 3xC 3,6V 2,5Ah 98865 230V IP20

Product code 17230

Brand INTELIGHT
Supply voltage 230V
Output voltage 12-24V
Protection class IP20
Height 36.0mm
Width 42.0mm
Length 180.0mm
Weight 432 g
Package weight 485 g
In package 1pc
Work environment indoor use
Operation temperature +5 ~ +50°C
Warranty 1 years



Battery device INTELIGHT Primus LED D4/A 3h MT + NiCd 3xD 3,6V 4,0Ah 230V IP20

Product code 20850

Brand INTELIGHT
Supply voltage 230V
Output voltage 230V
Protection class IP20
Height 36.0mm
Width 42.0mm
Length 180.0mm
Weight 558 g
Package weight 609 g
In package 1pc
Work environment indoor use
Operation temperature +5 ~ +50°C
Warranty 1 years



Battery device INTELIGHT PRIMUS LED D6/A 3h MT + NiCd 3xD 3,6V 4,0Ah 230V IP20

Product code 15334



Brand INTELIGHT
Supply voltage 230V
Protection class IP20
Height 36.0mm
Width 42.0mm
Length 151.0mm
Weight 559 g
Package weight 609 g
In package 1pc
Work environment indoor use
Operation temperature +5 ~ +50°C
Warranty 1 years

Battery device INTELIGHT Primus LED D9/A 2h MT + NiCd 3xC 3,6V 2,5Ah 230V IP20

Product code 17522



Brand INTELIGHT
Supply voltage 230V
Output voltage 230V
Protection class IP20
Height 36.0mm
Width 42.0mm
Length 180.0mm
Weight 558 g
Package weight 609 g
In package 1pc
Work environment indoor use
Operation temperature +5 ~ +50°C
Warranty 1 years

Battery device INTELIGHT PRIMUS LED D9/A 3h MT + NiCd 3xD 3,6V 4,0Ah 230V IP20

Product code 16193

Brand INTELIGHT
Supply voltage 230V
Output voltage 230V
Protection class IP20
Height 36.0mm
Width 42.0mm
Length 180.0mm
Weight 558 g
Package weight 609 g
In package 1pc
Work environment indoor use
Operation temperature +5 ~ +50°C
Warranty 1 years



Battery device LIFUD 120min LF-GSP055YC 230V 40W

Product code 14549

Brand LIFUD
Supply voltage 230V
Output voltage 27-40V
Output 40W
Maximum output 40W/1m
Rated current 1100mA
Certificates CE, RoHS

