

Battery device EMconverter LED BASIC 204 MH/LiFePO4 50-250V + Battery LiFePO4 3,0Ah 3,2V 2B CON

Product code 15389

Weight 163 g
In package 1pc
Warranty 5 years



Battery device EMconverter LED BASIC 204 NiCd/NiMH 10-50V + Battery Ni-Cd 4A 55 4,8V , 4,5Ah

Product code 15480

Weight 607 g
Package weight 615 g
Warranty 5 years



Battery INTELIGHT LifePO4 6,4V 1500mAh

Product code 17534

Brand [INTELIGHT](#)
In package 1pc

INTELIGHT battery for connecting to
emergency lighting.



Battery INTELIGHT LifePO4 6,4V 1600mAh

Product code 19596

Brand [INTELIGHT](#)
In package 1pc

INTELIGHT battery for connecting to emergency lighting.



Battery device INTELIGHT PRIMUS LED A9/A 2h MT + NiCd 3xC 3,6V 2,5Ah 230V IP20

Product code 16641

Brand [INTELIGHT](#)
Supply voltage 230V
Output voltage 230V
Protection class IP20
Height 36.0mm
Width 42.0mm
Length 180.0mm
Weight 432 g
Package weight 485 g
In package 1pc
Work environment indoor use
Operation temperature +5 ~ +50°C
Warranty 1 years



Battery device INTELIGHT PRIMUS LED A9/A 3h MT + NiCd 3xC 3,6V 4,0Ah 230V IP20

Product code 17955

Brand [INTELIGHT](#)
Supply voltage 230V
Output voltage 230V
Protection class IP20
Height 36.0mm
Width 42.0mm
Length 180.0mm
Weight 432 g
Package weight 485 g
In package 1pc
Work environment indoor use
Operation temperature +5 ~ +50°C
Warranty 1 years



Battery device INTELIGHT Primus LED D10.180/G 2h + NiCd 3xC 3,6V 2500mAh 230V IP20

Product code 21975

Brand [INTELIGHT](#)

Supply voltage 230V

Output voltage 230V

Protection class IP20

Height 36.0mm

Width 42.0mm

Length 180.0mm

Weight 432 g

Package weight 485 g

In package 1pc

Work environment indoor use

Operation temperature +5 ~ +50°C

Warranty 1 years



Battery device INTELIGHT Primus LED D2/A 2h MT + NiCd 3xC 3,6V 2,5Ah 98865 230V IP20

Product code 17230

Brand [INTELIGHT](#)

Supply voltage 230V

Output voltage 12-24V

Protection class IP20

Height 36.0mm

Width 42.0mm

Length 180.0mm

Weight 432 g

Package weight 485 g

In package 1pc

Work environment indoor use

Operation temperature +5 ~ +50°C

Warranty 1 years



Battery device INTELIGHT Primus LED D4/A 3h MT + NiCd 3xD 3,6V 4,0Ah 230V IP20

Product code 20850

Brand [INTELIGHT](#)

Supply voltage 230V

Output voltage 230V

Protection class IP20

Height 36.0mm

Width 42.0mm

Length 180.0mm

Weight 558 g

Package weight 609 g

In package 1pc

Work environment indoor use

Operation temperature +5 ~ +50°C

Warranty 1 years



Battery device INTELIGHT PRIMUS LED D6/A 3h MT + NiCd 3xD 3,6V 4,0Ah 230V IP20

Product code 15334

Brand [INTELIGHT](#)

Supply voltage 230V

Protection class IP20

Height 36.0mm

Width 42.0mm

Length 151.0mm

Weight 559 g

Package weight 609 g

In package 1pc

Work environment indoor use

Operation temperature +5 ~ +50°C

Warranty 1 years



Battery device INTELIGHT Primus LED D9/A 2h MT + NiCd 3xC 3,6V 2,5Ah 230V IP20

Product code 17522

Brand [INTELIGHT](#)

Supply voltage 230V

Output voltage 230V

Protection class IP20

Height 36.0mm

Width 42.0mm

Length 180.0mm

Weight 558 g

Package weight 609 g

In package 1pc

Work environment indoor use

Operation temperature +5 ~ +50°C

Warranty 1 years



Battery device INTELIGHT PRIMUS LED D9/A 3h MT + NiCd 3xD 3,6V 4,0Ah 230V IP20

Product code 16193

Brand [INTELIGHT](#)

Supply voltage 230V

Output voltage 230V

Protection class IP20

Height 36.0mm

Width 42.0mm

Length 180.0mm

Weight 558 g

Package weight 609 g

In package 1pc

Work environment indoor use

Operation temperature +5 ~ +50°C

Warranty 1 years



