

## Battery device EMconverter LED BASIC 204 MH/LiFePO4 50-250V + Battery LiFePO4 3,0Ah 3,2V 2B CON

**Product code 15389**

Weight 163 g  
In package 1pc  
Warranty 5 years



## Battery device EMconverter LED BASIC 204 NiCd/NiMH 10-50V + Battery Ni-Cd 4A 55 4,8V , 4,5Ah

**Product code 15480**

Weight 607 g  
Package weight 615 g  
Warranty 5 years



## Battery INTELIGHT LifePO4 6,4V 1500mAh

**Product code 17534**

Brand [INTELIGHT](#)  
In package 1pc

INTELIGHT battery for connecting to  
emergency lighting.



## Battery INTELIGHT LifePO4 6,4V 1600mAh

**Product code 19596**

Brand [INTELIGHT](#)  
In package 1pc

INTELIGHT battery for connecting to emergency lighting.



## Battery device INTELIGHT PRIMUS LED A9/A 2h MT + NiCd 3xC 3,6V 2,5Ah 230V IP20

**Product code 16641**

Brand [INTELIGHT](#)  
Supply voltage 230V  
Output voltage 230V  
Protection class IP20  
Height 36.0mm  
Width 42.0mm  
Length 180.0mm  
Weight 432 g  
Package weight 485 g  
In package 1pc  
Work environment indoor use  
Operation temperature +5 ~ +50°C  
Warranty 1 years



## Battery device INTELIGHT PRIMUS LED A9/A 3h MT + NiCd 3xC 3,6V 4,0Ah 230V IP20

**Product code 17955**

Brand [INTELIGHT](#)  
Supply voltage 230V  
Output voltage 230V  
Protection class IP20  
Height 36.0mm  
Width 42.0mm  
Length 180.0mm  
Weight 432 g  
Package weight 485 g  
In package 1pc  
Work environment indoor use  
Operation temperature +5 ~ +50°C  
Warranty 1 years



## Battery device INTELIGHT Primus LED D10.180/G 2h + NiCd 3xC 3,6V 2500mAh 230V IP20

**Product code 21975**

Brand [INTELIGHT](#)

Supply voltage 230V

Output voltage 230V

Protection class IP20

Height 36.0mm

Width 42.0mm

Length 180.0mm

Weight 432 g

Package weight 485 g

In package 1pc

Work environment indoor use

Operation temperature +5 ~ +50°C

Warranty 1 years



## Battery device INTELIGHT Primus LED D2/A 2h MT + NiCd 3xC 3,6V 2,5Ah 98865 230V IP20

**Product code 17230**

Brand [INTELIGHT](#)

Supply voltage 230V

Output voltage 12-24V

Protection class IP20

Height 36.0mm

Width 42.0mm

Length 180.0mm

Weight 432 g

Package weight 485 g

In package 1pc

Work environment indoor use

Operation temperature +5 ~ +50°C

Warranty 1 years



## Battery device INTELIGHT Primus LED D4/A 3h MT + NiCd 3xD 3,6V 4,0Ah 230V IP20

**Product code 20850**

Brand [INTELIGHT](#)

Supply voltage 230V

Output voltage 230V

Protection class IP20

Height 36.0mm

Width 42.0mm

Length 180.0mm

Weight 558 g

Package weight 609 g

In package 1pc

Work environment indoor use

Operation temperature +5 ~ +50°C

Warranty 1 years



## Battery device INTELIGHT PRIMUS LED D6/A 3h MT + NiCd 3xD 3,6V 4,0Ah 230V IP20

**Product code 15334**

Brand [INTELIGHT](#)

Supply voltage 230V

Protection class IP20

Height 36.0mm

Width 42.0mm

Length 151.0mm

Weight 559 g

Package weight 609 g

In package 1pc

Work environment indoor use

Operation temperature +5 ~ +50°C

Warranty 1 years



## Battery device INTELIGHT Primus LED D9/A 2h MT + NiCd 3xC 3,6V 2,5Ah 230V IP20

**Product code 17522**

Brand [INTELIGHT](#)

Supply voltage 230V

Output voltage 230V

Protection class IP20

Height 36.0mm

Width 42.0mm

Length 180.0mm

Weight 558 g

Package weight 609 g

In package 1pc

Work environment indoor use

Operation temperature +5 ~ +50°C

Warranty 1 years



## Battery device INTELIGHT PRIMUS LED D9/A 3h MT + NiCd 3xD 3,6V 4,0Ah 230V IP20

**Product code 16193**

Brand [INTELIGHT](#)

Supply voltage 230V

Output voltage 230V

Protection class IP20

Height 36.0mm

Width 42.0mm

Length 180.0mm

Weight 558 g

Package weight 609 g

In package 1pc

Work environment indoor use

Operation temperature +5 ~ +50°C

Warranty 1 years



## Battery device LIFUD 120min LF-GSP055YC 230V 40W

**Product code 14549**

Brand LIFUD  
Supply voltage 230V  
Output voltage 27-40V  
Output 40W  
Maximum output 40W/1m  
Rated current 1100mA  
Certificates CE, RoHS

