Industrial light Northcliffe BARAT LED2X3200 C116 T840 PC/PC OP IC EX 230V 55W 6947lm IP66 840

Product code 15796

Brand Northcliffe
Supply voltage 230V
Output 55W
Maximum output 55W/1m
Luminous flux 6947lumens
Luminaire’s efficiency 126W
Correlated colour temperature pure white 4000K
CRI 80
Protection class IP66
LLMF TM21 L80B10 @25°C 50.000h
Height 111.0mm
Width 146.0mm
Length 1572.0mm
Weight 3.3 kg
Impact resistance IK08
Warranty 3 years



High-quality LED ceiling light! 4000K LED lights provide clear and sharp light, perfect for illuminating shops and other commercial spaces. IP66 protection class ensures strong waterproofing for the light, allowing it to be used outdoors, even under direct water pressure. If the light malfunctions within 3 years, it will be replaced with a new one. Symbols: II 3G Ex nA IIC T6 Gc; II 3D Ex tD IIIC T85°C You can find the best selection of industrial lighting in the LED house product range!

Industrial light Northcliffe Barat LED2x4700 C117 T840 PC/PC OP IC Ex 230V 81W 9421lm IP66 840

Product code 18035

Brand Northcliffe
Supply voltage 230V
Output 81W
Maximum output 81W/1m
Luminous flux 9421lumens
Luminaire’s efficiency 116W
Correlated colour temperature pure white 4000K
CRI 80
Protection class IP66
LLMF TM21 L80B50 @25°C 75.000h
Height 111.0mm
Width 146.0mm
Length 1572.0mm
Weight 3.3 kg
Impact resistance IK08
Warranty 3 years



High-quality LED ceiling light! 4000K LED lights provide clear and sharp light, perfect for illuminating shops and other commercial spaces. IP66 protection class ensures strong waterproofing for the light, allowing it to be used outdoors, even under direct water pressure. If the light malfunctions within 3 years, it will be replaced with a new one. Symbols: II 3G Ex nA IIC T6 Gc; II 3D Ex tD IIIC T85°C You can find the best selection of industrial lighting in the LED house product range!

Explosion-proof light Prolumen Elegance EX 1200 DALI gray 230V 60W 9000lm 120° IP66 DALI 840

Product code 23599 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable DALI
Output 60W
Maximum output 60W/1m
Luminous flux 9000lumens
Luminaire’s efficiency 150W
Correlated colour temperature pure white 4000K
Lens angle 120
Source of light BRIDGELUX LED
CRI 80
SDCM - MacAdam Ellipses 6
Protection class IP66
Lifespan 50000h
Height 58.0mm
Width 70.0mm
Length 1200.0mm
Casing colour gray
Casing material aluminium
Impact resistance IK10
Work environment indoor / outdoor use
Warranty 5 years



Explosion-proof LED luminaire is a specially designed luminaire intended for use in hazardous environments where explosive gases, vapors, or dust clouds may occur. Created according to strict explosion-proof standards and certifications to ensure their safe use in such risk situations. Certificates of explosion-proof luminaire according to international standards: II 2G Ex eb mb IIC T4 Gb II 2D EX tb IIIC T(95C) Db You can find the best assortment of industrial lighting in the LED house product range!

Explosion-proof light Prolumen Elegance EX 1200 gray 230V 60W 9000lm 120° IP66 840

Product code 17029

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 60W
Maximum output 60W/1m
Luminous flux 9000lumens
Luminaire’s efficiency 150W
Correlated colour temperature pure white 4000K
Lens angle 120
Source of light BRIDGELUX LED
CRI 80
SDCM - MacAdam Ellipses 6
Protection class IP66
Lifespan 50000h
Height 58.0mm
Width 70.0mm
Length 1200.0mm
Casing colour gray
Casing material aluminium
Impact resistance IK10
Work environment indoor / outdoor use
Warranty 5 years



Explosion-proof LED luminaire is a specially designed luminaire intended for use in hazardous environments where explosive gases, vapors, or dust clouds may occur. Created according to strict explosion-proof standards and certifications to ensure their safe use in such risk situations. Certificates of explosion-proof luminaire according to international standards: II 2G Ex eb mb IIC T4 Gb II 2D EX tb IIIC T(95C) Db You can find the best assortment of industrial lighting in the LED house product range!

Explosion-proof light Prolumen Elegance EX 600 gray 230V 20W 3000lm 120° IP66 840

Product code 17026

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 20W
Maximum output 20W/1m
Luminous flux 3000lumens
Luminaire’s efficiency 150W
Correlated colour temperature pure white 4000K
Lens angle 120
Source of light BRIDGELUX LED
CRI 80
SDCM - MacAdam Ellipses 6
Protection class IP66
Lifespan 50000h
Height 58.0mm
Width 70.0mm
Length 600.0mm
Casing colour gray
Casing material aluminium
Impact resistance IK10
Work environment indoor / outdoor use
Warranty 5 years



Explosion-proof LED luminaire is a specially designed luminaire intended for use in hazardous environments where explosive gases, vapors, or dust clouds may occur. Created according to strict explosion-proof standards and certifications to ensure their safe use in such risk situations. Certificates of explosion-proof luminaire according to international standards: II 2G Ex eb mb IIC T4 Gb II 2D EX tb IIIC T(95C) Db You can find the best assortment of industrial lighting in the LED house product range!

Explosion-proof light Prolumen Elegance EX 600 gray 230V 40W 6000lm 120° IP66 840

Product code 17027

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 40W
Maximum output 40W/1m
Luminous flux 6000lumens
Luminaire’s efficiency 150W
Correlated colour temperature pure white 4000K
Lens angle 120
Source of light BRIDGELUX LED
CRI 80
SDCM - MacAdam Ellipses 6
Protection class IP66
Lifespan 50000h
Height 58.0mm
Width 70.0mm
Length 600.0mm
Casing colour gray
Casing material aluminium
Impact resistance IK10
Work environment indoor / outdoor use
Warranty 5 years



Explosion-proof LED luminaire is a specially designed luminaire intended for use in hazardous environments where explosive gases, vapors, or dust clouds may occur. Created according to strict explosion-proof standards and certifications to ensure their safe use in such risk situations. Certificates of explosion-proof luminaire according to international standards: II 2G Ex eb mb IIC T4 Gb II 2D EX tb IIIC T(95C) Db You can find the best assortment of industrial lighting in the LED house product range!

Explosion-proof light Prolumen Matrix 1400 230V 60W 8400lm 120° IP66 850

Product code 18036

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 60W
Maximum output 60W/1m
Luminous flux 8400lumens
Luminaire’s efficiency 140W
Correlated colour temperature pure white 5000K
Lens angle 120
Source of light BRIDGELUX LED
CRI 80
SDCM - MacAdam Ellipses 5
Protection class IP66
Lifespan 50000h
Height 63.0mm
Width 115.0mm
Length 1335.0mm
Power supply TRIDONIC
Impact resistance IK10
Work environment indoor / outdoor use
Warranty 5 years



Explosion-proof LED luminaire is a specially designed luminaire intended for use in hazardous environments where explosive gases, vapors, or dust clouds may occur. Installed, for example, in power plants, gas stations, tunnels, etc. Created according to strict explosion-proof standards and certifications to ensure their safe use in such risky situations. Luminaire explosion-proof certifications according to international standards: II 2 G Ex e mb IIC T6 Gc Parima tööstusvalgustuse sortimendi leiad LED house tootevalikust!

Explosion-proof light Prolumen Matrix 230V 80W 9600lm 120° IP65 840

Product code 15337

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 80W
Maximum output 80W/1m
Luminous flux 9600lumens
Luminaire’s efficiency 120W
Correlated colour temperature pure white 4000K
Lens angle 120
Source of light BRIDGELUX LED
CRI 80
SDCM - MacAdam Ellipses 5
Protection class IP65
Lifespan 50000h
Height 63.0mm
Width 115.0mm
Length 1335.0mm
Power supply LIFUD
Impact resistance IK10
Work environment indoor / outdoor use
Warranty 5 years



Explosion-proof LED luminaire is a specially designed luminaire intended for use in hazardous environments where explosive gases, vapors, or dust clouds may occur. Installed, for example, in power plants, gas stations, tunnels, etc. Created according to strict explosion-proof standards and certifications to ensure their safe use in such risky situations. Luminaire explosion-proof certifications according to international standards: II 2 G Ex e mb IIC T6 Gc Parima tööstusvalgustuse sortimendi leiad LED house tootevalikust!