

Power cable 5m toitepistikuga 2x2,5mm²

Product code 14964

Length 5000.0mm

Cable A for linking, 20cm 4pin

Product code 16981

Length 200.0mm



Cable A power cable, 20cm

Product code 15406

Length 200.0mm



Cable A power cable, 20cm 4pin

Product code 16979

Length 200.0mm



Mounting clip A series, fixed, with magnet

Product code 14960

Height 8.0mm
Width 18.0mm
Length 20.0mm



Cable B for linking, 30cm

Product code 15023



Cable B series power, 15cm

Product code 15043



LED luminaire REVAL BULB A seeria 560 24V 7W 250lm CRI80 120° IP40 RGB

Product code 16978

Brand [REVAL BULB](#)

Supply voltage 24V

Output 7W

Maximum output 7W/1m

Luminous flux 250lumens

Luminaire's efficiency lm79 36W

Correlated colour temperature RGB

RGB

Lens angle 120

Cri 80

Protection class IP40

Lifespan 50000h

Height 15.5mm

Width 20.0mm

Length 560.0mm

Work environment indoor use

Operation temperature -40 ~ +50°C

Certificates CE, RoHS


Warranty 2 years



LED luminaire REVAL BULB A series 1160 24V 18W 1440lm 120° IP40 840

Product code 14958

Brand [REVAL BULB](#)
Supply voltage 24V
Output 18W
Maximum output 18W/1m
Luminous flux 1440lumens
Luminaire's efficiency lm79 80W
Correlated colour temperature pure white 4000K
Lens angle 120
Cri 80
Protection class IP40
Lifespan 35000h
Height 16.0mm
Width 20.0mm
Length 1160.0mm
Work environment indoor use
Certificates CE, RoHS
Warranty 2 years



LED luminaire REVAL BULB A series 860 24V 13W 1040lm 120° IP40 840

Product code 14961

Brand [REVAL BULB](#)
Supply voltage 24V
Output 13W
Maximum output 13W/1m
Luminous flux 1040lumens
Luminaire's efficiency lm79 80W
Correlated colour temperature pure white 4000K
Lens angle 120
Cri 80
Protection class IP40
Lifespan 35000h
Height 16.0mm
Width 20.0mm
Length 860.0mm
Work environment indoor use
Certificates CE, RoHS



