

## Power cable 5m toitepistikuga 2x2,5mm<sup>2</sup>

**Product code 14964**

---

Length 5000.0mm

## Cable A for linking, 20cm 4pin

**Product code 16981**

---

Length 200.0mm



## Cable A power cable, 20cm

**Product code 15406**

---

Length 200.0mm



## Cable A power cable, 20cm 4pin

**Product code 16979**

---

Length 200.0mm



## Mounting clip A series, fixed, with magnet

**Product code 14960**

---



## Cable B for linking, 30cm

**Product code 15023**

---



## Cable B series power, 15cm

**Product code 15043**

---



## LED luminaire REVAL BULB A seeria 560 24V 7W 250lm CRI80 120° IP40 RGB

**Product code 16978**

---

Brand [REVAL BULB](#)

Supply voltage 24V

Output 7W

Maximum output 7W/1m

Luminous flux 250lumens

Luminaire's efficiency lm79 36W

Correlated colour temperature RGB

RGB

Lens angle 120

Cri 80

Protection class IP40

Lifespan 50000h

Height 15.5mm

Width 20.0mm

Length 560.0mm

Work environment indoor use

Operation temperature -40 ~ +50°C

Certificates CE, RoHS

Warranty 2 years



## LED luminaire REVAL BULB A series 1160 24V 18W 1440lm 120° IP40 840

**Product code 14958**

Brand [REVAL BULB](#)

Supply voltage 24V

Output 18W

Maximum output 18W/1m

Luminous flux 1440lumens

Luminaire's efficiency lm79 80W

Correlated colour temperature pure white 4000K

Lens angle 120

Cri 80

Protection class IP40

Lifespan 35000h

Height 16.0mm

Width 20.0mm

Length 1160.0mm

Work environment indoor use

Certificates CE, RoHS

Warranty 2 years



## LED luminaire REVAL BULB A series 860 24V 13W 1040lm 120° IP40 840

**Product code 14961**

Brand [REVAL BULB](#)

Supply voltage 24V

Output 13W

Maximum output 13W/1m

Luminous flux 1040lumens

Luminaire's efficiency lm79 80W

Correlated colour temperature pure white 4000K

Lens angle 120

Cri 80

Protection class IP40

Lifespan 35000h

Height 16.0mm

Width 20.0mm

Length 860.0mm

Work environment indoor use

Certificates CE, RoHS



