

LED bulb CB 230V 1W 90lm GU10 120° IP20 830

Product code 16501

Supply voltage 230V
Output 1W
Maximum output 1W/1m
Luminous flux 90lumens
Luminaire's efficiency lm79 90W
Correlated colour temperature warm white 3000K
Lens angle 120
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 10000h
Height 56.0mm
Diameter 50.0mm
Weight 40 g
In package 1pc
In box 100pcs
No. of switches 10000pcs
Work environment indoor use
Certificates CE
Warranty 2 years



LED bulb CB 230V 9W 1040lm GU10 120° IP20 830

Product code 20851

Supply voltage 230V
Output 9W
Maximum output 9W/1m
Luminous flux 1040lumens
Luminaire's efficiency lm79 116W
Correlated colour temperature warm white 3000K
Lens angle 120
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 10000h
Height 56.0mm
Diameter 50.0mm
Weight 40 g
In package 1pc
In box 100pcs
No. of switches 10000pcs
Work environment indoor use
Certificates CE
Warranty 2 years



LED bulb EMOS CLASSIC MR16 230V 3W 345lm GU10 100° IP20 840

Product code 18217

Brand [EMOS](#)
 Supply voltage 230V
 Power factor 0.52
 Output 3W
 Maximum output 3W/1m
 Luminous flux 345lumens
 Luminaire's efficiency lm79 115W
 Correlated colour temperature pure white 4000K
 Lens angle 100
 Socket GU10
 Cri 80
 Protection class IP20
 Lifespan 30000h
 Height 52.0mm
 Diameter 50.0mm
 In package 1pc
 In box 10pcs
 No. of switches 25000pcs
 Work environment indoor use
 Certificates CE, RoHS
 Warranty 3 years



LED bulb LEDVANCE PAR16 230V 6.1W 575lm GU10 60° IP20 930

Product code 23119

Brand LEDVANCE
 Supply voltage 230V
 Output 6.1W
 Maximum output 6.1W/1m
 Luminous flux 575lumens
 Luminaire's efficiency lm79 94W
 Correlated colour temperature warm white 3000K
 Lens angle 60
 Socket GU10
 Cri 90
 En62471 1
 Protection class IP20
 Lifespan 15000h
 Height 50.0mm
 Diameter 50.0mm
 Operation temperature -20° - +40°C
 Certificates CE, UKCA, EAC



LED bulb LEDVANCE Parathom PAR16 230V 4.5W 350lm GU10 36° IP20 827

Product code 19184

Brand LEDVANCE
 Supply voltage 230V
 Output 4.5W
 Maximum output 4.5W/1m
 Luminous flux 350lumens
 Luminaire's efficiency lm79 78W
 Correlated colour temperature warm white 2700K
 Lens angle 36
 Socket GU10
 Cri 80
 Sdcm - macadam ellipses 6
 En62471 1
 Protection class IP20
 Lifespan 15000h
 Height 50.0mm
 Diameter 50.0mm
 No. of switches 10000pcs
 Operation temperature -20° - +40°C
 Certificates CE, UKCA, EAC



LED bulb LEDVANCE Star PAR16 230V 6.9W 620lm GU10 120° IP20 827

Product code 19185

Brand LEDVANCE
 Supply voltage 230V
 Output 6.9W
 Maximum output 6.9W/1m
 Luminous flux 620lumens
 Luminaire's efficiency lm79 90W
 Correlated colour temperature warm white 2700K
 Lens angle 120
 Socket GU10
 Cri 80
 Sdcm - macadam ellipses 6
 En62471 1
 Protection class IP20
 Lifespan 15000h
 Height 50.0mm
 Diameter 50.0mm
 No. of switches 10000pcs
 Operation temperature -20° - +40°C
 Certificates CE, UKCA, EAC



LED bulb LEDVANCE Superstar Plus PAR16 230V 6W 575lm GU10 120° TRIAC 927

Product code 19182 TRIAC dimmable

Brand LEDVANCE
 Supply voltage 230V
 Dimmable TRIAC
 Output 6W
 Maximum output 6W/1m
 Luminous flux 575lumens
 Luminaire's efficiency lm79 96W
 Correlated colour temperature warm white 2700K
 Lens angle 120
 Socket GU10
 Cri 90
 Sdcm - macadam ellipses 5
 En62471 1
 Lifespan 25000h
 Height 50.0mm
 Diameter 50.0mm
 Operation temperature -20° - +40°C
 Certificates CE, UKCA, EAC



LED bulb LUMILEDS PAR16 230V 8W 650lm GU10 36° IP20 TRIAC 830

Product code 23122 TRIAC dimmable

Brand [LUMILEDS](#)
 Supply voltage 230V
 Dimmable TRIAC
 Output 8W
 Maximum output 8W/1m
 Luminous flux 650lumens
 Luminaire's efficiency lm79 81W
 Correlated colour temperature warm white 3000K
 Lens angle 36
 Socket GU10
 Cri 80
 En62471 1
 Protection class IP20
 Lifespan 15000h
 Operation temperature -20° - +40°C
 Certificates CE, UKCA, EAC



LED bulb NB 230V 1W 90lm GU10 120° IP20 840

Product code 16488

Supply voltage 230V
Output 1W
Maximum output 1W/1m
Luminous flux 90lumens
Luminaire's efficiency lm79 90W
Correlated colour temperature pure
white 4000K
Lens angle 120
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 10000h
Height 56.0mm
Diameter 50.0mm
Weight 40 g
In package 1pc
In box 100pcs
No. of switches 10000pcs
Work environment indoor use
Certificates CE
Warranty 2 years



LED bulb OSRAM LED Star 230V 4,3W 350lm GU10 36° IP20 927

Product code 19283

Brand OSRAM
Supply voltage 230V
Output 4,3W
Maximum output 4.3W/1m
Luminous flux 350lumens
Correlated colour temperature warm
white 2700K
Lens angle 36
Socket GU10
Cri 90
Protection class IP20



LED bulb OSRAM P16 230V 4,5W 350lm GU10 120° IP20 830

Product code 20209

Brand OSRAM
Supply voltage 230V
Output 4,5W
Maximum output 4.5W/1m
Luminous flux 350lumens
Correlated colour temperature warm white 3000K
Lens angle 120
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 15000h
Length 54.0mm
Diameter 50.0mm
No. of switches 10000pcs
Certificates CE, EAC



LED bulb PHILIPS Corepro LEDcapsule ND G9 830 230V 4W 400lm G9 IP20 830

Product code 19287


Brand [PHILIPS](#)
Supply voltage 230V
Output 4W
Maximum output 4W/1m
Luminous flux 400lumens
Luminaire's efficiency lm79 100W
Correlated colour temperature warm white 3000K
Socket G9
Cri 80
Protection class IP20
Height 54.0mm
Width 16.5mm
No. of switches 8000pcs



LED bulb PHILIPS Corepro LEDlinear 230V 6,5W 806lm IP20 830

Product code 19286

Brand [PHILIPS](#)
Supply voltage 230V
Output 6,5W
Maximum output 6.5W/1m
Luminous flux 806lumens
Correlated colour temperature warm
white 3000K
Cri 80
Protection class IP20
Height 118.0mm
Width 22.5mm
No. of switches 50000pcs



LED bulb PHILIPS Corepro LEDlinear 230V 7,5W 950lm IP20 830

Product code 19285

Brand [PHILIPS](#)
Supply voltage 230V
Output 7,5W
Maximum output 7.5W/1m
Luminous flux 950lumens
Correlated colour temperature warm
white 3000K
Cri 80
Protection class IP20



LED bulb PHILIPS Corepro LEDspot 230V 4.6W 355lm GU10 36° 827

Product code 19192

Brand [PHILIPS](#)

Supply voltage 230V

Output 4.6W

Maximum output 4.6W/1m

Luminous flux 355lumens

Luminaire's efficiency lm79 77W

Correlated colour temperature warm
white 2700K

Lens angle 36

Socket GU10

Cri 80

Lifespan 15000h

Weight 38 g

In package 1pc

In box 10pcs

Casing material glass

No. of switches 50000pcs

Work environment indoor use

Certificates CE, RoHS

Warranty 2 years



LED bulb PHILIPS Corepro LEDspot 230V 4.9W 550lm GU10 120° 840

Product code 16391

Brand [PHILIPS](#)

Supply voltage 230V

Output 4.9W

Maximum output 4.9W/1m

Luminous flux 550lumens

Luminaire's efficiency lm79 112W

Correlated colour temperature pure
white 4000K

Lens angle 120

Socket GU10

Cri 80

Lifespan 15000h

Weight 38 g

In package 1pc

In box 10pcs

Casing material glass

No. of switches 50000pcs

Work environment indoor use

Certificates CE, RoHS

Warranty 2 years



LED bulb PHILIPS LED Classic 230V 2.1W 375lm GU10 36° IP20 830

Product code 19095

Brand [PHILIPS](#)

Supply voltage 230V

Output 2.1W

Luminous flux 375lumens

Luminaire's efficiency lm79 179W

Correlated colour temperature warm

white 3000K

Lens angle 36

Socket GU10

Cri 80

Protection class IP20

Lifespan 50000h

Height 54.0mm

Diameter 50.0mm

No. of switches 50000pcs



LED bulb PHILIPS LED Classic 230V 4.7W 380lm GU10 36° IP20 827

Product code 19094

Brand [PHILIPS](#)

Supply voltage 230V

Output 4.7W

Luminous flux 380lumens

Luminaire's efficiency lm79 81W

Correlated colour temperature warm

white 2700K

Lens angle 36

Socket GU10

Cri 80

Protection class IP20

Lifespan 30000h

Height 56.0mm

Width 50.0mm

No. of switches 15000pcs



LED bulb PHILIPS LED Classic 230V 4.7W 440lm GU10 36° IP20 840

Product code 19093

Brand [PHILIPS](#)

Supply voltage 230V

Output 4.7W

Luminous flux 440lumens

Luminaire's efficiency lm79 94W

Correlated colour temperature pure white 4000K

Lens angle 36

Socket GU10

Cri 80

Protection class IP20

Lifespan 15000h

Height 560.0mm

Width 500.0mm

No. of switches 30000pcs



LED bulb PHILIPS LED Classic 230V 4.9W 460lm GU10 36° IP20 830

Product code 19098

Brand [PHILIPS](#)

Supply voltage 230V

Output 4.9W

Luminous flux 460lumens

Luminaire's efficiency lm79 94W

Correlated colour temperature warm white 3000K

Lens angle 36

Socket GU10

Cri 80

Protection class IP20



LED bulb PHILIPS LED Classic 230V 4W 345lm GU10 36° IP20 930

Product code 19096

Brand [PHILIPS](#)
Supply voltage 230V
Output 4W
Luminous flux 345lumens
Luminaire's efficiency lm79 86W
Correlated colour temperature warm
white 3000K
Lens angle 36
Socket GU10
Cri 90
Protection class IP20
Height 12.7mm



LED bulb PHILIPS LED Classic 230V 5W 460lm GU10 36° IP20 930

Product code 19282

Brand [PHILIPS](#)
Supply voltage 230V
Output 5W
Maximum output 5W/1m
Luminous flux 460lumens
Luminaire's efficiency lm79 92W
Correlated colour temperature warm
white 3000K
Lens angle 36
Socket GU10
Cri 90
Protection class IP20



LED bulb PHILIPS LED Classic 230V 6,2W 575lm GU10 36° IP20 TRIAC 927

Product code 19280 TRIAC dimmable

Brand [PHILIPS](#)

Supply voltage 230V

Dimmable TRIAC

Output 6,2W

Maximum output 6.2W/1m

Luminous flux 575lumens

Correlated colour temperature warm white 2700K

Lens angle 36

Socket GU10

Cri 90

Protection class IP20



LED bulb PHILIPS LED Classic 3-pack 230V 4.6W 355lm GU10 36° IP20 827

Product code 19193

Brand [PHILIPS](#)

Supply voltage 230V

Output 4.6W

Maximum output 4.6W/1m

Luminous flux 355lumens

Luminaire's efficiency lm79 77W

Correlated colour temperature warm white 2700K

Lens angle 36

Socket GU10

Cri 80

Protection class IP20

Height 54.0mm

Width 50.0mm

In package 3pcs



LED bulb PHILIPS LED Corepro 230V 4.6W 390lm GU10 36° IP20 840

Product code 19097

Brand [PHILIPS](#)

Supply voltage 230V

Output 4.6W

Luminous flux 390lumens

Luminaire's efficiency lm79 85W

Correlated colour temperature pure white 4000K

Lens angle 36

Socket GU10

Cri 80

Protection class IP20

Lifespan 50000h

No. of switches 15000pcs



LED bulb PHILIPS LED Corepro 230V 5,5W 400lm GU10 36° IP20 940

Product code 19091

Brand [PHILIPS](#)

Supply voltage 230V

Output 5,5W

Maximum output 5.5W/1m

Luminous flux 400lumens

Correlated colour temperature pure white 4000K

Lens angle 36

Socket GU10

Cri 97

Protection class IP20



LED bulb PHILIPS LED Corepro 230V 6,7W 670lm GU10 60° IP20 830

Product code 19090

Brand [PHILIPS](#)

Supply voltage 230V

Output 6,7W

Maximum output 6.7W/1m

Luminous flux 670lumens

Correlated colour temperature warm
white 3000K

Lens angle 60

Socket GU10

Cri 80

Protection class IP20



LED bulb PHILIPS LED Corepro 230V 6.7W 730lm GU10 60° IP20 840

Product code 19089

Brand [PHILIPS](#)

Supply voltage 230V

Output 6.7W

Luminous flux 730lumens

Luminaire's efficiency lm79 109W

Correlated colour temperature pure
white 4000K

Lens angle 60

Socket GU10

Cri 80

Protection class IP20



LED bulb PHILIPS LED Master 230V 5,5W 575lm GU10 36° TRIAC 840

Product code 19703 TRIAC dimmable

Brand [PHILIPS](#)

Supply voltage 230V

Dimmable TRIAC

Output 5,5W

Luminous flux 575lumens

Correlated colour temperature pure white 4000K

Lens angle 36

Socket GU10

Cri 80

Lifespan 15000h

In package 1pc

In box 100pcs

No. of switches 20000pcs

Certificates CE, RohS



LED bulb PHILIPS Master Value 940 120 D 230V 5,5W 680lm GU10 120° IP20 TRIAC 940

Product code 22015 TRIAC dimmable

Brand [PHILIPS](#)

Supply voltage 230V

Dimmable TRIAC

Output 5,5W

Luminous flux 680lumens

Correlated colour temperature pure white 4000K

Lens angle 120

Socket GU10

Cri 90

Protection class IP20

Lifespan 25000h

Weight 38 g

In package 1pc

In box 10pcs

Casing material glass

No. of switches 50000pcs

Work environment indoor use

Certificates CE, RoHS

Warranty 2 years



LED bulb PHILIPS MasterValue LEDSpot 230V 5,5W 575lm GU10 36° IP20 TRIAC 930

Product code 19411 TRIAC dimmable

Brand [PHILIPS](#)

Supply voltage 230V

Dimmable TRIAC

Output 5,5W

Maximum output 5.5W/1m

Luminous flux 575lumens

Correlated colour temperature warm white 3000K

Lens angle 36

Socket GU10

Cri 90

Protection class IP20

Lifespan 25000h

Weight 38 g

In package 1pc

In box 10pcs

Casing material glass

No. of switches 50000pcs

Work environment indoor use

Certificates CE, RoHS

Warranty 2 years



LED bulb PHILIPS MasterValue LEDSpot 230V 5,8W 490lm GU5.3 36° IP20 940

Product code 19284

Brand [PHILIPS](#)

Supply voltage 230V

Output 5,8W

Maximum output 5.8W/1m

Luminous flux 490lumens

Correlated colour temperature pure white 4000K

Lens angle 36

Socket GU5.3

Cri 90

Protection class IP20



LED bulb PHILIPS PLC LED 4pin G24q-2 kompaktlamp 230V 6,5W 700lm 36° IP20 840

Product code 21877

Brand [PHILIPS](#)

Supply voltage 230V

Output 6,5W

Luminous flux 700lumens

Correlated colour temperature pure
white 4000K

Lens angle 36

Cri 89

Protection class IP20

Lifespan 15000h

Height 140.6mm

Width 28.4mm

Diameter 50.0mm

No. of switches 50000pcs

Work environment indoor use

Operation temperature -20° - +40°C

Certificates CE,RoHS

Warranty 2 years



LED bulb PREMIUM SAMSUNG 230V 5W 480lm GU10 80° 830

Product code 15643

Brand PREMIUM

Supply voltage 230V

Output 5W

Maximum output 5W/1m

Luminous flux 480lumens

Luminaire's efficiency lm79 96W

Correlated colour temperature warm
white 3000K

Lens angle 80

Socket GU10

Source of light [SAMSUNG LED](#)

Cri 80

Lifespan 30000h

Height 55.0mm

Diameter 50.0mm

In package 1pc

In box 100pcs


No. of switches 20000pcs

Work environment indoor use

Operation temperature -20°C - 40°C

Certificates CE

Warranty 3 years



LED bulb Prolumen CITIZEN DL170L COB 230V 10W 1000lm 36° IP20 TRIAC 930

Product code 14897 TRIAC dimmable

Brand [Prolumen](#)

Supply voltage 230V

Power factor 0.90

Dimmable TRIAC

Output 10W

Maximum output 10W/1m

Luminous flux 1000lumens

Luminaire's efficiency lm79 100W

Correlated colour temperature warm
white 3000K

Lens angle 36

Source of light CITIZEN LED

Cri 90

Sdcm - macadam ellipses 6

Protection class IP20

Lifespan 50000h

Llmf tm21 L70 @25°C 50.000h

Height 51.0mm

Diameter 49.0mm

In box 100pcs

Casing material aluminium

Work environment indoor use

Certificates CE, RoHS

Warranty 5 years



LED bulb Prolumen CITIZEN DL170L COB 230V 10W 900lm 36° IP20 TRIAC 940

Product code 15280 TRIAC dimmable

Brand [Prolumen](#)

Supply voltage 230V

Dimmable TRIAC

Output 10W

Maximum output 10W/1m

Luminous flux 900lumens

Luminaire's efficiency lm79 90W

Correlated colour temperature pure
white 4000K

Lens angle 36

Source of light CITIZEN LED

Cri 90

Sdcm - macadam ellipses 6

Protection class IP20

Lifespan 50000h

Llmf tm21 L70 @25°C 50.000h

Height 51.0mm

Diameter 49.0mm

In box 100pcs

Casing material aluminium

Work environment indoor use

Certificates CE, RoHS

Warranty 5 years



LED bulb Prolumen CITIZEN DL170L COB 230V 13W 1200lm 36° IP20 DALI 930

Product code 14847 DALI dimmable

Brand [Prolumen](#)

Supply voltage 230V

Dimmable DALI

Output 13W

Maximum output 13W/1m

Luminous flux 1200lumens

Luminaire's efficiency lm79 92W

Correlated colour temperature warm
white 3000K

Lens angle 36

Source of light CITIZEN LED

Cri 90

Sdcm - macadam ellipses 6

Protection class IP20

Lifespan 50000h

Llmf tm21 L70 @25°C 50.000h

Height 61.0mm

Diameter 49.0mm

In box 100pcs

Casing material aluminium

Work environment indoor use

Certificates CE, RoHS

Warranty 5 years



LED bulb Prolumen CITIZEN DL170L COB 230V 13W 1400lm 36° IP20 DALI 930

Product code 17740 DALI dimmable

Brand [Prolumen](#)

Supply voltage 230V

Dimmable DALI

Output 13W

Maximum output 13W/1m

Luminous flux 1400lumens

Luminaire's efficiency lm79 108W

Correlated colour temperature warm
white 3000K

Lens angle 36

Source of light CITIZEN LED

Cri 90

Sdcm - macadam ellipses 6

Protection class IP20

Lifespan 50000h

Llmf tm21 L70 @25°C 50.000h

Height 61.0mm

Diameter 49.0mm

In box 100pcs

Casing material aluminium

Work environment indoor use

Certificates CE, RoHS

Warranty 5 years



LED bulb Prolumen CITIZEN DL170L COB 230V 13W 1400lm 36° IP20 DALI 940

Product code 17742 DALI dimmable

Brand [Prolumen](#)

Supply voltage 230V

Dimmable DALI

Output 13W

Maximum output 13W/1m

Luminous flux 1400lumens

Luminaire's efficiency lm79 108W

Correlated colour temperature pure
white 4000K

Lens angle 36

Source of light CITIZEN LED

Cri 90

Sdcm - macadam ellipses 6

Protection class IP20

Lifespan 50000h

Llmf tm21 L70 @25°C 50.000h

Height 61.0mm

Diameter 49.0mm

In box 100pcs

Casing material aluminium

Work environment indoor use

Certificates CE, RoHS

Warranty 5 years



LED bulb Prolumen CITIZEN DL170L COB 230V 18W 1800lm 36° IP20 TRIAC 830

Product code 14848 TRIAC dimmable

Brand [Prolumen](#)
 Supply voltage 230V
 Dimmable TRIAC
 Output 18W
 Maximum output 18W/1m
 Luminous flux 1800lumens
 Luminaire's efficiency lm79 100W
 Correlated colour temperature warm
 white 3000K
 Lens angle 36
 Source of light CITIZEN LED
 Cri 80
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Llmf tm21 L70 @25°C 50.000h
 Height 81.0mm
 Diameter 50.0mm
 Casing material aluminium
 Work environment indoor use
 Certificates CE, RoHS
 Warranty 5 years



LED bulb REVAL BULB ALU PAR30 230V 25W 2300lm E27 30° IP20 TRIAC 930

Product code 15415 TRIAC dimmable

Brand [REVAL BULB](#)
 Supply voltage 230V
 Dimmable TRIAC
 Output 25W
 Maximum output 25W/1m
 Luminous flux 2300lumens
 Luminaire's efficiency lm79 92W
 Correlated colour temperature warm
 white 3000K
 Lens angle 30
 Socket E27
 Source of light [CREE LED](#)
 Cri 90
 Protection class IP20
 Lifespan 35000h
 Height 125.0mm
 Diameter 95.0mm
 Casing material aluminium
 Certificates CE



LED bulb Star Trading 347-68-3 230V 5.7W 610lm GU10 36° IP20 TRIAC 840

Product code 16438 TRIAC dimmable

Brand [Star Trading](#)

Supply voltage 230V

Dimmable TRIAC

Output 5.7W

Maximum output 5.7W/1m

Luminous flux 610lumens

Luminaire's efficiency lm79 107W

Correlated colour temperature pure
white 4000K

Lens angle 36

Socket GU10

Cri 80

Sdcm - macadam ellipses 5

Protection class IP20

Lifespan 15000h

Height 54.0mm

Diameter 50.0mm

In package 1pc

No. of switches 7500pcs

Work environment indoor use

Operation temperature -20° - +40°C

Certificates CE, RoHS

Warranty 2 years



LED bulb Star Trading MR16 ST , 12LED 347-70-1 230V 7.4W 540lm GU10 36° IP20 TRIAC 927

Product code 16631 TRIAC dimmable

Brand [Star Trading](#)

Supply voltage 230V

Dimmable TRIAC

Output 7.4W

Maximum output 7.4W/1m

Luminous flux 540lumens

Luminaire's efficiency lm79 73W

Correlated colour temperature warm
white 2700K

Lens angle 36

Socket GU10

Cri 90

Sdcm - macadam ellipses 6

Protection class IP20

Lifespan 15000h

Height 54.0mm

Diameter 50.0mm

No. of switches 7500pcs

Work environment indoor use

Operation temperature -20° - +40°C

Certificates CE,RoHS

Warranty 2 years



LED bulb Star Trading PAR38 356-81 230V 15W 1300lm E27 35° IP65 840

Product code 15805

Brand [Star Trading](#)

Supply voltage 230V

Output 15W

Maximum output 15W/1m

Luminous flux 1300lumens

Luminaire's efficiency lm79 87W

Correlated colour temperature pure
white 4000K

Lens angle 35

Socket E27

Cri 80

Sdcm - macadam ellipses 6

Protection class IP65

Lifespan 15000h

Height 133.0mm

Diameter 121.0mm

No. of switches 12500pcs

Work environment outdoor use

Operation temperature -20 ~ 40°C



LED bulb Trio Lighting 230V 5W 400lm GU10 switch dimmer 830

Product code 19501 switch dimmer dimmable

Brand [Trio Lighting](#)
Supply voltage 230V
Dimmable switch dimmer
Output 5W
Luminous flux 400lumens
Luminaire's efficiency lm79 80W
Correlated colour temperature warm white 3000K
Socket GU10
Cri 80
Lifespan 25000h
Height 5.5mm
Diameter 5.0mm
No. of switches 15000pcs
Certificates CE



The LED light source with GU10 socket is ideal for use in recessed spotlights. The brightness of the light can be easily dimmed in 3 stages using a conventional light switch. The surface of the light source is absolutely timeless in silver colour. In addition, the luminaires feature modern LED technology, which stands for a high quality of light. LED light sources are characterized by a long service life and low heat generation.

LED bulb Trio Lighting Reality 3 X LED LM 230V 4,5W 345lm GU10 38° IP20 830

Product code 20886

Brand [Trio Lighting](#)

Supply voltage 230V

Output 4,5W

Luminous flux 345lumens

Correlated colour temperature warm
white 3000K

Lens angle 38

Socket GU10

Cri 80

Sdcm - macadam ellipses 6

En62471 1

Protection class IP20

Lifespan 25000h

Height 55.0mm

Diameter 50.0mm

No. of switches 15000pcs

Operation temperature -20° - +40°C

Certificates CE, UKCA, EAC

