LED bulb CB 230V 1W 90lm GU10 120° IP20 830

Product code 16501

Supply voltage 230V
Output 1W
Maximum output 1W/1m
Luminous flux 90lumens
Luminaire's efficiency lm79 90W
Correlated colour temperature warm white 3000K
Lens angle 120
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 10000h
Height 56.0mm
Diameter 50.0mm
Weight 40 g
In package 1pc
In box 100pcs
No. of switches 10000pcs
Work environment indoor use
Certificates CE
Warranty 2 years

LED bulb CB 230V 9W 1040lm GU10 120° IP20 830

Product code 20851

Supply voltage 230V
Output 9W
Maximum output 9W/1m
Luminous flux 1040lumens
Luminaire's efficiency lm79 116W
Correlated colour temperature warm white 3000K
Lens angle 120
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 10000h
Height 56.0mm
Diameter 50.0mm
Weight 40 g
In package 1pc
In box 100pcs
No. of switches 10000pcs
Work environment indoor use
Certificates CE
Warranty 2 years

LED bulb EMOS CLASSIC MR16 230V 3.8W 320lm GU10 110° IP20 840

Product code 17009

Brand EMOS
Supply voltage 230V
Power factor 0.52
Output 3.8W
Maximum output 3.8W/1m
Luminous flux 320lumens
Luminaire's efficiency lm79 84W
Correlated colour temperature pure white 4000K
Lens angle 110
Socket GU10
Cri 80
Protection class IP20
Lifespan 30000h
Height 52.0mm
Diameter 50.0mm
In package 1pc
In box 10pcs
No. of switches 25000pcs
Work environment indoor use
Certificates CE, RoHS
Warranty 3 years

LED bulb EMOS CLASSIC MR16 230V 3W 345lm GU10 100° IP20 840

Product code 18217

Brand EMOS
Supply voltage 230V
Power factor 0.52
Output 3W
Maximum output 3W/1m
Luminous flux 345lumens
Luminaire's efficiency lm79 115W
Correlated colour temperature pure white 4000K
Lens angle 100
Socket GU10
Cri 80
Protection class IP20
Lifespan 30000h
Height 52.0mm
Diameter 50.0mm
In package 1pc
In box 10pcs
No. of switches 25000pcs
Work environment indoor use
Certificates CE, RoHS
Warranty 3 years

LED bulb LEDVANCE Parathom PAR16 230V 4.5W 350lm GU10 36° IP20 827

Product code 19184

Brand LEDVANCE
Supply voltage 230V
Output 4.5W
Maximum output 4.5W/1m
Luminous flux 350lumens
Luminaire's efficiency lm79 78W
Correlated colour temperature warm white 2700K
Lens angle 36
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
En62471 1
Protection class IP20
Lifespan 15000h
Height 50.0mm
Diameter 50.0mm
No. of switches 10000pcs
Operation temperature -20° - +40°C
Certificates CE, UKCA, EAC

LED bulb LEDVANCE Star PAR16 230V 6.9W 620lm GU10 120° IP20 827

Product code 19185

Brand LEDVANCE
Supply voltage 230V
Output 6.9W
Maximum output 6.9W/1m
Luminous flux 620lumens
Luminaire's efficiency lm79 90W
Correlated colour temperature warm white 2700K
Lens angle 120
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
En62471 1
Protection class IP20
Lifespan 15000h
Height 50.0mm
Diameter 50.0mm
No. of switches 10000pcs
Operation temperature -20° - +40°C
Certificates CE, UKCA, EAC

LED bulb LEDVANCE Superstar Plus PAR16 230V 6W 575lm GU10 120° TRIAC 927

Product code 19182 TRIAC dimmable

Brand LEDVANCE
Supply voltage 230V
Dimmable TRIAC
Output 6W
Maximum output 6W/1m
Luminous flux 575lumens
Luminaire's efficiency lm79 96W
Correlated colour temperature warm white 2700K
Lens angle 120
Socket GU10
Cri 90
Sdcm - macadam ellipses 5
En62471 1
Lifespan 25000h
Height 50.0mm
Diameter 50.0mm
Operation temperature -20° - +40°C
Certificates CE, UKCA, EAC

LED bulb MR16 A5 12V 3W 225lm GU5.3 120° 830

Product code 14022

Supply voltage 12V
Output 3W
Maximum output 3W/1m
Rated current 30mA
Luminous flux 225lumens
Luminaire's efficiency lm79 75W
Correlated colour temperature warm white 3000K
Lens angle 120
Socket GU5.3
Cri 80
Lifespan 25000h
Height 52.5mm
Diameter 50.0mm
In package 5pcs
In box 50pcs
Casing material aluminium + plastic
No. of switches 12500pcs
Work environment indoor use
Operation temperature -10°C-40°C
Certificates CE,RoHS,TUV-GS

LED bulb MR16 A5 230V 4W 260lm GU10 120° 865

Product code 14128

Supply voltage 230V
Output 4W
Maximum output 4W/1m
Rated current 50mA
Luminous flux 260lumens
Luminaire's efficiency lm79 65W
Correlated colour temperature cold white 6500K
Lens angle 120
Socket GU10
Cri 80
Lifespan 25000h
Height 51.0mm
Diameter 50.0mm
In package 5pcs
In box 50pcs
Casing material aluminium + plastic
Polishing matt
No. of switches 12500pcs
Work environment indoor use
Operation temperature -10~+40°C
Certificates CE,RoHS,TUV-GS

LED bulb NB 230V 1W 90lm GU10 120° IP20 840

Product code 16488

Supply voltage 230V
Output 1W
Maximum output 1W/1m
Luminous flux 90lumens
Luminaire's efficiency lm79 90W
Correlated colour temperature pure white 4000K
Lens angle 120
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 10000h
Height 56.0mm
Diameter 50.0mm
Weight 40 g
In package 1pc
In box 100pcs
No. of switches 10000pcs
Work environment indoor use
Certificates CE
Warranty 2 years

LED bulb OSRAM P16 230V 4,5W 350lm GU10 120° IP20 830

Product code 20209

Brand OSRAM
Supply voltage 230V
Output 4,5W
Maximum output 4.5W/1m
Luminous flux 350lumens
Correlated colour temperature warm white 3000K
Lens angle 120
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 15000h
Length 54.0mm
Diameter 50.0mm
No. of switches 10000pcs
Certificates CE, EAC

# LED bulb PHILIPS Corepro LEDcapsule ND G9 830 230V 4W 400lm G9 IP20 830

Product code 19287

Brand PHILIPS
Supply voltage 230V
Output 4W
Maximum output 4W/1m
Luminous flux 400lumens
Luminaire's efficiency lm79 100W
Correlated colour temperature warm white 3000K
Socket G9
Cri 80
Protection class IP20
Height 54.0mm
Width 16.5mm
No. of switches 8000pcs

LED bulb PHILIPS Corepro LEDlinear 230V 6,5W 806lm IP20 830

Product code 19286

Brand PHILIPS
Supply voltage 230V
Output 6,5W
Maximum output 6.5W/1m
Luminous flux 806lumens
Correlated colour temperature warm white 3000K
Cri 80
Protection class IP20
Height 118.0mm
Width 22.5mm
No. of switches 50000pcs

LED bulb PHILIPS Corepro LEDlinear 230V 7,5W 950lm IP20 830

Product code 19285

Brand PHILIPS
Supply voltage 230V
Output 7,5W
Maximum output 7.5W/1m
Luminous flux 950lumens
Correlated colour temperature warm white 3000K
Cri 80
Protection class IP20

LED bulb PHILIPS Corepro LEDspot 230V 4.6W 355lm GU10 36° 827

Product code 19192

Brand PHILIPS
Supply voltage 230V
Output 4.6W
Maximum output 4.6W/1m
Luminous flux 355lumens
Luminaire's efficiency lm79 77W
Correlated colour temperature warm white 2700K
Lens angle 36
Socket GU10
Cri 80
Lifespan 15000h
Weight 38 g
In package 1pc
In box 10pcs
Casing material glass
No. of switches 50000pcs
Work environment indoor use
Certificates CE, RoHS
Warranty 2 years

LED bulb PHILIPS Corepro LEDspot 230V 4.9W 550lm GU10 120° 840

Product code 16391

Brand PHILIPS
Supply voltage 230V
Output 4.9W
Maximum output 4.9W/1m
Luminous flux 550lumens
Luminaire's efficiency lm79 112W
Correlated colour temperature pure white 4000K
Lens angle 120
Socket GU10
Cri 80
Lifespan 15000h
Weight 38 g
In package 1pc
In box 10pcs
Casing material glass
No. of switches 50000pcs
Work environment indoor use
Certificates CE, RoHS
Warranty 2 years

LED bulb PHILIPS Corepro LEDspot MR16 12V 7W 621lm GU5.3 36° IP20 830

Product code 19187

Brand PHILIPS
Supply voltage 12V
Output 7W
Maximum output 7W/1m
Luminous flux 621lumens
Luminaire's efficiency lm79 89W
Correlated colour temperature warm white 3000K
Lens angle 36
Socket GU5.3
Cri 80
Sdcm - macadam ellipses 6
En62471 1
Protection class IP20
Lifespan 15000h
Height 50.0mm
Diameter 50.0mm
Weight 34 g
No. of switches 50000pcs
Operation temperature -20° - +40°C
Certificates CE, UKCA, EAC

LED bulb PHILIPS LED Classic 230V 2.1W 375lm GU10 36° IP20 830

Product code 19095

Brand PHILIPS
Supply voltage 230V
Output 2.1W
Luminous flux 375lumens
Luminaire's efficiency lm79 179W
Correlated colour temperature warm white 3000K
Lens angle 36
Socket GU10
Cri 80
Protection class IP20
Lifespan 50000h
Height 54.0mm
Diameter 50.0mm
No. of switches 50000pcs

LED bulb PHILIPS LED Classic 230V 4.7W 380lm GU10 36° IP20 827

Product code 19094

Brand PHILIPS
Supply voltage 230V
Output 4.7W
Luminous flux 380lumens
Luminaire's efficiency lm79 81W
Correlated colour temperature warm white 2700K
Lens angle 36
Socket GU10
Cri 80
Protection class IP20
Lifespan 30000h
Height 56.0mm
Width 50.0mm
No. of switches 15000pcs

LED bulb PHILIPS LED Classic 230V 4.7W 440lm GU10 36° IP20 840

Product code 19093

Brand PHILIPS
Supply voltage 230V
Output 4.7W
Luminous flux 440lumens
Luminaire's efficiency lm79 94W
Correlated colour temperature pure white 4000K
Lens angle 36
Socket GU10
Cri 80
Protection class IP20
Lifespan 15000h
Height 560.0mm
Width 500.0mm
No. of switches 30000pcs

LED bulb PHILIPS LED Classic 230V 4.9W 460lm GU10 36° IP20 830

Product code 19098

Brand PHILIPS
Supply voltage 230V
Output 4.9W
Luminous flux 460lumens
Luminaire's efficiency lm79 94W
Correlated colour temperature warm white 3000K
Lens angle 36
Socket GU10
Cri 80
Protection class IP20

LED bulb PHILIPS LED Classic 230V 4W 345lm GU10 36° IP20 930

Product code 19096

Brand PHILIPS
Supply voltage 230V
Output 4W
Luminous flux 345lumens
Luminaire's efficiency lm79 86W
Correlated colour temperature warm white 3000K
Lens angle 36
Socket GU10
Cri 90
Protection class IP20
Height 12.7mm

LED bulb PHILIPS LED Classic 230V 5W 460lm GU10 36° IP20 930

Product code 19282

Brand PHILIPS
Supply voltage 230V
Output 5W
Maximum output 5W/1m
Luminous flux 460lumens
Luminaire's efficiency lm79 92W
Correlated colour temperature warm white 3000K
Lens angle 36
Socket GU10
Cri 90
Protection class IP20

LED bulb PHILIPS LED Classic 230V 6,2W 575lm GU10 36° IP20 TRIAC 927

Product code 19280 TRIAC dimmable

Brand PHILIPS
Supply voltage 230V
Dimmable TRIAC
Output 6,2W
Maximum output 6.2W/1m
Luminous flux 575lumens
Correlated colour temperature warm white 2700K
Lens angle 36
Socket GU10
Cri 90
Protection class IP20

LED bulb PHILIPS LED Classic 3-pack 230V 4.6W 355lm GU10 36° IP20 827

Product code 19193

Brand [PHILIPS](#)
Supply voltage 230V
Output 4.6W
Maximum output 4.6W/1m
Luminous flux 355lumens
Luminaire's efficiency lm79 77W
Correlated colour temperature warm white 2700K
Lens angle 36
Socket GU10
Cri 80
Protection class IP20
Height 54.0mm
Width 50.0mm
In package 3pcs

LED bulb PHILIPS LED Corepro 230V 4.6W 390lm GU10 36° IP20 840

Product code 19097

Brand [PHILIPS](#)
Supply voltage 230V
Output 4.6W
Luminous flux 390lumens
Luminaire's efficiency lm79 85W
Correlated colour temperature pure white 4000K
Lens angle 36
Socket GU10
Cri 80
Protection class IP20
Lifespan 50000h
No. of switches 15000pcs

LED bulb PHILIPS LED Corepro 230V 4.9W 460lm GU10 36° IP20 830

Product code 19092

Brand PHILIPS
Supply voltage 230V
Output 4.9W
Luminous flux 460lumens
Luminaire's efficiency lm79 94W
Correlated colour temperature warm white 3000K
Lens angle 36
Socket GU10
Cri 80
Protection class IP20

LED bulb PHILIPS LED Corepro 230V 5,5W 400lm GU10 36° IP20 940

Product code 19091

Brand PHILIPS
Supply voltage 230V
Output 5,5W
Maximum output 5.5W/1m
Luminous flux 400lumens
Correlated colour temperature pure white 4000K
Lens angle 36
Socket GU10
Cri 97
Protection class IP20

LED bulb PHILIPS LED Corepro 230V 6,7W 670lm GU10 60° IP20 830

Product code 19090

Brand PHILIPS
Supply voltage 230V
Output 6,7W
Maximum output 6.7W/1m
Luminous flux 670lumens
Correlated colour temperature warm white 3000K
Lens angle 60
Socket GU10
Cri 80
Protection class IP20

LED bulb PHILIPS LED Corepro 230V 6.7W 730lm GU10 60° IP20 840

Product code 19089

Brand PHILIPS
Supply voltage 230V
Output 6.7W
Luminous flux 730lumens
Luminaire's efficiency lm79 109W
Correlated colour temperature pure white 4000K
Lens angle 60
Socket GU10
Cri 80
Protection class IP20

LED bulb PHILIPS LED Master 230V 5,5W 575lm GU10 36° TRIAC 840

Product code 19703 TRIAC dimmable

Brand PHILIPS
Supply voltage 230V
Dimmable TRIAC
Output 5,5W
Luminous flux 575lumens
Correlated colour temperature pure white 4000K
Lens angle 36
Socket GU10
Cri 80
Lifespan 15000h
In package 1pc
In box 100pcs
No. of switches 20000pcs
Certificates CE, RohS

LED bulb PHILIPS Master Value 940 120 D 230V 5,5W 680lm GU10 120° IP20 TRIAC 940

Product code 22015 TRIAC dimmable

Brand PHILIPS
Supply voltage 230V
Dimmable TRIAC
Output 5,5W
Luminous flux 680lumens
Correlated colour temperature pure white 4000K
Lens angle 120
Socket GU10
Cri 90
Protection class IP20
Lifespan 25000h
Weight 38 g
In package 1pc
In box 10pcs
Casing material glass
No. of switches 50000pcs
Work environment indoor use
Certificates CE, RohS
Warranty 2 years

LED bulb PHILIPS MasterValue LEDSpot 230V 5,5W 575lm GU10 36° IP20 TRIAC 930

Product code 19411 TRIAC dimmable

Brand PHILIPS
Supply voltage 230V
Dimmable TRIAC
Output 5,5W
Maximum output 5.5W/1m
Luminous flux 575lumens
Correlated colour temperature warm
white 3000K
Lens angle 36
Socket GU10
Cri 90
Protection class IP20
Lifespan 25000h
Weight 38 g
In package 1pc
In box 10pcs
Casing material glass
No. of switches 50000pcs
Work environment indoor use
Certificates CE, RoHS
Warranty 2 years

LED bulb PHILIPS MasterValue LEDSpot 230V 5,8W 490lm GU5.3 36° IP20 940

Product code 19284

Brand PHILIPS
Supply voltage 230V
Output 5,8W
Maximum output 5.8W/1m
Luminous flux 490lumens
Correlated colour temperature pure
white 4000K
Lens angle 36
Socket GU5.3
Cri 90
Protection class IP20

LED bulb PHILIPS PLC LED 4pin G24q-2 kompaktlamp 230V 6,5W 700lm 36° IP20 840

Product code 21877

Brand PHILIPS
Supply voltage 230V
Output 6,5W
Luminous flux 700lumens
Correlated colour temperature pure
white 4000K
Lens angle 36
Cri 89
Protection class IP20
Lifespan 15000h
Height 140.6mm
Width 28.4mm
Diameter 50.0mm
No. of switches 50000pcs
Work environment indoor use
Operation temperature -20° - +40°C
Certificates CE,RoHS
Warranty 2 years

LED bulb PREMIUM SAMSUNG 230V 5W 480lm GU10 80° 830

Product code 15643

Brand PREMIUM
Supply voltage 230V
Output 5W
Maximum output 5W/1m
Luminous flux 480lumens
Luminaire's efficiency lm79 96W
Correlated colour temperature warm
white 3000K
Lens angle 80
Socket GU10
Source of light SAMSUNG LED
Cri 80
Lifespan 30000h
Height 55.0mm
Diameter 50.0mm
In package 1pc
In box 100pcs
No. of switches 20000pcs
Work environment indoor use
Operation temperature -20°C - 40°C
Certificates CE
Warranty 3 years

LED bulb Prolumen CITIZEN DL170L COB 230V 10W 1000lm 36° IP20 TRIAC 930

Product code 14897 TRIAC dimmable

Brand [Prolumen](#)
Supply voltage 230V
Power factor 0.90
Dimmable TRIAC
Output 10W
Maximum output 10W/1m
Luminous flux 1000lumens
Luminaire's efficiency lm79 100W
Correlated colour temperature warm white 3000K
Lens angle 36
Source of light CITIZEN LED
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70 @25°C 50.000h
Height 51.0mm
Diameter 49.0mm
In box 100pcs
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years

LED bulb Prolumen CITIZEN DL170L COB 230V 10W 900lm 36° IP20 TRIAC 940

Product code 15280 TRIAC dimmable

Brand Prolumen
Supply voltage 230V
Dimmable TRIAC
Output 10W
Maximum output 10W/1m
Luminous flux 900lumens
Luminaire's efficiency lm79 90W
Correlated colour temperature pure white 4000K
Lens angle 36
Source of light CITIZEN LED
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70 @25°C 50.000h
Height 51.0mm
Diameter 49.0mm
In box 100pcs
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years

LED bulb Prolumen CITIZEN DL170L COB 230V 13W 1200lm 36° IP20 DALI 930

Product code 14847 DALI dimmable

Brand Prolumen
Supply voltage 230V
Dimmable DALI
Output 13W
Maximum output 13W/1m
Luminous flux 1200lumens
Luminaire's efficiency lm79 92W
Correlated colour temperature warm white 3000K
Lens angle 36
Source of light CITIZEN LED
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70 @25°C 50.000h
Height 61.0mm
Diameter 49.0mm
In box 100pcs
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years

LED bulb Prolumen CITIZEN DL170L COB 230V 13W 1400lm 36° IP20 DALI 930

Product code 17740 DALI dimmable

Brand Prolumen
Supply voltage 230V
Dimmable DALI
Output 13W
Maximum output 13W/1m
Luminous flux 1400lumens
Luminaire's efficiency lm79 108W
Correlated colour temperature warm white 3000K
Lens angle 36
Source of light CITIZEN LED
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70 @25°C 50.000h
Height 61.0mm
Diameter 49.0mm
In box 100pcs
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years

LED bulb Prolumen CITIZEN DL170L COB 230V 13W 1400lm 36° IP20 DALI 940

Product code 17742 **DALI dimmable**

Brand [Prolumen](#)
Supply voltage 230V
Dimmable DALI
Output 13W
Maximum output 13W/1m
Luminous flux 1400lumens
Luminaire's efficiency lm79 108W
Correlated colour temperature pure
white 4000K
Lens angle 36
Source of light CITIZEN LED
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70 @25°C 50.000h
Height 61.0mm
Diameter 49.0mm
In box 100pcs
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years

LED bulb Prolumen CITIZEN DL170L COB 230V 18W 1800lm 36° IP20 TRIAC 830

Product code 14848 TRIAC dimmable

Brand [Prolumen](#)
Supply voltage 230V
Dimmable TRIAC
Output 18W
Maximum output 18W/1m
Luminous flux 1800lumens
Luminaire's efficiency lm79 100W
Correlated colour temperature warm white 3000K
Lens angle 36
Source of light CITIZEN LED
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70 @25°C 50.000h
Height 81.0mm
Diameter 50.0mm
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years

LED bulb REVAL BULB ALU PAR30 230V 25W 2300lm E27 30° IP20 TRIAC 930

Product code 15415 TRIAC dimmable

Brand [REVAL BULB](#)
Supply voltage 230V
Dimmable TRIAC
Output 25W
Maximum output 25W/1m
Luminous flux 2300lumens
Luminaire's efficiency lm79 92W
Correlated colour temperature warm white 3000K
Lens angle 30
Socket E27
Source of light [CREE LED](#)
Cri 90
Protection class IP20
Lifespan 35000h
Height 125.0mm
Diameter 95.0mm
Casing material aluminium
Certificates CE

LED bulb Star Trading 347-68-3 230V 5.7W 610lm GU10 36° IP20 TRIAC 840

Product code 16438 TRIAC dimmable

Brand Star Trading
Supply voltage 230V
Dimmable TRIAC
Output 5.7W
Maximum output 5.7W/1m
Luminous flux 610lumens
Luminaire's efficiency lm79 107W
Correlated colour temperature pure white 4000K
Lens angle 36
Socket GU10
Cri 80
Sdcm - macadam ellipses 5
Protection class IP20
Lifespan 15000h
Height 54.0mm
Diameter 50.0mm
In package 1pc
No. of switches 7500pcs
Work environment indoor use
Operation temperature -20° - +40°°C
Certificates CE, RoHS
Warranty 2 years

LED bulb Star Trading MR16 ST , 12LED 347-70-1 230V 7.4W 540lm GU10 36° IP20 TRIAC 927

Product code 16631 TRIAC dimmable

Brand Star Trading
Supply voltage 230V
Dimmable TRIAC
Output 7.4W
Maximum output 7.4W/1m
Luminous flux 540lumens
Luminaire's efficiency lm79 73W
Correlated colour temperature warm white 2700K
Lens angle 36
Socket GU10
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 15000h
Height 54.0mm
Diameter 50.0mm
No. of switches 7500pcs
Work environment indoor use
Operation temperature -20° - +40°C
Certificates CE,RoHS
Warranty 2 years

LED bulb Star Trading PAR38 356-81 230V 15W 1300lm E27 35° IP65 840

Product code 15805

Brand Star Trading
Supply voltage 230V
Output 15W
Maximum output 15W/1m
Luminous flux 1300lumens
Luminaire's efficiency lm79 87W
Correlated colour temperature pure white 4000K
Lens angle 35
Socket E27
Cri 80
Sdcm - macadam ellipses 6
Protection class IP65
Lifespan 15000h
Height 133.0mm
Diameter 121.0mm
No. of switches 12500pcs
Work environment outdoor use
Operation temperature -20 ~ 40°C

LED bulb Trio Lighting 230V 5W 400lm GU10 switch dimmer 830

Product code 19501 **switch dimmer dimmable**

Brand [Trio Lighting](#)
Supply voltage 230V
Dimmable switch dimmer
Output 5W
Luminous flux 400lumens
Luminaire's efficiency lm79 80W
Correlated colour temperature warm white 3000K
Socket GU10
Cri 80
Lifespan 25000h
Height 5.5mm
Diameter 5.0mm
No. of switches 15000pcs
Certificates CE

The LED light source with GU10 socket is ideal for use in recessed spotlights. The brightness of the light can be easily dimmed in 3 stages using a conventional light switch. The surface of the light source is absolutely timeless in silver colour. In addition, the luminaires feature modern LED technology, which stands for a high quality of light. LED light sources are characterized by a long service life and low heat generation.

LED bulb Trio Lighting Reality 3 X LED LM 230V 4,5W 345lm GU10 38° IP20 830

Product code 20886

Brand [Trio Lighting](#)
Supply voltage 230V
Output 4,5W
Luminous flux 345lumens
Correlated colour temperature warm white 3000K
Lens angle 38
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
En62471 1
Protection class IP20
Lifespan 25000h
Height 55.0mm
Diameter 50.0mm
No. of switches 15000pcs
Operation temperature -20° - +40°C
Certificates CE, UKCA, EAC