# LED bulb CB 230V 1W 90lm GU10 120° IP20 830

**Product code 16501**

Supply voltage 230V
Output 1W
Maximum output 1W/1m
Luminous flux 90lumens
Luminaire’s efficiency 90W
Correlated colour temperature warm white 3000K
Lens angle 120
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 10000h
Height 56.0mm
Diameter 50.0mm
Weight 40 g
In package 1pc
In box 100pcs
No. of switches 10000pcs
Work environment indoor use
Certificates CE
Warranty 2 years



# LED bulb CB 230V 9W 1040lm GU10 120° IP20 830

**Product code 20851**

Supply voltage 230V
Output 9W
Maximum output 9W/1m
Luminous flux 1040lumens
Luminaire’s efficiency 116W
Correlated colour temperature warm white 3000K
Lens angle 120
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 10000h
Height 56.0mm
Diameter 50.0mm
Weight 40 g
In package 1pc
In box 100pcs
No. of switches 10000pcs
Work environment indoor use
Certificates CE
Warranty 2 years



# LED bulb EMOS CLASSIC MR16 230V 3W 345lm GU10 100° IP20 840

**Product code 18217**

Brand EMOS
Supply voltage 230V
Power factor 0.52
Output 3W
Maximum output 3W/1m
Luminous flux 345lumens
Luminaire’s efficiency 115W
Correlated colour temperature pure white 4000K
Lens angle 100
Socket GU10
Cri 80
Protection class IP20
Lifespan 30000h
Height 52.0mm
Diameter 50.0mm
In package 1pc
In box 10pcs
No. of switches 25000pcs
Work environment indoor use
Certificates CE, RoHS
Warranty 3 years



# LED bulb LEDVANCE PAR16 230V 6.1W 575lm GU10 60° IP20 930

**Product code 23119**

Brand LEDVANCE
Supply voltage 230V
Output 6.1W
Maximum output 6.1W/1m
Luminous flux 575lumens
Luminaire’s efficiency 94W
Correlated colour temperature warm white 3000K
Lens angle 60
Socket GU10
Cri 90
En62471 1
Protection class IP20
Lifespan 15000h
Height 50.0mm
Diameter 50.0mm
Operation temperature -20° - +40°C
Certificates CE, UKCA, EAC



# LED bulb LEDVANCE Parathom PAR16 230V 4.5W 350lm GU10 36° IP20 827

**Product code 19184**

Brand LEDVANCE
Supply voltage 230V
Output 4.5W
Maximum output 4.5W/1m
Luminous flux 350lumens
Luminaire’s efficiency 78W
Correlated colour temperature warm white 2700K
Lens angle 36
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
En62471 1
Protection class IP20
Lifespan 15000h
Height 50.0mm
Diameter 50.0mm
No. of switches 10000pcs
Operation temperature -20° - +40°C
Certificates CE, UKCA, EAC




# LED bulb LEDVANCE Star PAR16 230V 6.9W 620lm GU10 120° IP20 827

**Product code 19185**

Brand LEDVANCE
Supply voltage 230V
Output 6.9W
Maximum output 6.9W/1m
Luminous flux 620lumens
Luminaire’s efficiency 90W
Correlated colour temperature warm white 2700K
Lens angle 120
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
En62471 1
Protection class IP20
Lifespan 15000h
Height 50.0mm
Diameter 50.0mm
No. of switches 10000pcs
Operation temperature -20° - +40°C
Certificates CE, UKCA, EAC



# LED bulb LEDVANCE Superstar Plus PAR16 230V 6W 575lm GU10 120° DIMMABLE 927

**Product code 19182** **dimmerdatav**
**dimmable**

Brand LEDVANCE
Supply voltage 230V
Dimmable dimmerdatav
Output 6W
Maximum output 6W/1m
Luminous flux 575lumens
Luminaire’s efficiency 96W
Correlated colour temperature warm white 2700K
Lens angle 120
Socket GU10
Cri 90
Sdcm - macadam ellipses 5
En62471 1
Lifespan 25000h
Height 50.0mm
Diameter 50.0mm
Operation temperature -20° - +40°C
Certificates CE, UKCA, EAC




# LED bulb LUMILEDS PAR16 230V 8W 650lm GU10 36° IP20 DIMMABLE 830

**Product code 23122** **dimmerdatav**
**dimmable**

Brand LUMILEDS
Supply voltage 230V
Dimmable dimmerdatav
Output 8W
Maximum output 8W/1m
Luminous flux 650lumens
Luminaire’s efficiency 81W
Correlated colour temperature warm white 3000K
Lens angle 36
Socket GU10
Cri 80
En62471 1
Protection class IP20
Lifespan 15000h
Operation temperature -20° - +40°C
Certificates CE, UKCA, EAC



# LED bulb NB 230V 1W 90lm GU10 120° IP20 840

**Product code 16488**

Supply voltage 230V
Output 1W
Maximum output 1W/1m
Luminous flux 90lumens
Luminaire’s efficiency 90W
Correlated colour temperature pure white 4000K
Lens angle 120
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 10000h
Height 56.0mm
Diameter 50.0mm
Weight 40 g
In package 1pc
In box 100pcs
No. of switches 10000pcs
Work environment indoor use
Certificates CE
Warranty 2 years



# LED bulb OSRAM P16 230V 4,5W 350lm GU10 120° IP20 830

**Product code 20209**

Brand OSRAM
Supply voltage 230V
Output 4,5W
Maximum output 4.5W/1m
Luminous flux 350lumens
Correlated colour temperature warm white 3000K
Lens angle 120
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 15000h
Length 54.0mm
Diameter 50.0mm
No. of switches 10000pcs
Certificates CE, EAC



# LED bulb OSRAM Star PAR16 230V 4,3W 350lm GU10 36° IP20 927

**Product code 19283**

Brand OSRAM
Supply voltage 230V
Output 4,3W
Maximum output 4.3W/1m
Luminous flux 350lumens
Correlated colour temperature warm white 2700K
Lens angle 36
Socket GU10
Cri 90
Protection class IP20
Lifespan 15000h
No. of switches 100000pcs



# LED bulb PHILIPS Corepro capsule ND G9 830 230V 4W 400lm G9 IP20 830

**Product code 19287**

Brand PHILIPS
Supply voltage 230V
Output 4W
Maximum output 4W/1m
Luminous flux 400lumens
Luminaire’s efficiency 100W
Correlated colour temperature warm white 3000K
Socket G9
Cri 80
Protection class IP20
Height 54.0mm
Width 16.5mm
No. of switches 8000pcs



# LED bulb PHILIPS CorePro G24Q-2 230V 6,5W 700lm 36° IP20 840

**Product code 21877**

Brand PHILIPS
Supply voltage 230V
Output 6,5W
Luminous flux 700lumens
Correlated colour temperature pure white 4000K
Lens angle 36
Cri 89
Protection class IP20
Lifespan 30000h
Height 140.6mm
Width 28.4mm
Diameter 50.0mm
No. of switches 50000pcs
Work environment indoor use
Operation temperature -20° - +40°C
Certificates CE,RoHS
Warranty 2 years



# LED bulb PHILIPS Corepro LEDlinear 230V 6,5W 806lm IP20 830

**Product code 19286**

Brand PHILIPS
Supply voltage 230V
Output 6,5W
Maximum output 6.5W/1m
Luminous flux 806lumens
Correlated colour temperature warm white 3000K
Cri 80
Protection class IP20
Height 118.0mm
Width 22.5mm
No. of switches 50000pcs





# LED bulb PHILIPS Corepro LEDlinear R7S 230V 6,5W 806lm IP20 830

**Product code 24011**

Brand PHILIPS
Supply voltage 230V
Output 6,5W
Maximum output 6.5W/1m
Luminous flux 806lumens
Correlated colour temperature warm white 3000K
Cri 80
Protection class IP20
Height 118.0mm
Diameter 22.5mm
No. of switches 50000pcs



# LED bulb PHILIPS Corepro linear R7S 230V 7,5W 950lm IP20 830

**Product code 19285**

Brand PHILIPS
Supply voltage 230V
Output 7,5W
Maximum output 7.5W/1m
Luminous flux 950lumens
Correlated colour temperature warm white 3000K
Cri 80
Protection class IP20



# LED bulb PHILIPS Corepro spot MR16 12V 7W 621lm GU5.3 36° IP20 830

**Product code 19187**

Brand PHILIPS
Supply voltage 12V
Output 7W
Maximum output 7W/1m
Luminous flux 621lumens
Luminaire’s efficiency 89W
Correlated colour temperature warm white 3000K
Lens angle 36
Socket GU5.3
Cri 80
Sdcm - macadam ellipses 6
En62471 1
Protection class IP20
Lifespan 15000h
Height 50.0mm
Diameter 50.0mm
Weight 34 g
No. of switches 50000pcs
Operation temperature -20° - +40°C
Certificates CE, UKCA, EAC







# LED bulb PHILIPS Corepro spot PAR16 230V 4.6W 355lm GU10 36° 827

**Product code 19192**

Brand PHILIPS
Supply voltage 230V
Output 4.6W
Maximum output 4.6W/1m
Luminous flux 355lumens
Luminaire’s efficiency 77W
Correlated colour temperature warm white 2700K
Lens angle 36
Socket GU10
Cri 80
Lifespan 15000h
Height 54.0mm
Diameter 50.0mm
Weight 38 g
In package 1pc
In box 10pcs
Casing material glass
No. of switches 50000pcs
Work environment indoor use
Certificates CE, RoHS
Warranty 2 years



# LED bulb PHILIPS Corepro spot PAR16 230V 4.6W 390lm GU10 36° IP20 840

**Product code 19097**

Brand PHILIPS
Supply voltage 230V
Output 4.6W
Luminous flux 390lumens
Luminaire’s efficiency 85W
Correlated colour temperature pure white 4000K
Lens angle 36
Socket GU10
Cri 80
Protection class IP20
Lifespan 15000h
Height 54.0mm
Diameter 50.0mm
No. of switches 50000pcs



# LED bulb PHILIPS Corepro spot PAR16 230V 4.9W 550lm GU10 120° 840

**Product code 16391**

Brand PHILIPS
Supply voltage 230V
Output 4.9W
Maximum output 4.9W/1m
Luminous flux 550lumens
Luminaire’s efficiency 112W
Correlated colour temperature pure white 4000K
Lens angle 120
Socket GU10
Cri 80
Lifespan 15000h
Height 54.0mm
Diameter 50.0mm
Weight 38 g
In package 1pc
In box 10pcs
Casing material glass
No. of switches 50000pcs
Work environment indoor use
Certificates CE, RoHS
Warranty 2 years



# LED bulb PHILIPS Corepro spot PAR16 230V 6,7W 670lm GU10 60° IP20 830

**Product code 19090**

Brand PHILIPS
Supply voltage 230V
Output 6,7W
Maximum output 6.7W/1m
Luminous flux 670lumens
Correlated colour temperature warm white 3000K
Lens angle 60
Socket GU10
Cri 80
Protection class IP20
Lifespan 25000h
Height 54.0mm
Diameter 50.0mm
No. of switches 50000pcs




# LED bulb PHILIPS Eye Comfort spot PAR16 230V 4W 345lm GU10 36° IP20 DIMMABLE 930

**Product code 19096 dimmerdatav dimmable**

Brand PHILIPS
Supply voltage 230V
Dimmable dimmerdatav
Output 4W
Luminous flux 345lumens
Luminaire’s efficiency 86W
Correlated colour temperature warm white 3000K
Lens angle 36
Socket GU10
Cri 90
Protection class IP20
Lifespan 15000h
Height 12.7mm
No. of switches 50000pcs






# LED bulb PHILIPS LED Master Expert Color 230V 5,5W 400lm GU10 36° IP20 dimmerdatav 940

**Product code 19091 dimmerdatav dimmable**

Brand PHILIPS
Supply voltage 230V
Dimmable dimmerdatav
Output 5,5W
Maximum output 5.5W/1m
Luminous flux 400lumens
Correlated colour temperature pure white 4000K
Lens angle 36
Socket GU10
Cri 97
Protection class IP20
Lifespan 40000h
Height 54.0mm
Diameter 50.0mm
No. of switches 50000pcs




# LED bulb PHILIPS LED Master PAR16 230V 5,5W 575lm GU10 36° dimmerdatav 940

**Product code 19703 dimmerdatav dimmable**

Brand PHILIPS
Supply voltage 230V
Dimmable dimmerdatav
Output 5,5W
Luminous flux 575lumens
Correlated colour temperature pure white 4000K
Lens angle 36
Socket GU10
Cri 90
Lifespan 25000h
Height 54.0mm
Diameter 50.0mm
In package 1pc
In box 100pcs
No. of switches 50000pcs
Certificates CE, RohS



# LED bulb PHILIPS Master Value PAR16 230V 5,5W 680lm GU10 120° IP20 dimmerdatav 940

**Product code 22015 dimmerdatav dimmable**

Brand PHILIPS
Supply voltage 230V
Dimmable dimmerdatav
Output 5,5W
Luminous flux 680lumens
Correlated colour temperature pure white 4000K
Lens angle 120
Socket GU10
Cri 90
Protection class IP20
Lifespan 25000h
Weight 38 g
In package 1pc
In box 10pcs
Casing material glass
No. of switches 50000pcs
Work environment indoor use
Certificates CE, RoHS
Warranty 2 years




# LED bulb PHILIPS Master Value spot MR16 230V 5,8W 490lm GU5.3 36° IP20 940

**Product code 19284**

Brand PHILIPS
Supply voltage 230V
Output 5,8W
Maximum output 5.8W/1m
Luminous flux 490lumens
Correlated colour temperature pure white 4000K
Lens angle 36
Socket GU5.3
Cri 90
Protection class IP20
Lifespan 25000h
No. of switches 50000pcs



# LED bulb PHILIPS Master Value spot PAR16 230V 5,5W 575lm GU10 36° IP20 DIMMABLE 930

**Product code 19411 dimmerdatav**
**dimmable**

Brand PHILIPS
Supply voltage 230V
Dimmable dimmerdatav
Output 5,5W
Maximum output 5.5W/1m
Luminous flux 575lumens
Correlated colour temperature warm white 3000K
Lens angle 36
Socket GU10
Cri 90
Protection class IP20
Lifespan 25000h
Weight 38 g
In package 1pc
In box 10pcs
Casing material glass
No. of switches 50000pcs
Work environment indoor use
Certificates CE, RoHS
Warranty 2 years




# LED bulb PHILIPS spot PAR16 230V 4.7W 380lm GU10 36° IP20 827

**Product code 19094**

Brand PHILIPS
Supply voltage 230V
Output 4.7W
Luminous flux 380lumens
Luminaire’s efficiency 81W
Correlated colour temperature warm white 2700K
Lens angle 36
Socket GU10
Cri 80
Protection class IP20
Lifespan 30000h
Height 56.0mm
Width 50.0mm
No. of switches 15000pcs



# LED bulb PHILIPS spot PAR16 230V 4.7W 440lm GU10 36° IP20 840

**Product code 19093**

Brand PHILIPS
Supply voltage 230V
Output 4.7W
Luminous flux 440lumens
Luminaire’s efficiency 94W
Correlated colour temperature pure white 4000K
Lens angle 36
Socket GU10
Cri 80
Protection class IP20
Lifespan 15000h
Height 560.0mm
Width 500.0mm
No. of switches 30000pcs




# LED bulb PHILIPS spot PAR16 230V 4.9W 460lm GU10 36° IP20 830

**Product code 19098**

Brand PHILIPS
Supply voltage 230V
Output 4.9W
Luminous flux 460lumens
Luminaire’s efficiency 94W
Correlated colour temperature warm white 3000K
Lens angle 36
Socket GU10
Cri 80
Protection class IP20
Lifespan 15000h
Height 54.0mm
Diameter 50.0mm
No. of switches 50000pcs



# LED bulb PHILIPS spot PAR16 230V 6,2W 575lm GU10 36° IP20 DIMMABLE 927

**Product code 19280 dimmerdatav dimmable**

Brand PHILIPS
Supply voltage 230V
Dimmable dimmerdatav
Output 6,2W
Maximum output 6.2W/1m
Luminous flux 575lumens
Correlated colour temperature warm white 2700K
Lens angle 36
Socket GU10
Cri 90
Protection class IP20
Lifespan 25000h
No. of switches 50000pcs




# LED bulb PHILIPS spot PAR16 3X 230V 4.6W 355lm GU10 36° IP20 827

**Product code 19193**

Brand PHILIPS
Supply voltage 230V
Output 4.6W
Maximum output 4.6W/1m
Luminous flux 355lumens
Luminaire’s efficiency 77W
Correlated colour temperature warm white 2700K
Lens angle 36
Socket GU10
Cri 80
Protection class IP20
Lifespan 15000h
Height 54.0mm
Width 50.0mm
In package 3pcs
No. of switches 50000pcs



# LED bulb PHILIPS Ultra Effecient spot PAR 16 230V 2.1W 375lm GU10 36° IP20 830

**Product code 19095**

Brand PHILIPS
Supply voltage 230V
Output 2.1W
Luminous flux 375lumens
Luminaire’s efficiency 179W
Correlated colour temperature warm white 3000K
Lens angle 36
Socket GU10
Cri 80
Protection class IP20
Lifespan 50000h
Height 54.0mm
Diameter 50.0mm
No. of switches 50000pcs




# LED bulb PREMIUM SAMSUNG 230V 5W 480lm GU10 80° 830

**Product code 15643**

Brand PREMIUM
Supply voltage 230V
Output 5W
Maximum output 5W/1m
Luminous flux 480lumens
Luminaire’s efficiency 96W
Correlated colour temperature warm white 3000K
Lens angle 80
Socket GU10
Source of light SAMSUNG LED
Cri 80
Lifespan 30000h
Height 55.0mm
Diameter 50.0mm
In package 1pc
In box 100pcs
No. of switches 20000pcs
Work environment indoor use
Operation temperature -20°C - 40°C
Certificates CE
Warranty 3 years



# LED bulb Prolumen CITIZEN DL170L COB 230V 10W 1000lm 36° IP20 DIMMABLE 930

**Product code 14897 dimmerdatav dimmable**

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable dimmerdatav
Output 10W
Maximum output 10W/1m
Luminous flux 1000lumens
Luminaire’s efficiency 100W
Correlated colour temperature warm white 3000K
Lens angle 36
Source of light CITIZEN LED
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70 @25°C 50.000h
Height 51.0mm
Diameter 49.0mm
In box 100pcs
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years



# LED bulb Prolumen CITIZEN DL170L COB 230V 10W 900lm 36° IP20 DIMMABLE 940

**Product code 15280 dimmerdatav**
**dimmable**

Brand Prolumen
Supply voltage 230V
Dimmable dimmerdatav
Output 10W
Maximum output 10W/1m
Luminous flux 900lumens
Luminaire’s efficiency 90W
Correlated colour temperature pure white 4000K
Lens angle 36
Source of light CITIZEN LED
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70 @25°C 50.000h
Height 51.0mm
Diameter 49.0mm
In box 100pcs
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years



*© LED House OÜ, (+372) 56 202 303*
*Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee*

# LED bulb Prolumen CITIZEN DL170L COB 230V 13W 1200lm 36° IP20 DALI 930

**Product code 14847 DALI dimmable**

Brand Prolumen
Supply voltage 230V
Dimmable DALI
Output 13W
Maximum output 13W/1m
Luminous flux 1200lumens
Luminaire’s efficiency 92W
Correlated colour temperature warm white 3000K
Lens angle 36
Source of light CITIZEN LED
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70 @25°C 50.000h
Height 61.0mm
Diameter 49.0mm
In box 100pcs
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years



*© LED House OÜ, (+372) 56 202 303*
*Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee*

# LED bulb Prolumen CITIZEN DL170L COB 230V 13W 1400lm 36° IP20 DALI 930

**Product code 17740 DALI dimmable**

Brand Prolumen
Supply voltage 230V
Dimmable DALI
Output 13W
Maximum output 13W/1m
Luminous flux 1400lumens
Luminaire’s efficiency 108W
Correlated colour temperature warm white 3000K
Lens angle 36
Source of light CITIZEN LED
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70 @25°C 50.000h
Height 61.0mm
Diameter 49.0mm
In box 100pcs
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years



*© LED House OÜ, (+372) 56 202 303*
*Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee*

# LED bulb Prolumen CITIZEN DL170L COB 230V 13W 1400lm 36° IP20 DALI 940

**Product code 17742 DALI dimmable**

Brand Prolumen
Supply voltage 230V
Dimmable DALI
Output 13W
Maximum output 13W/1m
Luminous flux 1400lumens
Luminaire’s efficiency 108W
Correlated colour temperature pure white 4000K
Lens angle 36
Source of light CITIZEN LED
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70 @25°C 50.000h
Height 61.0mm
Diameter 49.0mm
In box 100pcs
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years



# LED bulb Prolumen CITIZEN DL170L COB 230V 18W 1800lm 36° IP20 DIMMABLE 830

**Product code 14848 dimmerdatav**
**dimmable**

Brand Prolumen
Supply voltage 230V
Dimmable dimmerdatav
Output 18W
Maximum output 18W/1m
Luminous flux 1800lumens
Luminaire’s efficiency 100W
Correlated colour temperature warm white 3000K
Lens angle 36
Source of light CITIZEN LED
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70 @25°C 50.000h
Height 81.0mm
Diameter 50.0mm
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years



# LED bulb Prolumen Premium white 230V 9W 1040lm 120° IP20 940

**Product code 23961**

Brand Prolumen
Supply voltage 230V
Output 9W
Maximum output 9W/1m
Luminous flux 1040lumens
Luminaire’s efficiency 116W
Correlated colour temperature pure white 4000K
Lens angle 120
Source of light BRIDGELUX LED
Cri 90
Sdcm - macadam ellipses 4
Protection class IP20
Lifespan 50000h
Height 55.0mm
Diameter 50.0mm
Casing colour white
Work environment indoor use
Operation temperature -20 ~ 40°C
Certificates CE
Warranty 5 years



# LED bulb REVAL BULB ALU PAR30 230V 25W 2300lm E27 30° IP20 DIMMABLE 930

**Product code 15415 dimmerdatav**
**dimmable**

Brand REVAL BULB
Supply voltage 230V
Dimmable dimmerdatav
Output 25W
Maximum output 25W/1m
Luminous flux 2300lumens
Luminaire’s efficiency 92W
Correlated colour temperature warm white 3000K
Lens angle 30
Socket E27
Source of light CREE LED
Cri 90
Protection class IP20
Lifespan 35000h
Height 125.0mm
Diameter 95.0mm
Casing material aluminium
Certificates CE



# LED bulb REVAL BULB PAR30 230V 20W 2000lm E27 60° IP20 DIMMABLE 930

**Product code 17796 dimmerdatav**
**dimmable**

Brand REVAL BULB
Supply voltage 230V
Power factor 0.95
Dimmable dimmerdatav
Output 20W
Maximum output 20W/1m
Luminous flux 2000lumens
Luminaire’s efficiency 100W
Correlated colour temperature warm white 3000K
Lens angle 60
Socket E27
Cri 90
Sdcm - macadam ellipses 5
Protection class IP20
Lifespan 50000h
Height 126.0mm
Diameter 95.0mm
Weight 500 g
Package weight 553 g
In package 1pc
In box 40pcs
Work environment indoor use
Operation temperature -20° - +60°C
Certificates CE, EMC, LVD, RoHS
Warranty 3 years



# LED bulb Star Trading 347-68-3 230V 5.7W 610lm GU10 36° IP20 DIMMABLE 840

**Product code 16438** **dimmerdatav**
**dimmable**

Brand Star Trading
Supply voltage 230V
Dimmable dimmerdatav
Output 5.7W
Maximum output 5.7W/1m
Luminous flux 610lumens
Luminaire’s efficiency 107W
Correlated colour temperature pure white 4000K
Lens angle 36
Socket GU10
Cri 80
Sdcm - macadam ellipses 5
Protection class IP20
Lifespan 15000h
Height 54.0mm
Diameter 50.0mm
In package 1pc
No. of switches 7500pcs
Work environment indoor use
Operation temperature -20° - +40°°C
Certificates CE, RoHS
Warranty 2 years



# LED bulb Star Trading MR16 ST , 12LED 347-70-1 230V 7.4W 540lm GU10 36° IP20 DIMMABLE 927

**Product code 16631** **dimmerdatav**
**dimmable**

Brand Star Trading
Supply voltage 230V
Dimmable dimmerdatav
Output 7.4W
Maximum output 7.4W/1m
Luminous flux 540lumens
Luminaire’s efficiency 73W
Correlated colour temperature warm white 2700K
Lens angle 36
Socket GU10
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 15000h
Height 54.0mm
Diameter 50.0mm
No. of switches 7500pcs
Work environment indoor use
Operation temperature -20° - +40°C
Certificates CE,RoHS
Warranty 2 years




# LED bulb Star Trading PAR38 356-81 230V 15W 1300lm E27 35° IP65 840

**Product code 15805**

Brand Star Trading
Supply voltage 230V
Output 15W
Maximum output 15W/1m
Luminous flux 1300lumens
Luminaire’s efficiency 87W
Correlated colour temperature pure white 4000K
Lens angle 35
Socket E27
Cri 80
Sdcm - macadam ellipses 6
Protection class IP65
Lifespan 15000h
Height 133.0mm
Diameter 121.0mm
No. of switches 12500pcs
Work environment outdoor use
Operation temperature -20 ~ 40°C



# LED bulb Trio Lighting 230V 5W 400lm GU10 switch dimmer 830

**Product code 19501** **switch dimmer dimmable**

Brand Trio Lighting
Supply voltage 230V
Dimmable switch dimmer
Output 5W
Luminous flux 400lumens
Luminaire’s efficiency 80W
Correlated colour temperature warm white 3000K
Socket GU10
Cri 80
Lifespan 25000h
Height 5.5mm
Diameter 5.0mm
No. of switches 15000pcs
Certificates CE



The LED light source with GU10 socket is ideal for use in recessed spotlights. The brightness of the light can be easily dimmed in 3 stages using a conventional light switch. The surface of the light source is absolutely timeless in silver colour. In addition, the luminaires feature modern LED technology, which stands for a high quality of light. LED light sources are characterized by a long service life and low heat generation.

# LED bulb Trio Lighting Led Spot Mini 230V 4W 345lm GU10 90° IP20 DIMMABLE 827

**Product code 23473 dimmerdatav**
**dimmable**

Brand Trio Lighting
Supply voltage 230V
Dimmable dimmerdatav
Output 4W
Maximum output 4W/1m
Luminous flux 345lumens
Luminaire’s efficiency 86W
Correlated colour temperature warm white 2700K
Lens angle 90
Socket GU10
Cri 80
Protection class IP20
Lifespan 25000h
Height 46.0mm
Diameter 35.0mm
Casing material glass
No. of switches 50000pcs



This small light source emits a pleasantly warm light that creates a cosy and inviting atmosphere - ideal for living rooms, bedrooms or hallways. Thanks to its compact size, it can be used particularly flexibly, even in smaller luminaires or where space is limited. It is also suitable for use with external dimmers so that the brightness can be individually and continuously adjusted to suit your mood and requirements. The light source is made of transparent glass. In addition, the luminaires feature modern LED technology, which stands for a high quality of light. LED light sources are characterized by a long service life and low heat generation.

# LED bulb Trio Lighting Mini 230V 4W 345lm GU10 90° IP20 switch dimmer 830

**Product code 23472 switch dimmer dimmable**

Brand Trio Lighting
Supply voltage 230V
Dimmable switch dimmer
Output 4W
Maximum output 4W/1m
Luminous flux 345lumens
Luminaire’s efficiency 86W
Correlated colour temperature warm white 3000K
Lens angle 90
Socket GU10
Cri 80
Protection class IP20
Lifespan 25000h
Height 44.0mm
Diameter 35.0mm
Casing material plastic
No. of switches 50000pcs



This small light source emits a pleasantly warm light that creates a cosy and inviting atmosphere - ideal for living rooms, bedrooms or hallways. Thanks to its compact size, it can be used in a variety of ways, even in smaller luminaires or limited installation situations. It is also suitable for switch dimmers so that the brightness can be conveniently adjusted in three levels (100 %, 50 % and 25 %) - to suit your mood and requirements. The light source is white. In addition, the luminaires feature modern LED technology, which stands for a high quality of light. LED light sources are characterized by a long service life and low heat generation.

# LED bulb Trio Lighting Reality 3 X LED LM 230V 4,5W 345lm GU10 38° IP20 830

**Product code 20886**

Brand Trio Lighting
Supply voltage 230V
Output 4,5W
Luminous flux 345lumens
Correlated colour temperature warm white 3000K
Lens angle 38
Socket GU10
Cri 80
Sdcm - macadam ellipses 6
En62471 1
Protection class IP20
Lifespan 25000h
Height 55.0mm
Diameter 50.0mm
No. of switches 15000pcs
Operation temperature -20° - +40°C
Certificates CE, UKCA, EAC

