

## LED Terrace lighting REVAL BULB Brest silvery round 12V 1W 95lm CRI80 45° IP67 3000K warm white

**Product code 15684**

Price 17,00+VAT

Brand [REVAL BULB](#)

Supply voltage 12V

Output 1W

Luminous flux 95lumens

Luminaire's efficiency 95W

Correlated colour temperature (cct)  
warm white 3000K

Lens angle 45

Source of light OSRAM LED

Cri 80

Protection class IP67

Lifespan 25000h

Height 38.0mm

Diameter 35.0mm

Installation opening diameter 28mm

In package 1pc

In box 12pcs

Casing colour silvery


Casing material aluminum

Shape round

Work environment indoor / outdoor  
use

Operation temperature -25 ~ +45°C

Warranty 2 years



## LED Terrace lighting REVAL BULB Lille silvery round 12V 1W 95lm CRI80 180° IP67 3000K warm white

**Product code 15690**

Price 13,98+VAT

Brand [REVAL BULB](#)

Supply voltage 12V

Output 1W

Luminous flux 95lumens

Luminaire's efficiency 95W

Correlated colour temperature (cct)  
warm white 3000K

Lens angle 180

Source of light [EPISTAR LED](#)

Cri 80

Protection class IP67

Height 39.0mm

Diameter 36.0mm

Installation opening diameter 27mm

Casing colour silvery


Casing material aluminum + plastic

Shape round

Work environment outdoor use

Operation temperature -25 ~ +45°C

Warranty 2 years



## LED downlight REVAL BULB Lucelle black square 230V 3W 300lm CRI90 IP65 3000K warm white

**Product code 16178**

Price 45,00+VAT

Brand [REVAL BULB](#)

Supply voltage 230V

Output 3W

Luminous flux 300lumens

Luminaire's efficiency 100W

Correlated colour temperature (cct)  
warm white 3000K

Source of light [LUMINUS](#)

Cri 90

Protection class IP65

Height 56.0mm

Diameter 55.0mm

Installation opening diameter 49mm

Casing colour black

Casing material aluminum

Polishing matt

Shape square

Power supply AcTEC

Work environment indoor / outdoor  
use

Certificates CE



## LED Terrace lighting REVAL BULB Metz silvery round 12V 3W 280lm CRI80 180° IP67 3000K warm white

**Product code 15697**

Price 22,00+VAT

Brand [REVAL BULB](#)

Supply voltage 12V

Output 3W

Luminous flux 280lumens

Luminaire's efficiency 93W

Correlated colour temperature (cct)

warm white 3000K

Lens angle 180

Source of light OSRAM LED

Cri 80

Protection class IP67

Lifespan 25000h

Height 38.0mm

Diameter 50.0mm

Installation opening diameter 33mm

Casing colour silvery



Casing material aluminum

Shape round

Work environment outdoor use

Operation temperature -25 ~ +45°C

Warranty 2 years



## LED Terrace lighting REVAL BULB Rouen silvery round 12V 1W 95lm CRI80 IP67 3000K warm white

**Product code 15688**

Price 17,00+VAT

Brand [REVAL BULB](#)

Supply voltage 12V

Output 1W

Luminous flux 95lumens

Luminaire's efficiency 95W

Correlated colour temperature (cct)

warm white 3000K

Source of light OSRAM LED

Cri 80

Protection class IP67

Lifespan 25000h

Height 36.0mm

Diameter 35.0mm

Installation opening diameter 27mm

Casing colour silvery

Casing material aluminum

Shape round

Work environment outdoor use

Operation temperature -25 ~ +45°C

Warranty 2 years



## LED Terrace lighting REVAL BULB Sizun PWM dim silvery 24V 3W 180lm 45° IP68 RGB

**Product code 16296**

Price 48,00+VAT

Brand [REVAL BULB](#)

Supply voltage 24V

Output 3W

Luminous flux 180lumens

Luminaire's efficiency 60W

Correlated colour temperature (cct)

RGB RGB

Lens angle 45

Source of light [EPILEDs](#)

Protection class IP68

Lifespan 25000h

Height 67.0mm

Diameter 52.0mm

In package 1pc

In box 12pcs

Casing colour silvery

Casing material aluminum

Work environment indoor / outdoor  
use

Operation temperature -25 ~ +45°C

Warranty 2 years



## LED Terrace lighting REVAL BULB Vichy silvery round 12V 3W 220lm CRI80 30° IP67 3000K warm white

**Product code 15686**

Price 23,00+VAT

Brand [REVAL BULB](#)

Supply voltage 12V

Output 3W

Luminous flux 220lumens

Luminaire's efficiency 73W

Correlated colour temperature (cct)  
warm white 3000K

Lens angle 30

Source of light OSRAM LED

Cri 80

Sdcm - macadam ellipses 6

Protection class IP67

Lifespan 25000h

Height 42.0mm

Diameter 50.0mm

Installation opening diameter 36mm

Casing colour silvery

Casing material aluminum

Shape round

Work environment outdoor use

Operation temperature -25 ~ +45°C

Certificates CE

Warranty 2 years

