

## LED strip remote + controller 230V RF RGB

**Product code 16100**

Maximum output 720W/1m  
Rated current 4000mA



**Controller Deko-Light RF-kontroller - RF-smart, stardikomplekt  
RGB/W/CCT, 12-48 V, 20 A koos puldiga black 12-48V IP20  
PUSH**

**Product code 20809 PUSH dimmable**

Brand [Deko-Light](#)

Supply voltage 12-48V

Dimmable PUSH

Protection class IP20

Lifespan 50000h

Height 25.0mm

Width 120.0mm

Length 47.0mm

In package 1pc

Casing colour black

Casing material plastic

Polishing matt

Work environment indoor / outdoor use

Operation temperature -20 - +50°C

Certificates CE

Warranty 5 years

Dimmable brightness and colour saturation 16 million adjustable colours and adjustable colour temperature 18 pre-installed automatic programs Intelli-Push dim function [on/off, brightness] via potential-free push-button Can be controlled with RF-smart wireless remote controls [2.4 GHz, range approx. 30 m] Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo [Alexa], Google Assistant, Tuya [relevant gateway required, outdoor range up to 100 m] Program and remote control synchronisation when operating multiple RF-smart components [repeater function] Control of RGB/RGBW/RGB+CCT components Flicker-free [images/videos] Power: max. 20 A/controller, max. 10 A/channel 12 V = 240 W, 24 V = 480 W, 48 V = 960 W One control zone Remote control requires 2x AAA batteries [not included in the scope of delivery]



## Controller Deko-Light RF-smart, stardikomplekt LED üksik/CCT, 12-48 V, 20 A koos kaugjuhtimispuldiga black 12-48V IP20

**Product code 20810**

Brand [Deko-Light](#)

Supply voltage 12-48V

Protection class IP20

Height 25.0mm

Width 120.0mm

Length 47.0mm

In package 1pc

Casing colour black

Casing material plastic

Polishing matt

Work environment indoor / outdoor use

Operation temperature -20 - +50°C

Certificates CE

Warranty 5 years

Dimmable brightness and colour saturation Intelli-Push dim function [on/off, brightness] via potential-free push-button Can be controlled with all RF-smart wireless remote controls [2.4 GHz, range approx. 30 m] Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo [Alexa], Google Assistant, Tuya [relevant gateway required, outdoor range up to 100 m] Program and remote control synchronisation when operating multiple RF-smart components [repeater function] Control of single/CCT components Flicker-free [images/videos] Power: max. 20 A/controller, max. 10 A/channel 12 V = 240 W, 24 V = 480 W, 48 V = 960 W One control zone Remote control requires 2x AAA batteries [not included in the scope of delivery]



## LED strip remote + controller LTECH Mini 6 RGB 3x3A white 12-24V

**Product code 14035**

Brand LTECH  
Supply voltage 12-24V  
Rated current 9000mA  
Weight 89 g  
Package weight 120 g  
Casing colour white  
Casing material plastic  
Operation temperature -20°C- +55°C  
Battery DC3V (CR2032)  
Certificates CE, RoHS  
Warranty 3 years



## LED strip remote + controller LTECH Mini 8 RGBW 20A 5-24V

**Product code 13938**

Brand LTECH  
Supply voltage 5-24V  
Maximum output 480W/1m  
Rated current 20000mA  
Weight 125 g  
In package 1pc  
Work environment indoor use  
Operation temperature -30 ° C to 55°C  
Certificates CE, RoHS  
Warranty 3 years



5V 100W 12V 240W 24V 480W

## LED strip remote + controller SKYDANCE R6-1 + V1 set 1 zone 8A 5-36V RF

**Product code 15721 RF dimmable**

Brand [SKYDANCE](#)

Supply voltage 5-36V

Dimmable RF

Output voltage 5-36V

Maximum output 288W/1m

Rated current 8000mA

Weight 89 g

In package 1pc

Casing material plastic

Work environment indoor use

Operation temperature -30~55°C

Battery CR2032

Certificates CE

Warranty 5 years



8A x 1CH 12V - 96W 24V - 192W 1 zone NB! No batteries included.

## LED strip remote + controller SKYDANCE R7-1 + V2 set 12-24V IP20 RF

**Product code 16358 RF dimmable**

Brand [SKYDANCE](#)

Supply voltage 12-24V

Dimmable RF

Maximum output 240W/1m

Rated current 10000mA

Protection class IP20

Height 18.0mm

Width 33.0mm

Length 97.0mm

Weight 89 g

In package 1pc

Work environment indoor use

Operation temperature -30°C~55°C

Battery DC3V CR2032

Certificates CE, RoHS

Warranty 5 years



2x5A

## LED strip remote + controller SKYDANCE R8-1+V3 set RGB 12A 12-24V RF

**Product code 15722 RF dimmable**

Brand [SKYDANCE](#)

Supply voltage 12-24V

Dimmable RF

Maximum output 288W/1m

Rated current 12000mA

In package 1pc

Work environment indoor use

Battery CR2032

Certificates CE



3A x 4CH, Max 12A 12V - 144W 24V - 288W 1 zone NB! No batteries included.

## LED strip remote + controller SKYDANCE R8-1+VP set RGBW 12A 12-24V RF

**Product code 15723 RF dimmable**

Brand [SKYDANCE](#)

Supply voltage 12-24V

Dimmable RF

Maximum output 288W/1m

Rated current 12000mA

Operation temperature -30~55°C

Battery CR2032

Warranty 5 years



3A\*4CH, Max 12A 144W/288W(12/24V) 1 zone NB! Does not include any batteries.

## LED strip remote + controller SKYDANCE RF SPI Controller SC+R9 set 5-24V RF

**Product code 15832 RF dimmable**

Brand [SKYDANCE](#)

Supply voltage 5-24V

Dimmable RF

Height 18.0mm

Width 33.0mm

Length 97.0mm

In package 1pc

Work environment indoor use

Operation temperature -30~55°C

Battery CR2032

Certificates CE

Warranty 5 years

