





## LED dome light module LMM1842 230V 18W 1700lm 180° IP20 842

### **Product code 16303**

Supply voltage 230V Output 18W Luminous flux 1700lumens Luminaire's efficiency Im79 94W Correlated colour temperature pure white 4200K Lens angle 180 Cri 80 Protection class IP20 Lifespan 25000h Height 25.0mm Diameter 215.0mm Weight 100g Package weight 150g No. of switches 15000pcs Work environment indoor use Operation temperature -25 ~ +50°C









Dome light Nairos LX with motion sensor white round 230V 24W 2520lm CRI80 120° IP65 3000K, 4000K, 6000K WW/DW/CW



2/27 20.04.2024



Supply voltage 230V Power factor 0.70 Output 24W Luminous flux 2520lumens Luminaire's efficiency lm79 105W Correlated colour temperature WW/DW/CW 3000K, 4000K, 6000K Lens angle 120 Cri 80 Protection class IP65 Lifespan 30000h Height 55.0mm Diameter 300.0mm Weight 650g In box 5pcs Casing colour white Casing material metal + plastic Shape round No. of switches 20000pcs Impact resistance IK08 Work environment indoor / outdoor Operation temperature -20 ~ +40°C Certificates CE Warranty 3 years

A modern luminaire suitable for both indoor and outdoor use. This round ceiling light fixture features a motion sensor, the option to choose between 3000K, 4000K, and 6500K light temperatures, and can be mounted on both walls and ceilings. With an IP65 protection rating, this luminaire is protected against fine dust and lowpressure jets of water. This allows the luminaire to be used in stairwells, on terraces, in corridors, as well as in office spaces. If you haven't found the perfect light fixture from our product range yet, then browse through the PROLUMEN catalogue as well!





### Dome light PROLUMEN AL08 D250 white 230V 12W 1068lm 120° IP54 830



3/27 20.04.2024

#### Product code 15089

**Brand PROLUMEN** Supply voltage 230V Power factor 0.90 Output 12W Luminous flux 1068lumens Luminaire's efficiency Im79 89W Correlated colour temperature warm white 3000K Lens angle 120 Cri 80 Sdcm - macadam ellipses 6 Protection class IP54 Lifespan 40000h Height 48.0mm Diameter 250.0mm Weight 800g Package weight 930g In box 20pcs Casing colour white Casing material plastic Impact resistance IK08 Operation temperature -20 ~ 45°C Certificates CE, RoHS Warranty 5 years













## Dome light PROLUMEN AL08 D250 with motion sensor white 230V 12W 968lm 120° IP54 930

#### **Product code 17104**

**Brand PROLUMEN** Supply voltage 230V Power factor 0.90 Output 12W Luminous flux 968lumens Luminaire's efficiency Im79 81W Correlated colour temperature warm white 3000K Lens angle 120 Cri 90 Sdcm - macadam ellipses 6 Protection class IP54 Lifespan 40000h Height 48.0mm Diameter 250.0mm Weight 800g Package weight 930g In box 20pcs Casing colour white Casing material plastic Impact resistance IK08 Operation temperature -20 ~ 45°C Certificates CE, RoHS Warranty 5 years














### Dome light PROLUMEN AL08 D300 white 230V 18W 1710lm 120° IP54 830

#### Product code 16581

**Brand PROLUMEN** Supply voltage 230V Power factor 0.90 Output 18W Luminous flux 1710lumens Luminaire's efficiency Im79 95W Correlated colour temperature warm white 3000K Lens angle 120 Cri 80 Sdcm - macadam ellipses 6 Protection class IP54 Lifespan 40000h Height 40.0mm Diameter 300.0mm Weight 800g Package weight 930g In package 1pc In box 10pcs Casing colour white Casing material plastic Impact resistance IK08 Operation temperature -20 ~ 45°C Certificates CE, RoHS Warranty 5 years













### Dome light PROLUMEN AL08 D300 white 230V 18W 1800lm 120° IP54 840

#### **Product code 13448**

**Brand PROLUMEN** Supply voltage 230V Power factor 0.90 Output 18W Luminous flux 1800lumens Luminaire's efficiency Im79 100W Correlated colour temperature pure white 4000K Lens angle 120 Cri 80 Sdcm - macadam ellipses 6 Protection class IP54 Lifespan 40000h Height 48.0mm Diameter 300.0mm Weight 980g Package weight 1110g In box 10pcs Casing colour white Casing material plastic Impact resistance IK08 Operation temperature -20 ~ 45°C Certificates CE, RoHS Warranty 5 years













## Dome light PROLUMEN AL08 D300 with motion sensor white 230V 25W 2550lm 120° IP54 940

#### **Product code 15302**

**Brand PROLUMEN** Supply voltage 230V Power factor 0.90 Output 25W Luminous flux 2550lumens Luminaire's efficiency Im79 102W Correlated colour temperature pure white 4000K Lens angle 120 Cri 90 Sdcm - macadam ellipses 6 Protection class IP54 Lifespan 40000h Height 40.0mm Diameter 300.0mm Weight 800g Package weight 930g In box 10pcs Casing colour white Casing material plastic Impact resistance IK08 Operation temperature -20 ~ 45°C Certificates CE, RoHS Warranty 5 years











3/27 20.04.2024



### Dome light PROLUMEN AL08 D400 white 230V 30W 3000lm 120° IP54 830

#### **Product code 14989**

**Brand PROLUMEN** Supply voltage 230V Power factor 0.90 Output 30W Luminous flux 3000lumens Luminaire's efficiency Im79 100W Correlated colour temperature warm white 3000K Lens angle 120 Cri 80 Sdcm - macadam ellipses 6 Protection class IP54 Lifespan 40000h Height 52.0mm Diameter 400.0mm Weight 1400g Package weight 1700g In package 1pc In box 10pcs Casing colour white Casing material plastic Impact resistance IK08 Operation temperature -20 ~ 45°C Certificates CE, RoHS Warranty 5 years













# Dome light PROLUMEN AL127 D400 DALI white 230V 25W 2400lm 120° IP54 940

#### Product code 16975 DALI dimmable

**Brand PROLUMEN** Supply voltage 230V Power factor 0.90 Dimmable DALI Output 25W Luminous flux 2400lumens Luminaire's efficiency Im79 96W Correlated colour temperature pure white 4000K Lens angle 120 Cri 90 Sdcm - macadam ellipses 6 Protection class IP54 Lifespan 40000h Height 58.0mm Diameter 400.0mm Weight 1920g In package 1pc In box 10pcs Casing colour white Casing material plastic Operation temperature -20 ~ 45°C Certificates CE, RoHS Warranty 5 years



### Dome light PROLUMEN AL37 white 230V 25W 2800lm 100° 930 $\,$



10/27 20.04.2024

#### **Product code 14710**

Brand **PROLUMEN** Supply voltage 230V Output 25W Luminous flux 2800lumens Luminaire's efficiency Im79 112W Correlated colour temperature warm white 3000K Lens angle 100 Cri 90 Lifespan 50000h Height 33.0mm Diameter 400.0mm Weight 1440g Casing colour white Certificates CE, RoHS Warranty 5 years

Compact LED ceiling light for living rooms, bedrooms, and other indoor spaces. Its minimalist design blends perfectly with various interiors, whether at home, in the office, or in a business environment. This luminaire has an ideal color rendering index (CRI90) for workspaces and offices. The light temperature of 3000K adds warm white light to the room. From the LED house product range, you can find several other ceiling lights that complement this luminaire to create unique lighting effects in your space!



# Dome light PROLUMEN AL45 D270 white round 230V 12W 1200lm 120° IP65 840





#### **Product code 15787**

**Brand PROLUMEN** Supply voltage 230V Output 12W Luminous flux 1200lumens Luminaire's efficiency Im79 100W Correlated colour temperature pure white 4000K Lens angle 120 Cri 80 Protection class IP65 Lifespan 50000h Height 70.0mm Diameter 270.0mm Package weight 755g In box 10pcs Casing colour white Casing material plastic Polishing matt Shape round Impact resistance IK10 Work environment indoor / outdoor Operation temperature -20 ~ 45°C Certificates CE Warranty 5 years

Classic LED ceiling light with a round design. Thanks to the IP65 protection class, this luminaire can be used both indoors and outdoors. The luminaire is protected against ordinary dust and splashes from any direction. Options with different light intensities available! 1200lm for example for bedrooms, hallways, smaller office spaces 2500lm for example for living rooms, kitchens, office spaces 3500lm for example for retail spaces, workshops, larger office spaces 4000lm for example for open-plan living areas, retail spaces, indoor parking lots. Possibility to order in light temperatures: 3000K (warm white) and 4000K (daylight white). Possible wattages: 12W, 18W, 25W, 30W, 35W, 40W,







## Dome light PROLUMEN AL45 D320 white round 230V 25W 2500lm 120° IP65 840

#### **Product code 15545**

**Brand PROLUMEN** Supply voltage 230V Output 25W Luminous flux 2500lumens Luminaire's efficiency Im79 100W Correlated colour temperature pure white 4000K Lens angle 120 Cri 80 Protection class IP65 Lifespan 50000h Height 70.0mm Diameter 320.0mm In box 6pcs Casing colour white Casing material plastic Polishing matt Shape round Impact resistance IK10 Work environment indoor / outdoor Operation temperature -20 ~ 45°C Certificates CE Warranty 5 years

Classic LED ceiling light with a round design. Thanks to the IP65 protection class, this luminaire can be used both indoors and outdoors. The luminaire is protected against ordinary dust and splashes from any direction. Options with different light intensities available! 1200lm for example for bedrooms, hallways, smaller office spaces 2500lm for example for living rooms, kitchens, office spaces 3500lm for example for retail spaces, workshops, larger office spaces 4000lm for example for open-plan living areas, retail spaces, indoor parking lots. Possibility to order in light temperatures: 3000K (warm white) and 4000K (daylight white). Possible wattages: 12W, 18W, 25W, 30W, 35W, 40W.







### Dome light PROLUMEN AL45 D520 round 230V 35W 3500lm 120° IP65 940

#### **Product code 15786**

**Brand PROLUMEN** Supply voltage 230V Output 35W Luminous flux 3500lumens Luminaire's efficiency Im79 100W Correlated colour temperature pure white 4000K Lens angle 120 Cri 90 Protection class IP65 Lifespan 50000h Height 85.0mm Diameter 520.0mm In box 6pcs Casing material plastic Polishing matt Shape round Impact resistance IK10 Work environment indoor / outdoor use Operation temperature -20 ~ 45°C Certificates CE Warranty 5 years

Classic LED ceiling light with a round design. Thanks to the IP65 protection class, this luminaire can be used both indoors and outdoors. The luminaire is protected against ordinary dust and splashes from any direction. Options with different light intensities available! 1200lm for example for bedrooms, hallways, smaller office spaces 2500lm for example for living rooms, kitchens, office spaces 3500lm for example for retail spaces, workshops, larger office spaces 4000lm for example for open-plan living areas, retail spaces, indoor parking lots. Possibility to order in light temperatures: 3000K (warm white) and 4000K (daylight white). Possible wattages: 12W, 18W, 25W, 30W, 35W, 40W.







# Dome light PROLUMEN AL45 D520 white round 230V 40W 4000lm CRI80 120° IP65 3000K, 4000K, 5700K WW/DW/CW

#### **Product code 15857**

**Brand PROLUMEN** Supply voltage 230V Output 40W Luminous flux 4000lumens Luminaire's efficiency Im79 100W Correlated colour temperature WW/DW/CW 3000K, 4000K, 5700K Lens angle 120 Cri 80 Protection class IP65 Lifespan 50000h Height 85.0mm Diameter 520.0mm Weight 2400g In box 6pcs Casing colour white Casing material plastic Polishing matt Shape round Impact resistance IK10 Work environment indoor / outdoor Operation temperature -20 ~ 45°C Certificates CE Warranty 5 years

Classic LED ceiling light with a round design. Thanks to the IP65 protection class, this luminaire can be used both indoors and outdoors. The luminaire is protected against ordinary dust and splashes from any direction. Options with different light intensities available! 1200lm for example for bedrooms, hallways, smaller office spaces 2500lm for example for living rooms, kitchens, office spaces 3500lm for example for retail spaces, workshops, larger office spaces 4000lm for example for open-plan living areas, retail spaces, indoor parking lots. Possibility to order in light temperatures: 3000K (warm white) and 4000K (daylight white). Possible wattages: 12W, 18W, 25W, 30W, 35W, 40W.







### Dome light PROLUMEN AL96 D200 black 230V 12W 1000lm 120° IP65 830

### **Product code 16034**

**Brand PROLUMEN** Supply voltage 230V Power factor 0.90 Output 12W Luminous flux 1000lumens Luminaire's efficiency Im79 83W Correlated colour temperature warm white 3000K Lens angle 120 Cri 80 Sdcm - macadam ellipses 6 Protection class IP65 Lifespan 50000h Height 60.0mm Diameter 200.0mm In package 1pc In box 12pcs Casing colour black Casing material plastic Impact resistance IK10 Work environment indoor / outdoor Operation temperature -20 ~ 45°C Certificates CE, RoHS Warranty 5 years

Contemporary designed LED ceiling light. The luminaire is surfacemountable, suitable for both walls and ceilings. As the base and shade cover of the luminaire are separable, maintenance is made particularly easy! The IP65 protection class means that the luminaire is water and dust resistant, making it suitable for both indoor and outdoor use. Additionally, our recommendation is to install it in offices, shops, schools, hotels, stairwells, living rooms and corridors. The luminaire adds warm white light (3000K) to the room, and thanks to CRI90, the colours of illuminated areas remain very true and natural. Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!







### Dome light PROLUMEN AL96 D275 black 230V 18W 1650lm 110° IP65 830

### **Product code 16005**

**Brand PROLUMEN** Supply voltage 230V Power factor 0.90 Output 18W Luminous flux 1650lumens Luminaire's efficiency Im79 92W Correlated colour temperature warm white 3000K Lens angle 110 Cri 80 Sdcm - macadam ellipses 6 Protection class IP65 Lifespan 50000h Height 60.0mm Diameter 275.0mm In package 1pc In box 12pcs Casing colour black Casing material plastic Impact resistance IK10 Work environment indoor / outdoor Operation temperature -20 ~ 45°C Certificates CE, RoHS Warranty 5 years

Contemporary designed LED ceiling light. The luminaire is surfacemountable, suitable for both walls and ceilings. As the base and shade cover of the luminaire are separable, maintenance is made particularly easy! The IP65 protection class means that the luminaire is water and dust resistant, making it suitable for both indoor and outdoor use. Additionally, our recommendation is to install it in offices, shops, schools, hotels, stairwells, living rooms and corridors. The luminaire adds warm white light (3000K) to the room, and thanks to CRI90, the colours of illuminated areas remain very true and natural. Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!







### Dome light PROLUMEN AL96 D350 black 230V 30W 2560lm 120° IP65 930

### **Product code 17233**

**Brand PROLUMEN** Supply voltage 230V Power factor 0.90 Output 30W Luminous flux 2560lumens Luminaire's efficiency Im79 85W Correlated colour temperature warm white 3000K Lens angle 120 Cri 90 Sdcm - macadam ellipses 6 Protection class IP65 Lifespan 50000h Height 60.0mm Diameter 350.0mm In package 1pc In box 6pcs Casing colour black Casing material plastic Impact resistance IK10 Work environment indoor / outdoor Operation temperature -20 ~ 45°C Certificates CE, RoHS Warranty 5 years

Contemporary designed LED ceiling light. The luminaire is surfacemountable, suitable for both walls and ceilings. As the base and shade cover of the luminaire are separable, maintenance is made particularly easy! The IP65 protection class means that the luminaire is water and dust resistant, making it suitable for both indoor and outdoor use. Additionally, our recommendation is to install it in offices, shops, schools, hotels, stairwells, living rooms and corridors. The luminaire adds warm white light (3000K) to the room, and thanks to CRI90, the colours of illuminated areas remain very true and natural. Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!







## Dome light PROLUMEN AL96 D350 DALI black 230V 30W 2560lm 120° IP65 930

#### Product code 17015 DALI dimmable

**Brand PROLUMEN** Supply voltage 230V Power factor 0.90 Dimmable DALI Output 30W Luminous flux 2560lumens Luminaire's efficiency Im79 85W Correlated colour temperature warm white 3000K Lens angle 120 Cri 90 Sdcm - macadam ellipses 6 Protection class IP65 Lifespan 50000h Height 60.0mm Diameter 350.0mm In package 1pc In box 6pcs Casing colour black Casing material plastic Impact resistance IK10 Work environment indoor / outdoor Operation temperature -20 ~ 45°C Certificates CE, RoHS

Contemporary designed LED ceiling light. The luminaire is surfacemountable, suitable for both walls and ceilings. As the base and shade cover of the luminaire are separable, maintenance is made particularly easy! The IP65 protection class means that the luminaire is water and dust resistant, making it suitable for both indoor and outdoor use. Additionally, our recommendation is to install it in offices, shops, schools, hotels, stairwells, living rooms and corridors. The luminaire adds warm white light (3000K) to the room, and thanks to CRI90, the colours of illuminated areas remain very true and natural. Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!

Warranty 5 years








### Dome light Zoe black round 230V 12W 770lm 115° IP44 840

### **Product code 16078**

Supply voltage 230V Output 12W Luminous flux 770lumens Luminaire's efficiency Im79 64W Correlated colour temperature pure white 4000K Lens angle 115 Cri 80 Protection class IP44 Lifespan 25000h Height 80.0mm Diameter 300.0mm Weight 440g In box 5pcs Casing colour black Casing material metal + plastic Shape round No. of switches 15000pcs Work environment indoor / outdoor use Operation temperature -20 ~ +40°C Certificates CE Warranty 3 years










### Dome light Zoe black round 230V 18W 1135lm 115° IP44 840

### **Product code 16079**

Supply voltage 230V Output 18W Luminous flux 1135lumens Luminaire's efficiency Im79 63W Correlated colour temperature pure white 4000K Lens angle 115 Cri 80 Protection class IP44 Lifespan 25000h Height 80.0mm Diameter 300.0mm Weight 450g In box 5pcs Casing colour black Casing material metal + plastic Shape round No. of switches 15000pcs Work environment indoor / outdoor use Operation temperature -20 ~ +40°C Certificates CE Warranty 3 years

LED ceiling light with modern design. The luminaire is surface-mountable, suitable for both walls and ceilings. As the base and cover of the luminaire are separable, maintenance and installation are made exceptionally easy! The luminaire adds daylight (4000K) to the room. Improve the quality of light in your everyday life and choose a top-notch lighting solution from <a







### Dome light Zoe black round 230V 24W 1540lm 115° IP44 840

### **Product code 16080**

Supply voltage 230V Output 24W Luminous flux 1540lumens Luminaire's efficiency Im79 64W Correlated colour temperature pure white 4000K Lens angle 115 Cri 80 Protection class IP44 Lifespan 25000h Height 80.0mm Diameter 300.0mm Weight 540g In box 5pcs Casing colour black Casing material metal + plastic Shape round No. of switches 15000pcs Work environment indoor / outdoor use Operation temperature -20 ~ +40°C Certificates CE Warranty 3 years

LED ceiling light with modern design. The luminaire is surface-mountable, suitable for both walls and ceilings. As the base and cover of the luminaire are separable, maintenance and installation are made exceptionally easy! The luminaire adds daylight (4000K) to the room. Improve the quality of light in your everyday life and choose a top-notch lighting solution from <a







## Dome light Zoe LX with motion sensor black round 230V 24W 1540lm 115° IP44 840

#### **Product code 16735**

Supply voltage 230V Output 24W Luminous flux 1540lumens Luminaire's efficiency Im79 64W Correlated colour temperature pure white 4000K Lens angle 115 Cri 80 Protection class IP44 Lifespan 25000h Height 80.0mm Diameter 300.0mm Weight 650g In box 5pcs Casing colour black Casing material metal + plastic Shape round No. of switches 15000pcs Work environment indoor / outdoor use Operation temperature -20 ~ +40°C Certificates CE Warranty 3 years

LED ceiling light with modern design. The luminaire is surface-mountable, suitable for both walls and ceilings. As the base and cover of the luminaire are separable, maintenance and installation are made exceptionally easy! The luminaire adds daylight (4000K) to the room. Improve the quality of light in your everyday life and choose a top-notch lighting solution from <a







# Dome light Zoe LX with motion sensor white round 230V 19W 1284lm 115° IP44 840

### Product code 17135

Supply voltage 230V Output 19W Luminous flux 1284lumens Luminaire's efficiency Im79 68W Correlated colour temperature pure white 4000K Lens angle 115 Cri 80 Protection class IP44 Lifespan 25000h Height 80.0mm Diameter 300.0mm Weight 450g In box 5pcs Casing colour white Casing material metal + plastic Shape round No. of switches 15000pcs Work environment indoor / outdoor use Operation temperature -20 ~ +40°C Certificates CE Warranty 3 years






# Dome light Zoe LX with motion sensor white round 230V 24W 1712lm 115° IP44 840

#### **Product code 16732**

Supply voltage 230V Output 24W Luminous flux 1712lumens Luminaire's efficiency Im79 71W Correlated colour temperature pure white 4000K Lens angle 115 Cri 80 Protection class IP44 Lifespan 25000h Height 80.0mm Diameter 300.0mm Weight 650g In box 5pcs Casing colour white Casing material metal + plastic Shape round No. of switches 15000pcs Work environment indoor / outdoor use Operation temperature -20 ~ +40°C Certificates CE Warranty 3 years







### Dome light Zoe white round 230V 12W 856lm 115° IP44 840

### **Product code 16075**

Supply voltage 230V Output 12W Luminous flux 856lumens Luminaire's efficiency Im79 71W Correlated colour temperature pure white 4000K Lens angle 115 Cri 80 Protection class IP44 Lifespan 25000h Height 80.0mm Diameter 300.0mm Weight 440g In box 5pcs Casing colour white Casing material metal + plastic Shape round No. of switches 15000pcs Work environment indoor / outdoor use Operation temperature -20 ~ +40°C Certificates CE Warranty 3 years





### Dome light Zoe white round 230V 18W 1284lm 115° IP44 840

### **Product code 16076**

Supply voltage 230V Output 18W Luminous flux 1284lumens Luminaire's efficiency Im79 71W Correlated colour temperature pure white 4000K Lens angle 115 Cri 80 Protection class IP44 Lifespan 25000h Height 80.0mm Diameter 300.0mm Weight 450g In box 5pcs Casing colour white Casing material metal + plastic Shape round No. of switches 15000pcs Work environment indoor / outdoor use Operation temperature -20 ~ +40°C Certificates CE Warranty 3 years





### **Dome light Zoe white round 230V 24W 1712lm 115° IP44 840**

### **Product code 16077**

Supply voltage 230V Output 24W Luminous flux 1712lumens Luminaire's efficiency Im79 71W Correlated colour temperature pure white 4000K Lens angle 115 Cri 80 Protection class IP44 Lifespan 25000h Height 80.0mm Diameter 300.0mm Weight 540g In box 5pcs Casing colour white Casing material metal + plastic Shape round No. of switches 15000pcs Work environment indoor / outdoor use Operation temperature -20 ~ +40°C Certificates CE Warranty 3 years