Signal amplifier 4x6A 12-24V 576W IP20

Product code 15587

Supply voltage 12-24V
Output 576W
Maximum output 576W/1m
Rated current 24000mA
Protection class IP20
Height 24.0mm
Width 55.0mm
Length 65.0mm
Weight 100 g
Casing material aluminium
Work environment indoor use
Certificates CE
Warranty 2 years



Signal amplifier LTECH LT-122 SPI 5-36V IP67

Product code 15908

Brand LTECH
Supply voltage 5-36V
Protection class IP67
Warranty 5 years



Signal amplifier LTECH LT-3060 24A 5-24V 576W

Product code 13790

Brand LTECH
Supply voltage 5-24V
Output 576W
Maximum output 576W/1m
Rated current 24000mA
Height 23.0mm
Width 87.0mm
Length 148.0mm
Weight 380 g
Operation temperature -30℃~65°C
Certificates CE, RoHS
Warranty 3 years



Signal amplifier SKYDANCE EV3 3x6A 12-36V 648W IP20

Product code 16454

Brand SKYDANCE
Supply voltage 12-36V
Output 648W
Maximum output 648W/1m
Rated current 18000mA
Protection class IP20
Height 27.0mm
Width 45.0mm
Length 175.0mm
Weight 109 g
Package weight 129 g
Casing material plastic
Work environment indoor use
Operation temperature -30~55°C
Certificates CE, EMC, LVD
Warranty 5 years



Signal amplifier SKYDANCE EV4 4x5A 12-24V IP20

Product code 16968

Brand SKYDANCE
Supply voltage 12-24V
Maximum output 480W/1m
Rated current 20000mA
Protection class IP20
Height 27.0mm
Width 45.0mm
Length 175.0mm
Weight 120 g
Package weight 140 g
Casing material plastic
Work environment indoor use
Operation temperature -30~55°C
Certificates CE
Warranty 5 years



Signal amplifier SKYDANCE EV4-X 4x8A 12-24V IP20

Product code 16967

Brand SKYDANCE
Supply voltage 12-24V
Maximum output 768W/1m
Rated current 32000mA
Protection class IP20
Height 24.5mm
Width 76.0mm
Length 107.0mm
Weight 267 g
Package weight 287 g
Casing material aluminium
Work environment indoor use
Operation temperature -30~55°C
Certificates CE
Warranty 5 years



Signal amplifier SKYDANCE SPI SA 5-24V IP20 RF

Product code 15831 RF dimmable

Brand SKYDANCE
Supply voltage 5-24V
Dimmable RF
Protection class IP20
Height 26.0mm
Width 52.0mm
Length 52.0mm
In package 1pc
Work environment indoor use
Operation temperature -30~55°C
Certificates CE
Warranty 5 years

