



LED floodlight BLP-F24A50P black 230V 47W 7500lm 120° IP66 0-10V 730

Product code 18284 0-10V dimmable

Supply voltage 230V Power factor 0.95 Dimmable 0-10V Output 47W Maximum output 47W/1m Luminous flux 7500lumens Luminaire's efficiency Im79 160W Correlated colour temperature warm white 3000K Lens angle 120 Cri 70 Sdcm - macadam ellipses 3 Protection class IP66 Lifespan 50000h Llmf tm21 L80B50 @25°C 50.000h Height 142.0mm Width 200.0mm Length 265.0mm Weight 2300g In package 1pc Casing colour black Casing material aluminum Polishing matt Power supply **SOSEN** Impact resistance IK08 Work environment indoor / outdoor use Operation temperature -25°C - +45°C Certificates CE, RoHS Warranty 5 years

A reliable LED floodlight for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - let's bring your vision to life!





LED floodlight EMOS ASIMO black 230V 200W 22000lm 55x125° IP66 840

Product code 16608

Brand EMOS Supply voltage 230V Power factor 0.90 Output 200W Maximum output 200W/1m Luminous flux 22000lumens Luminaire's efficiency Im79 110W Correlated colour temperature pure white 4000K Lens angle 55x125 Cri 80 Protection class IP66 Lifespan 50000h Height 70.0mm Width 300.0mm Length 305.0mm Casing colour black Casing material aluminum + glass Impact resistance IK08 Work environment outdoor use Operation temperature -30 ~ 50°C Warranty 5 years

A reliable LED floodlight for illuminating areas and parking lots. The floodlight's protection class is IP66, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - let's bring your vision to life!







LED floodlight EMOS ASIMO black 230V 300W 33000lm 55x125° IP66 840

Product code 16609

Brand EMOS Supply voltage 230V Power factor 0.90 Output 300W Maximum output 300W/1m Luminous flux 33000lumens Luminaire's efficiency Im79 110W Correlated colour temperature pure white 4000K Lens angle 55x125 Cri 80 Protection class IP66 Lifespan 50000h Height 80.0mm Width 363.0mm Length 370.0mm In package 1pc Casing colour black Casing material aluminum + glass Impact resistance IK08 Work environment outdoor use Operation temperature -30 ~ 50°C Warranty 5 years

A reliable <u>LED floodlight</u> for illuminating areas and parking lots. The floodlight's protection class is IP66, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - <u>let's bring your vision to life!</u>







LED floodlight EMOS INOVO black 230V 20W 2200lm 120° IP65 840

Product code 16516

Brand EMOS Supply voltage 230V Power factor 0.70 Output 20W Maximum output 20W/1m Luminous flux 2200lumens Luminaire's efficiency Im79 110W Correlated colour temperature pure white 4000K Lens angle 120 Cri 80 Protection class IP65 Lifespan 50000h Height 28.0mm Width 95.0mm Length 135.0mm In package 1pc Casing colour black Casing material aluminum + glass Impact resistance IK07 Work environment outdoor use Operation temperature -20 ~ 40°C Warranty 5 years

A reliable LED floodlight for illuminating areas and parking lots. The floodlight's protection class is IP65, which means the light fixture withstands outdoor conditions excellently. Emos lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - let's bring your vision to life!









LED floodlight LEDVANCE FL 50 P black 230V 27-41W 6000lm 100° IP66 840

Product code 19186

Brand LEDVANCE Supply voltage 230V Output 27-41W Maximum output 41W/1m Luminous flux 6000lumens Correlated colour temperature pure white 4000K Lens angle 100 Cri 80 Sdcm - macadam ellipses 5 En62471 1 Protection class IP66 Lifespan 100000h Height 179.0mm Width 43.0mm Length 201.0mm Weight 830g Casing colour black Casing material aluminum Impact resistance IK07 Work environment outdoor use Operation temperature -30...+50°C Certificates CE, CB, ENEC, EAC, UKCA, **EPD**







Floodlight Piston 140 black 12V 16W 1419lm 60° IP67 RGB+4000K RGBW pure white

Product code 19107

Supply voltage 12V Output 16W Maximum output 16W/1m Luminous flux 1419lumens Luminaire's efficiency Im79 89W Correlated colour temperature RGBW pure white RGB+4000K Lens angle 60 Sdcm - macadam ellipses 3 Protection class IP67 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 60.0mm Width 168.0mm Length 185.0mm In package 1pc Casing colour black Casing material aluminum + plastic Polishing matt Impact resistance IK10 Work environment outdoor use Operation temperature -40 ~ 45°C Certificates CE Warranty 5 years





5.08.2025



Floodlight Piston 200 gray 36W 2232lm 40° IP67 RGB+4000K RGBW pure white

Product code 19114

Output 36W Maximum output 36W/1m Luminous flux 2232lumens Luminaire's efficiency Im79 62W Correlated colour temperature RGBW pure white RGB+4000K Lens angle 40 Sdcm - macadam ellipses 3 Protection class IP67 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 60.0mm Width 228.0mm Length 233.0mm In package 1pc Casing colour gray Casing material aluminum + plastic Polishing matt Impact resistance IK10 Work environment outdoor use Operation temperature -40 ~ 45°C Certificates CE Warranty 5 years



Floodlight Piston 200 gray 66W 8008lm IP67 4000K pure white

Product code 19112

Warranty 5 years

Output 66W Maximum output 66W/1m Luminous flux 8008lumens Luminaire's efficiency lm79 121W Correlated colour temperature pure white 4000K Sdcm - macadam ellipses 3 Protection class IP67 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 60.0mm Width 228.0mm Length 233.0mm In package 1pc Casing colour gray Casing material aluminum + plastic Polishing matt Impact resistance IK10 Work environment outdoor use Operation temperature -40 ~ 45°C Certificates CE







Floodlight Piston 200 LV gray 44W 6025lm IP67 3000K warm white

Product code 19110

Output 44W Maximum output 44W/1m Luminous flux 6025lumens Luminaire's efficiency Im79 137W Correlated colour temperature warm white 3000K Sdcm - macadam ellipses 3 Protection class IP67 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 60.0mm Width 228.0mm Length 233.0mm In package 1pc Casing colour gray Casing material aluminum + plastic Polishing matt Impact resistance IK10 Work environment outdoor use Operation temperature -40 ~ 45°C Certificates CE Warranty 5 years



Floodlight Piston 200 LV gray 66W 7528lm IP67 3000K warm white

Product code 19109

Warranty 5 years

Output 66W Maximum output 66W/1m Luminous flux 7528lumens Luminaire's efficiency Im79 114W Correlated colour temperature warm white 3000K Sdcm - macadam ellipses 3 Protection class IP67 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 60.0mm Width 228.0mm Length 233.0mm In package 1pc Casing colour gray Casing material aluminum + plastic Polishing matt Impact resistance IK10 Work environment outdoor use Operation temperature -40 ~ 45°C Certificates CE







LED floodlight PROLUMEN AKITA gray 230V 600W 76330lm 20x40° IP66 0-10V 750

Product code 17776 0-10V dimmable

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Dimmable 0-10V Output 600W Maximum output 600W/1m Luminous flux 76330lumens Luminaire's efficiency Im79 127W Correlated colour temperature pure white 5700K Lens angle 20x40 Source of light OSRAM LED Cri 70 Protection class IP66 Lifespan 50000h Height 311.0mm Width 308.0mm Length 686.0mm Weight 13000g Casing colour gray Casing material aluminum Power supply **INVENTRONICS** Impact resistance IK10 Work environment outdoor use Operation temperature -40° - +50°C Certificates ENEC, CE, CB







LED floodlight PROLUMEN AKITA gray 230V 600W 89307lm 50° IP66 0-10V 750

Product code 17775 0-10V dimmable

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Dimmable 0-10V Output 600W Maximum output 600W/1m Luminous flux 89307lumens Luminaire's efficiency Im79 149W Correlated colour temperature pure white 5700K Lens angle 50 Source of light **LUMILEDS** Cri 70 Protection class IP66 Lifespan 50000h Height 311.0mm Width 308.0mm Length 686.0mm Weight 13000g Casing colour gray Casing material aluminum Power supply **INVENTRONICS** Impact resistance IK10 Work environment outdoor use Operation temperature -40° - +50°C Certificates ENEC, CE, CB







Floodlight PROLUMEN FLV black 230V 70W 8400lm 120° IP65 830

Product code 16208

Brand PROLUMEN Supply voltage 230V Output 70W Maximum output 70W/1m Luminous flux 8400lumens Luminaire's efficiency Im79 120W Correlated colour temperature warm white 3000K Lens angle 120 Source of light **CREE LED** Cri 80 Protection class IP65 Lifespan 50000h Casing colour black Casing material aluminum + glass Impact resistance IK08 Work environment outdoor use Warranty 5 years

A reliable LED floodlight for illuminating areas and parking lots. The floodlight's protection class is IP65, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - let's bring your vision to life!







LED floodlight PROLUMEN Light Slim G3 100W 15000lm 120x150° No dim 740

Product code 18974 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 100W
Maximum output 100W/1m
Luminous flux 15000lumens
Luminaire's efficiency Im79 150W
Correlated colour temperature pure white 4000K
Lens angle 120x150
Cri 70
Power supply MEAN WELL
Warranty 5 years

A reliable <u>LED floodlight</u> for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - let's bring your vision to life!





LED floodlight PROLUMEN Light Slim G3 100W 15000lm 120x150° No dim 750

Product code 18978 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 100W
Maximum output 100W/1m
Luminous flux 15000lumens
Luminaire's efficiency Im79 150W
Correlated colour temperature pure white 5000K
Lens angle 120x150
Cri 70
Power supply OSRAM
Warranty 5 years







LED floodlight PROLUMEN Light Slim G3 100W 15000lm 120x150° No dim 750

Product code 18979 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 100W
Maximum output 100W/1m
Luminous flux 15000lumens
Luminaire's efficiency Im79 150W
Correlated colour temperature pure white 5000K
Lens angle 120x150
Cri 70
Power supply MEAN WELL
Warranty 5 years

A reliable <u>LED floodlight</u> for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - let's bring your vision to life!





LED floodlight PROLUMEN Light Slim G3 100W 16000lm 120x150° No dim 750

Product code 18990 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 100W
Maximum output 100W/1m
Luminous flux 16000lumens
Luminaire's efficiency Im79 160W
Correlated colour temperature pure white 5000K
Lens angle 120x150
Cri 70
Power supply SOSEN
Warranty 5 years







LED floodlight PROLUMEN Light Slim G3 150W 22500lm 120x150° No dim 740

Product code 18975 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 150W
Maximum output 150W/1m
Luminous flux 22500lumens
Luminaire's efficiency Im79 150W
Correlated colour temperature pure white 4000K
Lens angle 120x150
Cri 70
Power supply MEAN WELL
Warranty 5 years







LED floodlight PROLUMEN Light Slim G3 150W 22500lm 120x150° No dim 750

Product code 18980 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 150W
Maximum output 150W/1m
Luminous flux 22500lumens
Luminaire's efficiency Im79 150W
Correlated colour temperature pure white 5000K
Lens angle 120x150
Cri 70
Power supply OSRAM
Warranty 5 years







LED floodlight PROLUMEN Light Slim G3 150W 22500lm 120x150° No dim 750

Product code 18981 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 150W
Maximum output 150W/1m
Luminous flux 22500lumens
Luminaire's efficiency Im79 150W
Correlated colour temperature pure white 5000K
Lens angle 120x150
Cri 70
Power supply MEAN WELL
Warranty 5 years

A reliable <u>LED floodlight</u> for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - let's bring your vision to life!





LED floodlight PROLUMEN Light Slim G3 150W 25500lm 100x60° No dim 750

Product code 18995 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 150W
Maximum output 150W/1m
Luminous flux 25500lumens
Luminaire's efficiency Im79 170W
Correlated colour temperature pure white 5000K
Lens angle 100x60
Cri 70
Power supply SOSEN
Warranty 5 years







LED floodlight PROLUMEN Light Slim G3 150W 25500lm 120x150° No dim 750

Product code 18991 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 150W
Maximum output 150W/1m
Luminous flux 25500lumens
Luminaire's efficiency Im79 170W
Correlated colour temperature pure white 5000K
Lens angle 120x150
Cri 70
Power supply SOSEN
Warranty 5 years

A reliable <u>LED floodlight</u> for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - let's bring your vision to life!





LED floodlight PROLUMEN Light Slim G3 200W 34000lm 100x60° No dim 750

Product code 18996 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 200W
Maximum output 200W/1m
Luminous flux 34000lumens
Luminaire's efficiency Im79 170W
Correlated colour temperature pure white 5000K
Lens angle 100x60
Cri 70
Power supply SOSEN
Warranty 5 years








LED floodlight PROLUMEN Light Slim G3 200W 34000lm MLP30° No dim 740

Product code 18976 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 200W
Maximum output 200W/1m
Luminous flux 34000lumens
Luminaire's efficiency Im79 170W
Correlated colour temperature pure
white 4000K
Lens angle MLP30
Cri 70
Power supply MEAN WELL
Warranty 5 years







LED floodlight PROLUMEN Light Slim G3 200W 34000lm MLP30° No dim 750

Product code 18982 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 200W
Maximum output 200W/1m
Luminous flux 34000lumens
Luminaire's efficiency Im79 170W
Correlated colour temperature pure white 5000K
Lens angle MLP30
Cri 70
Power supply OSRAM
Warranty 5 years








LED floodlight PROLUMEN Light Slim G3 200W 34000lm MLP30° No dim 750

Product code 18983 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 200W
Maximum output 200W/1m
Luminous flux 34000lumens
Luminaire's efficiency Im79 170W
Correlated colour temperature pure white 5000K
Lens angle MLP30
Cri 70
Power supply MEAN WELL
Warranty 5 years







LED floodlight PROLUMEN Light Slim G3 200W 34000lm P45° No dim 740

Product code 18987 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 200W
Maximum output 200W/1m
Luminous flux 34000lumens
Luminaire's efficiency Im79 170W
Correlated colour temperature pure white 4000K
Lens angle P45
Cri 70
Power supply SOSEN
Warranty 5 years







LED floodlight PROLUMEN Light Slim G3 200W 34000lm P45° No dim 750

Product code 18992 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 200W
Maximum output 200W/1m
Luminous flux 34000lumens
Luminaire's efficiency Im79 170W
Correlated colour temperature pure white 5000K
Lens angle P45
Cri 70
Power supply SOSEN
Warranty 5 years

A reliable <u>LED floodlight</u> for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - let's bring your vision to life!





LED floodlight PROLUMEN Light Slim G3 240W 40800lm 25° No dim 750

Product code 18997 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 240W
Maximum output 240W/1m
Luminous flux 40800lumens
Luminaire's efficiency Im79 170W
Correlated colour temperature pure white 5000K
Lens angle 25
Cri 70
Power supply SOSEN
Warranty 5 years







LED floodlight PROLUMEN Light Slim G3 240W 40800lm MLP30° No dim 740

Product code 18977 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 240W
Maximum output 240W/1m
Luminous flux 40800lumens
Luminaire's efficiency Im79 170W
Correlated colour temperature pure white 4000K
Lens angle MLP30
Cri 70
Power supply MEAN WELL
Warranty 5 years

A reliable <u>LED floodlight</u> for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - let's bring your vision to life!





LED floodlight PROLUMEN Light Slim G3 240W 40800lm MLP30° No dim 750

Product code 18984 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 240W
Maximum output 240W/1m
Luminous flux 40800lumens
Luminaire's efficiency Im79 170W
Correlated colour temperature pure white 5000K
Lens angle MLP30
Cri 70
Power supply MEAN WELL
Warranty 5 years







LED floodlight PROLUMEN Light Slim G3 240W 40800lm P45° No dim 740

Product code 18988 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 240W
Maximum output 240W/1m
Luminous flux 40800lumens
Luminaire's efficiency Im79 170W
Correlated colour temperature pure white 4000K
Lens angle P45
Cri 70
Power supply SOSEN
Warranty 5 years

A reliable <u>LED floodlight</u> for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - let's bring your vision to life!





LED floodlight PROLUMEN Light Slim G3 240W 40800lm P45° No dim 750

Product code 18993 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 240W
Maximum output 240W/1m
Luminous flux 40800lumens
Luminaire's efficiency Im79 170W
Correlated colour temperature pure white 5000K
Lens angle P45
Cri 70
Power supply SOSEN
Warranty 5 years








LED floodlight PROLUMEN Light Slim G3 400W 68000lm 25° No dim 750

Product code 18998 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 400W
Maximum output 400W/1m
Luminous flux 68000lumens
Luminaire's efficiency Im79 170W
Correlated colour temperature pure white 5000K
Lens angle 25
Cri 70
Power supply SOSEN
Warranty 5 years







LED floodlight PROLUMEN Light Slim G3 400W 68000lm MLP30° No dim 750

Product code 18985 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 400W
Maximum output 400W/1m
Luminous flux 68000lumens
Luminaire's efficiency Im79 170W
Correlated colour temperature pure white 5000K
Lens angle MLP30
Cri 70
Power supply MEAN WELL
Warranty 5 years







LED floodlight PROLUMEN Light Slim G3 400W 68000lm P45° No dim 740

Product code 18989 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 400W
Maximum output 400W/1m
Luminous flux 68000lumens
Luminaire's efficiency Im79 170W
Correlated colour temperature pure white 4000K
Lens angle P45
Cri 70
Power supply SOSEN
Warranty 5 years

A reliable <u>LED floodlight</u> for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - <u>let's bring your vision to life!</u>





LED floodlight PROLUMEN Light Slim G3 400W 68000lm P45° No dim 750

Product code 18994 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 400W
Maximum output 400W/1m
Luminous flux 68000lumens
Luminaire's efficiency Im79 170W
Correlated colour temperature pure white 5000K
Lens angle P45
Cri 70
Power supply SOSEN
Warranty 5 years







LED floodlight PROLUMEN Recon

Product code 18973

Brand <u>PROLUMEN</u> Warranty 2 years

A reliable LED floodlight for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - let's bring your vision to life!





LED floodlight PROLUMEN Recon 30W 4500lm 120° No dim 750

Product code 18971 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 30W
Maximum output 30W/1m
Luminous flux 4500lumens
Luminaire's efficiency Im79 150W
Correlated colour temperature pure white 5000K
Lens angle 120
Cri 70
Power supply DONE
Warranty 3 years

A reliable LED floodlight for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - let's bring your vision to life!







LED floodlight PROLUMEN Recon 50W 7500lm 120° No dim 750

Product code 18972 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 50W
Maximum output 50W/1m
Luminous flux 7500lumens
Luminaire's efficiency Im79 150W
Correlated colour temperature pure white 5000K
Lens angle 120
Cri 70
Power supply DONE
Warranty 3 years

A reliable LED floodlight for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - let's bring your vision to life!





LED floodlight PROLUMEN Recon black 230V 100W 15000lm 90° IP66 740




Product code 16421

Brand PROLUMEN Supply voltage 230V Power factor 0.90 Output 100W Maximum output 100W/1m Luminous flux 15000lumens Luminaire's efficiency Im79 150W Correlated colour temperature pure white 4000K Lens angle 90 Source of light PHILIPS LED Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 35000h Llmf tm21 L80B10 @25°C 50.000h Height 53.0mm Width 319.0mm Length 354.0mm In package 1pc In box 4pcs Casing colour black Casing material aluminum Polishing matt No. of switches 30000pcs Power supply SOSEN Impact resistance IK08 Work environment indoor / outdoor use Operation temperature -25°C - +45°C Certificates CE, RoHS

A reliable LED floodlight for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - let's bring your vision to life!









LED floodlight PROLUMEN Recon black 230V 150W 22500lm 90° IP66 740

Product code 16422

Brand PROLUMEN Supply voltage 230V Power factor 0.90 Output 150W Maximum output 150W/1m Luminous flux 22500lumens Luminaire's efficiency Im79 150W Correlated colour temperature pure white 4000K Lens angle 90 Source of light PHILIPS LED Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 35000h Llmf tm21 L80B10 @25°C 50.000h Height 63.0mm Width 359.0mm Length 400.0mm In package 1pc In box 4pcs Casing colour black Casing material aluminum Polishing matt No. of switches 30000pcs Power supply **SOSEN** Impact resistance IK08 Work environment indoor / outdoor use Operation temperature -25°C - +45°C Certificates CE, RoHS

A reliable <u>LED floodlight</u> for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - <u>let's bring your vision to life!</u>









LED floodlight PROLUMEN Recon black 230V 200W 30000lm 90° IP66 740

Product code 16423

Brand PROLUMEN Supply voltage 230V Power factor 0.90 Output 200W Maximum output 200W/1m Luminous flux 30000lumens Luminaire's efficiency Im79 150W Correlated colour temperature pure white 4000K Lens angle 90 Source of light PHILIPS LED Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 35000h Llmf tm21 L80B10 @25°C 50.000h Height 63.0mm Width 389.0mm Length 430.0mm In package 1pc In box 3pcs Casing colour black Casing material aluminum Polishing matt No. of switches 30000pcs Power supply **SOSEN** Impact resistance IK08 Work environment indoor / outdoor use Operation temperature -25°C - +45°C Certificates CE, RoHS

A reliable <u>LED floodlight</u> for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - <u>let's bring your vision to life!</u>









LED floodlight PROLUMEN Recon black 230V 200W 30000lm 90° IP66 750

Product code 17079

Brand PROLUMEN Supply voltage 230V Power factor 0.90 Output 200W Maximum output 200W/1m Luminous flux 30000lumens Luminaire's efficiency Im79 150W Correlated colour temperature pure white 5000K Lens angle 90 Source of light PHILIPS LED Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 35000h Llmf tm21 L80B10 @25°C 50.000h Height 63.0mm Width 389.0mm Length 430.0mm In package 1pc In box 3pcs Casing colour black Casing material aluminum Polishing matt No. of switches 30000pcs Power supply **SOSEN** Impact resistance IK08 Work environment indoor / outdoor use Operation temperature -25°C - +45°C Certificates CE, RoHS

A reliable <u>LED floodlight</u> for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - <u>let's bring your vision to life!</u>









LED floodlight PROLUMEN Recon black 230V 30W 4000lm 120° IP66 727

Product code 18004

Brand PROLUMEN Supply voltage 230V Power factor 0.90 Output 30W Maximum output 30W/1m Luminous flux 4000lumens Luminaire's efficiency Im79 133W Correlated colour temperature warm white 2700K Lens angle 120 Source of light PHILIPS LED Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 35000h Llmf tm21 L80B10 @25°C 50.000h Height 53.0mm Width 204.0mm Length 232.0mm In package 1pc In box 5pcs Casing colour black Casing material aluminum Polishing matt No. of switches 30000pcs Power supply TUREFUL Impact resistance IK08 Work environment indoor / outdoor use Operation temperature -25°C - +45°C Certificates CE, RoHS

A reliable <u>LED floodlight</u> for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - <u>let's bring your vision to life!</u>









LED floodlight PROLUMEN Recon black 230V 30W 4500lm 120° IP66 740

Product code 17225

Brand PROLUMEN Supply voltage 230V Power factor 0.90 Output 30W Maximum output 30W/1m Luminous flux 4500lumens Luminaire's efficiency Im79 150W Correlated colour temperature pure white 4000K Lens angle 120 Source of light PHILIPS LED Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 35000h Llmf tm21 L80B10 @25°C 50.000h Height 53.0mm Width 204.0mm Length 232.0mm In package 1pc In box 5pcs Casing colour black Casing material aluminum Polishing matt No. of switches 30000pcs Power supply TUREFUL Impact resistance IK08 Work environment indoor / outdoor use Operation temperature -25°C - +45°C Certificates CE, RoHS

A reliable LED floodlight for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - let's bring your vision to life!









LED floodlight PROLUMEN Recon black 230V 30W 4500lm 120° IP66 750

Product code 16328

Brand PROLUMEN Supply voltage 230V Power factor 0.90 Output 30W Maximum output 30W/1m Luminous flux 4500lumens Luminaire's efficiency Im79 150W Correlated colour temperature pure white 5000K Lens angle 120 Source of light PHILIPS LED Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 35000h Llmf tm21 L80B10 @25°C 50.000h Height 53.0mm Width 204.0mm Length 232.0mm In package 1pc In box 5pcs Casing colour black Casing material aluminum Polishing matt No. of switches 30000pcs Power supply TUREFUL Impact resistance IK08 Work environment indoor / outdoor use Operation temperature -25°C - +45°C Certificates CE, RoHS

A reliable <u>LED floodlight</u> for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - <u>let's bring your vision to life!</u>









LED floodlight PROLUMEN Recon black 230V 50W 6500lm 120° IP66 727

Product code 18005

Brand PROLUMEN Supply voltage 230V Power factor 0.90 Output 50W Maximum output 50W/1m Luminous flux 6500lumens Luminaire's efficiency Im79 130W Correlated colour temperature warm white 2700K Lens angle 120 Source of light PHILIPS LED Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 35000h Llmf tm21 L80B10 @25°C 50.000h Height 53.0mm Width 245.0mm Length 280.0mm In package 1pc In box 5pcs Casing colour black Casing material aluminum Polishing matt No. of switches 30000pcs Power supply **DONE** Impact resistance IK08 Work environment indoor / outdoor use Operation temperature -25°C - +45°C Certificates CE, RoHS

A reliable <u>LED floodlight</u> for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - <u>let's bring your vision to life!</u>









LED floodlight PROLUMEN Recon black 230V 50W 7500lm 120° IP66 740

Product code 17585

Brand PROLUMEN Supply voltage 230V Power factor 0.90 Output 50W Maximum output 50W/1m Luminous flux 7500lumens Luminaire's efficiency Im79 150W Correlated colour temperature pure white 4000K Lens angle 120 Source of light PHILIPS LED Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 35000h Llmf tm21 L80B10 @25°C 50.000h Height 53.0mm Width 245.0mm Length 280.0mm In package 1pc In box 5pcs Casing colour black Casing material aluminum Polishing matt No. of switches 30000pcs Power supply **DONE** Impact resistance IK08 Work environment indoor / outdoor use Operation temperature -25°C - +45°C Certificates CE, RoHS

A reliable <u>LED floodlight</u> for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - <u>let's bring your vision to life!</u>









LED floodlight PROLUMEN Recon black 230V 50W 7500lm 120° IP66 750


Product code 16329

Brand PROLUMEN Supply voltage 230V Power factor 0.90 Output 50W Maximum output 50W/1m Luminous flux 7500lumens Luminaire's efficiency Im79 150W Correlated colour temperature pure white 5000K Lens angle 120 Source of light PHILIPS LED Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 35000h Llmf tm21 L80B10 @25°C 50.000h Height 53.0mm Width 245.0mm Length 280.0mm In package 1pc In box 5pcs Casing colour black Casing material aluminum Polishing matt No. of switches 30000pcs Power supply TUREFUL Impact resistance IK08 Work environment indoor / outdoor use Operation temperature -25°C - +45°C Certificates CE, RoHS Warranty 5 years

A reliable <u>LED floodlight</u> for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - <u>let's bring your vision to life!</u>









LED floodlight PROLUMEN Slim black 230V 100W 16000lm 120X150° IP66 740

Product code 17700

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Output 100W Maximum output 100W/1m Luminous flux 16000lumens Luminaire's efficiency Im79 160W Correlated colour temperature pure white 4000K Lens angle 120X150 Source of light PHILIPS LED Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 50000h Llmf tm21 L90B10 @25°C 50.000h Height 105.0mm Width 275.0mm Length 370.0mm In package 1pc In box 4pcs Casing colour black Casing material aluminum Polishing matt Power supply **SOSEN** Impact resistance IK08 Work environment indoor / outdoor Operation temperature -40° - +50°C Certificates CE

A reliable LED floodlight for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - let's bring your vision to life!









LED floodlight PROLUMEN Slim black 230V 150W 25500lm 120X150° IP66 740


Product code 17718

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Output 150W Maximum output 150W/1m Luminous flux 25500lumens Luminaire's efficiency Im79 170W Correlated colour temperature pure white 4000K Lens angle 120X150 Source of light PHILIPS LED Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 50000h Llmf tm21 L90B10 @25°C 50.000h Height 105.0mm Width 275.0mm Length 370.0mm In package 1pc In box 3pcs Casing colour black Casing material aluminum Polishing matt Power supply **SOSEN** Impact resistance IK08 Work environment indoor / outdoor Operation temperature -40° - +50°C Certificates CE

A reliable LED floodlight for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - let's bring your vision to life!









Motion sensor Quick plug-in Micro-wave sensor, 5.8Ghz, Micro-wave + daylight sensor 230V

- daylight sensor 230V

Product code 14853

Supply voltage 230V Warranty 2 years

