

LED floodlight BLP-F24A50P black 230V 47W 7500lm 120° IP66 0-10V 730

Product code 18284 0-10V dimmable

Supply voltage 230V
Power factor 0.95
Dimmable 0-10V
Output 47W
Maximum output 47W/1m
Luminous flux 7500lumens
Luminaire's efficiency lm79 160W
Correlated colour temperature warm
white 3000K
Lens angle 120
Cri 70
Sdcm - macadam ellipses 3
Protection class IP66
Lifespan 50000h
Llmf tm21 L80B50 @25°C 50.000h
Height 142.0mm
Width 200.0mm
Length 265.0mm
Weight 2.3 kg
In package 1pc
Casing colour black
Casing material aluminium
Polishing matt
Power supply [SOSEN](#)
Impact resistance IK08
Work environment indoor / outdoor
use
Operation temperature -25°C - +45°C
Certificates CE, RoHS
Warranty 5 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

Floodlight Deko-Light Flood Flex II black 230V 12W IP65 3000K warm white

Product code 20993

Brand [Deko-Light](#)
 Supply voltage 230V
 Output 12W
 Correlated colour temperature warm white 3000K
 Protection class IP65
 Height 152.0mm
 Width 200.0mm
 Length 56.0mm
 Casing colour black
 Casing material aluminium
 Impact resistance IK08
 Work environment outdoor use
 Warranty 5 years



Floodlight Deko-Light Flood RF II gray 230V 10W 270lm 115° IP65 RGB + 3000K RGBW warm

Product code 20994

Brand [Deko-Light](#)
 Supply voltage 230V
 Output 10W
 Luminous flux 270lumens
 Luminaire's efficiency lm79 27W
 Correlated colour temperature RGBW warm RGB + 3000K
 Lens angle 115
 Protection class IP65
 Lifespan 25000h
 Height 179.0mm
 Width 133.0mm
 Length 57.0mm
 Casing colour gray
 Casing material plastic
 Impact resistance IK08
 Work environment outdoor use
 Operation temperature -20 kuni 50 °C
 Warranty 5 years



LED floodlight EMOS ASIMO black 230V 300W 33000lm 55x125° IP66 840

Product code 16609

Brand [EMOS](#)

Supply voltage 230V

Power factor 0.90

Output 300W

Maximum output 300W/1m

Luminous flux 33000lumens

Luminaire's efficiency lm79 110W

Correlated colour temperature pure white 4000K

Lens angle 55x125

Cri 80

Protection class IP66

Lifespan 50000h

Height 80.0mm

Width 363.0mm

Length 370.0mm

In package 1pc

Casing colour black

Casing material aluminum + glass

Impact resistance IK08

Work environment outdoor use

Operation temperature -30 ~ 50°C

Warranty 5 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight LED slim black 230V 10W 1050lm 90° IP65 845

Product code 22716

Supply voltage 230V
Output 10W
Maximum output 10W/1m
Luminous flux 1050lumens
Luminaire's efficiency lm79 105W
Correlated colour temperature pure white 4500K
Lens angle 90
Cri 80
Sdcm - macadam ellipses 5
En62471 1
Protection class IP65
Lifespan 100000h
Casing colour black
Casing material aluminium
Impact resistance IK07
Work environment outdoor use
Operation temperature -30...+50°C
Certificates CE, CB, ENEC, EAC, UKCA, EPD



LED floodlight LEDVANCE FL 50 P black 230V 27-41W 6000lm 100° IP66 840

Product code 19186

Brand LEDVANCE
Supply voltage 230V
Output 27-41W
Maximum output 41W/1m
Luminous flux 6000lumens
Correlated colour temperature pure white 4000K
Lens angle 100
Cri 80
Sdcm - macadam ellipses 5
En62471 1
Protection class IP66
Lifespan 100000h
Height 179.0mm
Width 43.0mm
Length 201.0mm
Weight 830 g
Casing colour black
Casing material aluminium
Impact resistance IK07
Work environment outdoor use
Operation temperature -30...+50°C
Certificates CE, CB, ENEC, EAC, UKCA, EPD



Floodlight Liralighting Piston 140 black 12V 16W 1419lm 60° IP67 RGB+4000K RGBW pure white

Product code 19107

Brand [Liralighting](#)
Supply voltage 12V
Output 16W
Maximum output 16W/1m
Luminous flux 1419lumens
Luminaire's efficiency lm79 89W
Correlated colour temperature RGBW
pure white RGB+4000K
Lens angle 60
Sdcm - macadam ellipses 3
Protection class IP67
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 60.0mm
Width 168.0mm
Length 185.0mm
In package 1pc
Casing colour black
Casing material aluminium + plastic
Polishing matt
Impact resistance IK10
Work environment outdoor use
Operation temperature -40 ~ 45°C
Certificates CE
Warranty 5 years



Floodlight Liralighting Piston 140 black 17W 2191lm 10° IP67 3000K warm white

Product code 22744

Brand [Liralighting](#)

Output 17W

Maximum output 17W/1m

Luminous flux 2191lumens

Luminaire's efficiency lm79 129W

Correlated colour temperature warm
white 3000K

Lens angle 10

Sdcm - macadam ellipses 3

Protection class IP67

Lifespan 100000h

Llmf tm21 L80B10 @25°C 100.000h

Height 200.0mm

Width 380.0mm

Length 300.0mm

In package 1pc

Casing colour black

Casing material aluminium + plastic

Polishing matt

Impact resistance IK10

Work environment outdoor use

Operation temperature -40 ~ 45°C

Certificates CE

Warranty 5 years



Floodlight Liralighting Piston 140 gray 12V 16W 1419lm 60° IP67 RGB + 3000K RGBW warm

Product code 23292

Brand [Liralighting](#)
Supply voltage 12V
Output 16W
Maximum output 16W/1m
Luminous flux 1419lumens
Luminaire's efficiency lm79 89W
Correlated colour temperature RGBW
warm RGB + 3000K
Lens angle 60
Sdcm - macadam ellipses 3
Protection class IP67
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 60.0mm
Width 168.0mm
Length 185.0mm
In package 1pc
Casing colour gray
Casing material aluminium + plastic
Polishing matt
Impact resistance IK10
Work environment outdoor use
Operation temperature -40 ~ 45°C
Certificates CE
Warranty 5 years



Floodlight Liralighting Piston 200 black 230V 25W 3012lm 10° IP65 DALI 830

Product code 22860 DALI dimmable

Brand [Liralighting](#)

Supply voltage 230V

Dimmable DALI

Output 25W

Maximum output 25W/1m

Luminous flux 3012lumens

Luminaire's efficiency lm79 120W

Correlated colour temperature warm
white 3000K

Lens angle 10°

Cri 80

Sdcm - macadam ellipses 3

Protection class IP65

Lifespan 100000h

Llmf tm21 L80B10 @25°C 100.000h

Height 233.0mm

Diameter 200.0mm

Weight 4.9 kg

In package 1pc

Casing colour black

Casing material aluminium

Polishing matt

Impact resistance IK10

Work environment outdoor use

Operation temperature -40 ~ 45°C

Certificates CE

Warranty 5 years



Floodlight Liralighting Piston 200 black 230V 36W 3192lm 45° IP67 DMX RGB+4000K RGBW pure white

Product code 20155 DMX dimmable

Brand [Liralighting](#)
Supply voltage 230V
Dimmable DMX
Output 36W
Maximum output 36W/1m
Luminous flux 3192lumens
Luminaire's efficiency lm79 89W
Correlated colour temperature RGBW
pure white RGB+4000K
Lens angle 45
Sdcm - macadam ellipses 3
Protection class IP67
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 60.0mm
Width 228.0mm
Length 233.0mm
Weight 3.7 kg
In package 1pc
Casing colour black
Casing material aluminium + plastic
Polishing matt
Impact resistance IK10
Work environment outdoor use
Operation temperature -40 ~ 45°C
Certificates CE
Warranty 5 years



Floodlight Liralighting Piston 200 gray 36W 2232lm 40° IP67 RGB+4000K RGBW pure white

Product code 19114

Brand [Liralighting](#)

Output 36W

Maximum output 36W/1m

Luminous flux 2232lumens

Luminaire's efficiency lm79 62W

Correlated colour temperature RGBW

pure white RGB+4000K

Lens angle 40

Sdcm - macadam ellipses 3

Protection class IP67

Lifespan 100000h

Llmf tm21 L80B10 @25°C 100.000h

Height 60.0mm

Width 228.0mm

Length 233.0mm

In package 1pc

Casing colour gray

Casing material aluminium + plastic

Polishing matt

Impact resistance IK10

Work environment outdoor use

Operation temperature -40 ~ 45°C

Certificates CE

Warranty 5 years



Floodlight Liralighting Piston 200 gray 66W 8008lm IP67 4000K pure white

Product code 19112

Brand [Liralighting](#)

Output 66W

Maximum output 66W/1m

Luminous flux 8008lumens

Luminaire's efficiency lm79 121W

Correlated colour temperature pure
white 4000K

Sdcm - macadam ellipses 3

Protection class IP67

Lifespan 100000h

Llmf tm21 L80B10 @25°C 100.000h

Height 60.0mm

Width 228.0mm

Length 233.0mm

In package 1pc

Casing colour gray

Casing material aluminium + plastic

Polishing matt

Impact resistance IK10

Work environment outdoor use

Operation temperature -40 ~ 45°C

Certificates CE

Warranty 5 years



Floodlight Liralighting Piston 200 LV gray 44W 6025lm IP67 3000K warm white

Product code 19110

Brand [Liralighting](#)

Output 44W

Maximum output 44W/1m

Luminous flux 6025lumens

Luminaire's efficiency lm79 137W

Correlated colour temperature warm
white 3000K

Sdcm - macadam ellipses 3

Protection class IP67

Lifespan 100000h

Llmf tm21 L80B10 @25°C 100.000h

Height 60.0mm

Width 228.0mm

Length 233.0mm

In package 1pc

Casing colour gray

Casing material aluminium + plastic

Polishing matt

Impact resistance IK10

Work environment outdoor use

Operation temperature -40 ~ 45°C

Certificates CE

Warranty 5 years



Floodlight Liralighting Piston 200 LV gray 66W 7528lm IP67 3000K warm white

Product code 19109

Brand [Liralighting](#)

Output 66W

Maximum output 66W/1m

Luminous flux 7528lumens

Luminaire's efficiency lm79 114W

Correlated colour temperature warm
white 3000K

Sdcm - macadam ellipses 3

Protection class IP67

Lifespan 100000h

Lmf tm21 L80B10 @25°C 100.000h

Height 60.0mm

Width 228.0mm

Length 233.0mm

In package 1pc

Casing colour gray

Casing material aluminium + plastic

Polishing matt

Impact resistance IK10

Work environment outdoor use

Operation temperature -40 ~ 45°C

Certificates CE

Warranty 5 years



LED floodlight PHILIPS BVP154 motion sensor 10W 1000lm IP65 3000K warm white

Product code 19106

Brand [PHILIPS](#)

Output 10W

Maximum output 10W/1m

Luminous flux 1000lumens

Luminaire's efficiency lm79 100W

Correlated colour temperature warm
white 3000K

Protection class IP65

Height 35.0mm

Width 150.0mm

Length 160.0mm

Impact resistance IK07

Work environment indoor / outdoor
use



LED floodlight PHILIPS BVP164 motion sensor 20W 2200lm IP65 3000K warm white

Product code 19103

Brand [PHILIPS](#)

Output 20W

Maximum output 20W/1m

Luminous flux 2200lumens

Luminaire's efficiency lm79 110W

Correlated colour temperature warm white 3000K

Protection class IP65

Height 52.0mm

Width 97.0mm

Length 172.0mm

Impact resistance IK07

Work environment indoor / outdoor use



LED floodlight PHILIPS BVP167 30W 3600lm IP65 3000K, 4000K, 6500K 3CCT

Product code 19102

Brand [PHILIPS](#)

Output 30W

Maximum output 30W/1m

Luminous flux 3600lumens

Luminaire's efficiency lm79 120W

Correlated colour temperature 3CCT

3000K, 4000K, 6500K

Protection class IP65

Height 29.0mm

Width 133.0mm

Length 182.0mm

Work environment indoor / outdoor use



LED floodlight Prolumen AKITA gray 230V 600W 76330lm 50° IP66 0-10V 750

Product code 17776 0-10V dimmable

Brand [Prolumen](#)

Supply voltage 230V

Power factor 0.95

Dimmable 0-10V

Output 600W

Maximum output 600W/1m

Luminous flux 76330lumens

Luminaire's efficiency lm79 127W

Correlated colour temperature pure
white 5700K

Lens angle 50

Source of light OSRAM LED

Cri 70

Protection class IP66

Lifespan 50000h

Height 311.0mm

Width 308.0mm

Length 686.0mm

Weight 13 kg

Casing colour gray

Casing material aluminium

Power supply [INVENTRONICS](#)

Impact resistance IK10

Work environment outdoor use

Operation temperature -40° - +50°C

Certificates ENEC, CE, CB

Warranty 7 years



LED floodlight Prolumen AKITA gray 230V 600W 89307lm 50° IP66 0-10V 750

Product code 17775 0-10V dimmable

Brand [Prolumen](#)

Supply voltage 230V

Power factor 0.95

Dimmable 0-10V

Output 600W

Maximum output 600W/1m

Luminous flux 89307lumens

Luminaire's efficiency lm79 149W

Correlated colour temperature pure
white 5700K

Lens angle 50

Source of light [LUMILEDS](#)

Cri 70

Protection class IP66

Lifespan 50000h

Height 311.0mm

Width 308.0mm

Length 686.0mm

Weight 13 kg

Casing colour gray

Casing material aluminium

Power supply [INVENTRONICS](#)

Impact resistance IK10

Work environment outdoor use

Operation temperature -40° - +50°C

Certificates ENEC, CE, CB

Warranty 7 years



Floodlight Prolumen FLV black 230V 70W 8400lm 120° IP65 830

Product code 16208

Brand [Prolumen](#)

Supply voltage 230V

Output 70W

Maximum output 70W/1m

Luminous flux 8400lumens

Luminaire's efficiency lm79 120W

Correlated colour temperature warm white 3000K

Lens angle 120

Source of light [CREE LED](#)

Cri 80

Protection class IP65

Lifespan 50000h

Casing colour black

Casing material aluminum + glass

Impact resistance IK08

Work environment outdoor use

Warranty 5 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP65, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 100W 15000lm 120x150° IP66 No dim 750

Product code 18979 No dim dimmable

Brand [Prolumen](#)
Dimmable No dim
Output 100W
Maximum output 100W/1m
Luminous flux 15000lumens
Luminaire's efficiency lm79 150W
Correlated colour temperature pure white 5000K
Lens angle 120x150
Cri 70
Protection class IP66
Power supply [MEAN WELL](#)
Warranty 5 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 100W 16000lm 120x150° IP66 No dim 750

Product code 18990 No dim dimmable

Brand [Prolumen](#)
Dimmable No dim
Output 100W
Maximum output 100W/1m
Luminous flux 16000lumens
Luminaire's efficiency lm79 160W
Correlated colour temperature pure white 5000K
Lens angle 120x150
Cri 70
Protection class IP66
Power supply [SOSEN](#)
Warranty 5 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 150W 22500lm 120x150° No dim 740

**Product code 18975 No dim
dimmable**

Brand [Prolumen](#)
Dimmable No dim
Output 150W
Maximum output 150W/1m
Luminous flux 22500lumens
Luminaire's efficiency lm79 150W
Correlated colour temperature pure white 4000K
Lens angle 120x150
Cri 70
Power supply [MEAN WELL](#)
Warranty 5 years
Cable 1m



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 150W 22500lm 120x150° No dim 750

**Product code 18980 No dim
dimmable**

Brand [Prolumen](#)
Dimmable No dim
Output 150W
Maximum output 150W/1m
Luminous flux 22500lumens
Luminaire's efficiency lm79 150W
Correlated colour temperature pure white 5000K
Lens angle 120x150
Cri 70
Power supply OSRAM
Warranty 5 years
Cable 1m



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 150W 22500lm 120x150° No dim 750

**Product code 18981 No dim
dimmable**

Brand [Prolumen](#)
Dimmable No dim
Output 150W
Maximum output 150W/1m
Luminous flux 22500lumens
Luminaire's efficiency lm79 150W
Correlated colour temperature pure white 5000K
Lens angle 120x150
Cri 70
Power supply [MEAN WELL](#)
Warranty 5 years
Cable 1m



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 150W 25500lm 100x60° No dim 750

**Product code 18995 No dim
dimmable**

Brand [Prolumen](#)
Dimmable No dim
Output 150W
Maximum output 150W/1m
Luminous flux 25500lumens
Luminaire's efficiency lm79 170W
Correlated colour temperature pure white 5000K
Lens angle 100x60
Cri 70
Power supply [SOSEN](#)
Warranty 5 years
Cable 1m



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 150W 25500lm 120x150° No dim 750

**Product code 18991 No dim
dimmable**

Brand [Prolumen](#)
Dimmable No dim
Output 150W
Maximum output 150W/1m
Luminous flux 25500lumens
Luminaire's efficiency lm79 170W
Correlated colour temperature pure white 5000K
Lens angle 120x150
Cri 70
Power supply [SOSEN](#)
Warranty 5 years
Cable 1m



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 200W 34000lm 100x60° IP66 No dim 750

**Product code 18996 No dim
dimmable**

Brand [Prolumen](#)
Dimmable No dim
Output 200W
Maximum output 200W/1m
Luminous flux 34000lumens
Luminaire's efficiency lm79 170W
Correlated colour temperature pure
white 5000K
Lens angle 100x60
Cri 70
Protection class IP66
Power supply [SOSEN](#)
Warranty 5 years



A reliable [LED floodlight](#) for
illuminating areas and parking lots.
The floodlight's protection class is
IP66 and IK08, which means the light
fixture withstands outdoor conditions
excellently. Trust your lighting project
to the experienced team of LED House
- [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 200W 34000lm MLP30° No dim 740

**Product code 18976 No dim
dimmable**

Brand [Prolumen](#)
Dimmable No dim
Output 200W
Maximum output 200W/1m
Luminous flux 34000lumens
Luminaire's efficiency lm79 170W
Correlated colour temperature pure
white 4000K
Lens angle MLP30
Cri 70
Power supply [MEAN WELL](#)
Warranty 5 years
Cable 1m



A reliable [LED floodlight](#) for
illuminating areas and parking lots.
The floodlight's protection class is
IP66 and IK08, which means the light
fixture withstands outdoor conditions
excellently. Trust your lighting project
to the experienced team of LED House
- [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 200W 34000lm P45° No dim 750

Product code 18992 No dim dimmable

Brand [Prolumen](#)
Dimmable No dim
Output 200W
Maximum output 200W/1m
Luminous flux 34000lumens
Luminaire's efficiency lm79 170W
Correlated colour temperature pure white 5000K
Lens angle P45
Cri 70
Power supply [SOSEN](#)
Warranty 5 years
Cable 1m



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 230V 100W 15000lm 120x150° No dim 740

**Product code 18974 No dim
dimmable**

Brand [Prolumen](#)
Supply voltage 230V
Power factor 0.90
Dimmable No dim
Output 100W
Maximum output 100W/1m
Luminous flux 15000lumens
Luminaire's efficiency lm79 150W
Correlated colour temperature pure
white 4000K
Lens angle 120x150
Cri 70
Sdcm - macadam ellipses 6
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 57.0mm
Width 254.0mm
Length 288.0mm
In box 6pcs
Power supply [MEAN WELL](#)
Warranty 5 years



A reliable [LED floodlight](#) for
illuminating areas and parking lots.
The floodlight's protection class is
IP66 and IK08, which means the light
fixture withstands outdoor conditions
excellently. Trust your lighting project
to the experienced team of LED House
- [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 230V 200W 34000lm 45x100° No dim 740

**Product code 18987 No dim
dimmable**

Brand [Prolumen](#)
Supply voltage 230V
Power factor 0.90
Dimmable No dim
Output 200W
Maximum output 200W/1m
Luminous flux 34000lumens
Luminaire's efficiency lm79 170W
Correlated colour temperature pure white 4000K
Lens angle 45x100
Cri 70
Sdcm - macadam ellipses 6
Lifespan 50000h
Lmf tm21 L80B10 @25°C 50.000h
Height 57.0mm
Width 333.0mm
Length 403.0mm
In box 6pcs
Power supply [SOSEN](#)
Warranty 5 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 230V 200W 34000lm 45° No dim 740

**Product code 21862 No dim
dimmable**

Brand [Prolumen](#)
Supply voltage 230V
Power factor 0.90
Dimmable No dim
Output 200W
Maximum output 200W/1m
Luminous flux 34000lumens
Luminaire's efficiency lm79 170W
Correlated colour temperature pure
white 4000K
Lens angle 45
Cri 70
Sdcm - macadam ellipses 6
Lifespan 50000h
Lmf tm21 L80B10 @25°C 50.000h
Height 57.0mm
Width 333.0mm
Length 403.0mm
In box 6pcs
Power supply [SOSEN](#)
Warranty 5 years



A reliable [LED floodlight](#) for
illuminating areas and parking lots.
The floodlight's protection class is
IP66 and IK08, which means the light
fixture withstands outdoor conditions
excellently. Trust your lighting project
to the experienced team of LED House
- [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 230V 400W 68000lm 38x70° No dim 740

**Product code 18989 No dim
dimmable**

Brand [Prolumen](#)
Supply voltage 230V
Power factor 0.90
Dimmable No dim
Output 400W
Maximum output 400W/1m
Luminous flux 68000lumens
Luminaire's efficiency lm79 170W
Correlated colour temperature pure white 4000K
Lens angle 38x70
Cri 70
Sdcm - macadam ellipses 6
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 500.0mm
Width 370.0mm
Length 80.0mm
No. of switches 30000pcs
Power supply [SOSEN](#)
Warranty 5 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 240W 40800lm 25° No dim 750

Product code 18997 No dim dimmable

Brand [Prolumen](#)
 Dimmable No dim
 Output 240W
 Maximum output 240W/1m
 Luminous flux 40800lumens
 Luminaire's efficiency lm79 170W
 Correlated colour temperature pure white 5000K
 Lens angle 25
 Cri 70
 Power supply [SOSEN](#)
 Warranty 5 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 240W 40800lm MLP30° No dim 740

Product code 18977 No dim dimmable

Brand [Prolumen](#)
 Dimmable No dim
 Output 240W
 Maximum output 240W/1m
 Luminous flux 40800lumens
 Luminaire's efficiency lm79 170W
 Correlated colour temperature pure white 4000K
 Lens angle MLP30
 Cri 70
 Power supply [MEAN WELL](#)
 Warranty 5 years
 Cable 1m



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 240W 40800lm MLP30° No dim 750

**Product code 18984 No dim
dimmable**

Brand [Prolumen](#)
Dimmable No dim
Output 240W
Maximum output 240W/1m
Luminous flux 40800lumens
Luminaire's efficiency lm79 170W
Correlated colour temperature pure
white 5000K
Lens angle MLP30
Cri 70
Power supply [MEAN WELL](#)
Warranty 5 years
Cable 1m



A reliable [LED floodlight](#) for
illuminating areas and parking lots.
The floodlight's protection class is
IP66 and IK08, which means the light
fixture withstands outdoor conditions
excellently. Trust your lighting project
to the experienced team of LED House
- [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 240W 40800lm P45° No dim 740

Product code 18988 No dim dimmable

Brand [Prolumen](#)
Dimmable No dim
Output 240W
Maximum output 240W/1m
Luminous flux 40800lumens
Luminaire's efficiency lm79 170W
Correlated colour temperature pure white 4000K
Lens angle P45
Cri 70
Power supply [SOSEN](#)
Warranty 5 years
Cable 1m



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 240W 40800lm P45° No dim 750

Product code 18993 No dim dimmable

Brand [Prolumen](#)
Dimmable No dim
Output 240W
Maximum output 240W/1m
Luminous flux 40800lumens
Luminaire's efficiency lm79 170W
Correlated colour temperature pure white 5000K
Lens angle P45
Cri 70
Power supply [SOSEN](#)
Warranty 5 years
Cable 1m



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 400W 68000lm 25° No dim 750

Product code 18998 No dim dimmable

Brand [Prolumen](#)
Dimmable No dim
Output 400W
Maximum output 400W/1m
Luminous flux 68000lumens
Luminaire's efficiency lm79 170W
Correlated colour temperature pure white 5000K
Lens angle 25
Cri 70
Power supply [SOSEN](#)
Warranty 5 years
Cable 1m



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 400W 68000lm MLP30° No dim 750

**Product code 18985 No dim
dimmable**

Brand [Prolumen](#)
Dimmable No dim
Output 400W
Maximum output 400W/1m
Luminous flux 68000lumens
Luminaire's efficiency lm79 170W
Correlated colour temperature pure
white 5000K
Lens angle MLP30
Cri 70
Power supply [MEAN WELL](#)
Warranty 5 years
Cable 1m



A reliable [LED floodlight](#) for
illuminating areas and parking lots.
The floodlight's protection class is
IP66 and IK08, which means the light
fixture withstands outdoor conditions
excellently. Trust your lighting project
to the experienced team of LED House
- [let's bring your vision to life!](#)

LED floodlight Prolumen Light Slim G3 400W 68000lm P45° No dim 750

Product code 18994 No dim dimmable

Brand [Prolumen](#)
Dimmable No dim
Output 400W
Maximum output 400W/1m
Luminous flux 68000lumens
Luminaire's efficiency lm79 170W
Correlated colour temperature pure white 5000K
Lens angle P45
Cri 70
Power supply [SOSEN](#)
Warranty 5 years
Cable 1m



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Recon 30W 4500lm 120° No dim 750

**Product code 18971 No dim
dimmable**

Brand [Prolumen](#)

Dimmable No dim

Output 30W

Maximum output 30W/1m

Luminous flux 4500lumens

Luminaire's efficiency lm79 150W

Correlated colour temperature pure
white 5000K

Lens angle 120

Cri 70

Power supply [DONE](#)

Warranty 3 years

A reliable [LED floodlight](#) for
illuminating areas and parking lots.
The floodlight's protection class is
IP66 and IK08, which means the light
fixture withstands outdoor conditions
excellently. Recon lights in the LED
House selection are available in
different power levels - we will find
the perfect outdoor light for any
environment! Trust your lighting
project to the experienced team of
LED House - [let's bring your vision to
life!](#)



LED floodlight Prolumen Recon 50W 7500lm 120° No dim 750

Product code 18972 No dim dimmable

Brand [Prolumen](#)

Dimmable No dim

Output 50W

Maximum output 50W/1m

Luminous flux 7500lumens

Luminaire's efficiency lm79 150W

Correlated colour temperature pure white 5000K

Lens angle 120

Cri 70

Power supply [DONE](#)

Warranty 3 years

A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)



LED floodlight Prolumen Recon black 230V 150W 22500lm 90° IP66 740

Product code 16422

Brand [Prolumen](#)
Supply voltage 230V
Power factor 0.90
Output 150W
Maximum output 150W/1m
Luminous flux 22500lumens
Luminaire's efficiency lm79 150W
Correlated colour temperature pure white 4000K
Lens angle 90
Source of light [PHILIPS LED](#)
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 35000h
Llmf tm21 L80B10 @25°C 50.000h
Height 63.0mm
Width 359.0mm
Length 400.0mm
In package 1pc
In box 4pcs
Casing colour black
Casing material aluminium
Polishing matt
No. of switches 30000pcs
Power supply [SOSEN](#)
Impact resistance IK08
Work environment indoor / outdoor use
Operation temperature -25°C - +45°C
Certificates CE, RoHS
Warranty 5 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Recon black 230V 200W 30000lm 90° IP66 740

Product code 16423

Brand [Prolumen](#)
 Supply voltage 230V
 Power factor 0.90
 Output 200W
 Maximum output 200W/1m
 Luminous flux 30000lumens
 Luminaire's efficiency lm79 150W
 Correlated colour temperature pure white 4000K
 Lens angle 90
 Source of light [PHILIPS LED](#)
 Cri 70
 Sdcm - macadam ellipses 6
 Protection class IP66
 Lifespan 35000h
 Llmf tm21 L80B10 @25°C 50.000h
 Height 63.0mm
 Width 389.0mm
 Length 430.0mm
 In package 1pc
 In box 3pcs
 Casing colour black
 Casing material aluminium
 Polishing matt
 No. of switches 30000pcs
 Power supply [SOSEN](#)
 Impact resistance IK08
 Work environment indoor / outdoor use
 Operation temperature -25°C - +45°C
 Certificates CE, RoHS
 Warranty 5 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Recon black 230V 30W 4000lm 120° IP66 727

Product code 18004

Brand [Prolumen](#)
 Supply voltage 230V
 Power factor 0.90
 Output 30W
 Maximum output 30W/1m
 Luminous flux 4000lumens
 Luminaire's efficiency lm79 133W
 Correlated colour temperature warm white 2700K
 Lens angle 120
 Source of light [PHILIPS LED](#)
 Cri 70
 Sdcm - macadam ellipses 6
 Protection class IP66
 Lifespan 35000h
 Llmf tm21 L80B10 @25°C 50.000h
 Height 53.0mm
 Width 204.0mm
 Length 232.0mm
 In package 1pc
 In box 5pcs
 Casing colour black
 Casing material aluminium
 Polishing matt
 No. of switches 30000pcs
 Power supply [TUREFUL](#)
 Impact resistance IK08
 Work environment indoor / outdoor use
 Operation temperature -25°C - +45°C
 Certificates CE, RoHS
 Warranty 5 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Recon black 230V 30W 4500lm 120° IP66 740

Product code 17225

Brand [Prolumen](#)
 Supply voltage 230V
 Power factor 0.90
 Output 30W
 Maximum output 30W/1m
 Luminous flux 4500lumens
 Luminaire's efficiency lm79 150W
 Correlated colour temperature pure white 4000K
 Lens angle 120
 Source of light [PHILIPS LED](#)
 Cri 70
 Sdcm - macadam ellipses 6
 Protection class IP66
 Lifespan 35000h
 Llmf tm21 L80B10 @25°C 50.000h
 Height 53.0mm
 Width 204.0mm
 Length 232.0mm
 In package 1pc
 In box 5pcs
 Casing colour black
 Casing material aluminium
 Polishing matt
 No. of switches 30000pcs
 Power supply [TUREFUL](#)
 Impact resistance IK08
 Work environment indoor / outdoor use
 Operation temperature -25°C - +45°C
 Certificates CE, RoHS
 Warranty 5 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Recon black 230V 30W 4500lm 120° IP66 750

Product code 16328

Brand [Prolumen](#)
 Supply voltage 230V
 Power factor 0.90
 Output 30W
 Maximum output 30W/1m
 Luminous flux 4500lumens
 Luminaire's efficiency lm79 150W
 Correlated colour temperature pure white 5000K
 Lens angle 120
 Source of light [PHILIPS LED](#)
 Cri 70
 Sdcm - macadam ellipses 6
 Protection class IP66
 Lifespan 35000h
 Llmf tm21 L80B10 @25°C 50.000h
 Height 53.0mm
 Width 204.0mm
 Length 232.0mm
 In package 1pc
 In box 5pcs
 Casing colour black
 Casing material aluminium
 Polishing matt
 No. of switches 30000pcs
 Power supply [TUREFUL](#)
 Impact resistance IK08
 Work environment indoor / outdoor use
 Operation temperature -25°C - +45°C
 Certificates CE, RoHS
 Warranty 3 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Recon black 230V 50W 6500lm 120° IP66 727

Product code 18005

Brand [Prolumen](#)
 Supply voltage 230V
 Power factor 0.90
 Output 50W
 Maximum output 50W/1m
 Luminous flux 6500lumens
 Luminaire's efficiency lm79 130W
 Correlated colour temperature warm white 2700K
 Lens angle 120
 Source of light [PHILIPS LED](#)
 Cri 70
 Sdcm - macadam ellipses 6
 Protection class IP66
 Lifespan 35000h
 Llmf tm21 L80B10 @25°C 50.000h
 Height 53.0mm
 Width 245.0mm
 Length 280.0mm
 In package 1pc
 In box 5pcs
 Casing colour black
 Casing material aluminium
 Polishing matt
 No. of switches 30000pcs
 Power supply [DONE](#)
 Impact resistance IK08
 Work environment indoor / outdoor use
 Operation temperature -25°C - +45°C
 Certificates CE, RoHS
 Warranty 5 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Recon black 230V 50W 7500lm 120° IP66 740

Product code 17585

Brand [Prolumen](#)
 Supply voltage 230V
 Power factor 0.90
 Output 50W
 Maximum output 50W/1m
 Luminous flux 7500lumens
 Luminaire's efficiency lm79 150W
 Correlated colour temperature pure white 4000K
 Lens angle 120
 Source of light [PHILIPS LED](#)
 Cri 70
 Sdcm - macadam ellipses 6
 Protection class IP66
 Lifespan 35000h
 Llmf tm21 L80B10 @25°C 50.000h
 Height 53.0mm
 Width 245.0mm
 Length 280.0mm
 In package 1pc
 In box 5pcs
 Casing colour black
 Casing material aluminium
 Polishing matt
 No. of switches 30000pcs
 Power supply [DONE](#)
 Impact resistance IK08
 Work environment indoor / outdoor use
 Operation temperature -25°C - +45°C
 Certificates CE, RoHS
 Warranty 5 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Recon black 230V 50W 7500lm 120° IP66 750

Product code 16329

Brand [Prolumen](#)
 Supply voltage 230V
 Power factor 0.90
 Output 50W
 Maximum output 50W/1m
 Luminous flux 7500lumens
 Luminaire's efficiency lm79 150W
 Correlated colour temperature pure white 5000K
 Lens angle 120
 Source of light [PHILIPS LED](#)
 Cri 70
 Sdcm - macadam ellipses 6
 Protection class IP66
 Lifespan 35000h
 Llmf tm21 L80B10 @25°C 50.000h
 Height 53.0mm
 Width 245.0mm
 Length 280.0mm
 In package 1pc
 In box 5pcs
 Casing colour black
 Casing material aluminium
 Polishing matt
 No. of switches 30000pcs
 Power supply [TUREFUL](#)
 Impact resistance IK08
 Work environment indoor / outdoor use
 Operation temperature -25°C - +45°C
 Certificates CE, RoHS
 Warranty 5 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Recon lights in the LED House selection are available in different power levels - we will find the perfect outdoor light for any environment! Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Slim black 230V 100W 16000lm 120X150° IP66 740

Product code 17700

Brand [Prolumen](#)
Supply voltage 230V
Power factor 0.95
Output 100W
Maximum output 100W/1m
Luminous flux 16000lumens
Luminaire's efficiency lm79 160W
Correlated colour temperature pure white 4000K
Lens angle 120X150
Source of light [PHILIPS LED](#)
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 50000h
Llmf tm21 L90B10 @25°C 50.000h
Height 105.0mm
Width 275.0mm
Length 370.0mm
In package 1pc
In box 4pcs
Casing colour black
Casing material aluminium
Polishing matt
Power supply [SOSEN](#)
Impact resistance IK08
Work environment indoor / outdoor use
Operation temperature -40° - +50°C
Certificates CE
Warranty 5 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

LED floodlight Prolumen Slim black 230V 150W 25500lm 120X150° IP66 740

Product code 17718

Brand [Prolumen](#)
Supply voltage 230V
Power factor 0.95
Output 150W
Maximum output 150W/1m
Luminous flux 25500lumens
Luminaire's efficiency lm79 170W
Correlated colour temperature pure white 4000K
Lens angle 120X150
Source of light [PHILIPS LED](#)
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 50000h
Llmf tm21 L90B10 @25°C 50.000h
Height 105.0mm
Width 275.0mm
Length 370.0mm
In package 1pc
In box 3pcs
Casing colour black
Casing material aluminium
Polishing matt
Power supply [SOSEN](#)
Impact resistance IK08
Work environment indoor / outdoor use
Operation temperature -40° - +50°C
Certificates CE
Warranty 5 years



A reliable [LED floodlight](#) for illuminating areas and parking lots. The floodlight's protection class is IP66 and IK08, which means the light fixture withstands outdoor conditions excellently. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)

Motion sensor Quick plug-in Micro-wave sensor, 5.8Ghz, Micro-wave + daylight sensor 230V



Product code 14853

Supply voltage 230V
Warranty 2 years

Motion sensor Quick plug-in PIR sensor, infrared motion sensor + daylight sensor



Product code 18973

Warranty 2 years

