Ceiling lamp DB157 UGR<19 1200 DALI white 230V 25-40W 4400lm CRI95 80° IP20 DALI 3000K-4000K 2CCT

Product code 22320 DALI dimmable

Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 25-40W
Maximum output 40W/1m
Rated current 1250mA
Luminous flux 4400lumens
Correlated colour temperature 2CCT 3000K-4000K
Lens angle 80
Cri 95
Ugr 19
Sdcm - macadam ellipses 3
Protection class IP20
Lifespan 50000h
Height 59.0mm
Width 120.0mm
Length 1200.0mm
In package 1pc
In box 6pcs
Casing colour white
Casing material aluminium
Power supply BOKE
Impact resistance IK08
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years



Ceiling lamp DB157 UGR<19 1200 white 230V 30W 3500lm 80° IP20 940

Product code 18172

Supply voltage 230V
Power factor 0.90
Output 30W
Maximum output 30W/1m
Rated current 1250mA
Luminous flux 3500lumens
Luminaire’s efficiency 117W
Correlated colour temperature pure white 4000K
Lens angle 80
Cri 95
Ugr 19
Sdcm - macadam ellipses 3
Protection class IP20
Lifespan 50000h
Height 59.0mm
Width 120.0mm
Length 1200.0mm
In package 1pc
In box 6pcs
Casing colour white
Casing material aluminium
Impact resistance IK08
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years



© LED House OÜ, (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee

LED luminaire ECO Bianca BFLH-12-36C1 white 230V 21-36W 5760lm CRI80 120° IP44 3000K, 3500K, 4000K 3CCT

Product code 19396

Brand ECO
Supply voltage 230V
Power factor 0.90
Output 21-36W
Maximum output 36W/1m
Luminous flux 5760lumens
Correlated colour temperature 3CCT
3000K, 3500K, 4000K
Lens angle 120
Cri 80
Sdcm - macadam ellipses 5
Protection class IP44
Lifespan 50000h
Height 61.0mm
Width 160.0mm
Length 1160.0mm
In package 1pc
In box 4pcs
Casing colour white
Casing material polycarbonate
Polishing matt
Power supply PHILIPS
Impact resistance IK08
Work environment indoor use
Operation temperature -20 - +45°C
Certificates CE
Warranty 3 years



LED luminaire ECO Bianca BFLH-15-42C1 white 230V 25-42W 6720lm CRI80 120° IP44 3000K, 3500K, 4000K 3CCT

Product code 19397

Brand ECO
Supply voltage 230V
Power factor 0.90
Output 25-42W
Maximum output 42W/1m
Luminous flux 6720lumens
Correlated colour temperature 3CCT
3000K, 3500K, 4000K
Lens angle 120
Cri 80
Sdcm - macadam ellipses 5
Protection class IP44
Lifespan 50000h
Height 61.0mm
Width 160.0mm
Length 1440.0mm
In package 1pc
In box 4pcs
Casing colour white
Casing material polycarbonate
Polishing matt
Power supply PHILIPS
Impact resistance IK08
Work environment indoor use
Operation temperature -20 - +45°C
Certificates CE
Warranty 3 years



Ceiling lamp Koline 1200 black 230V 20W 2400lm 105° IP20 840

Product code 17275

Supply voltage 230V
Power factor 0.90
Output 20W
Maximum output 20W/1m
Luminous flux 2400lumens
Luminaire’s efficiency 120W
Correlated colour temperature pure white 4000K
Lens angle 105
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1.5 kg
In package 1pc
In box 9pcs
Casing colour black
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20 ~40°C
Certificates CE
Warranty 5 years



An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!

Ceiling lamp Koline 1200 white 230V 20W 2600lm 105° IP20 840

Product code 17276

Supply voltage 230V
Power factor 0.90
Output 20W
Maximum output 20W/1m
Luminous flux 2600lumens
Luminaire’s efficiency 130W
Correlated colour temperature pure white 4000K
Lens angle 105
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1.55 kg
In package 1pc
In box 9pcs
Casing colour white
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20° - +40°C
Certificates CE
Warranty 5 years



An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!

Ceiling lamp Koline 1200 white 230V 40W 5200lm 105° IP20 840

Product code 17274

Supply voltage 230V
Power factor 0.90
Output 40W
Maximum output 40W/1m
Luminous flux 5200lumens
Luminaire’s efficiency 130W
Correlated colour temperature pure white 4000K
Lens angle 105
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1.55 kg
In package 1pc
In box 9pcs
Casing colour white
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years



An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!

Ceiling lamp Koline GO 1200 black 230V 40W 4800lm CRI80 110° IP20 3000K, 4000K, 6000K 3CCT

Product code 23943

Supply voltage 230V
Power factor 0.90
Output 40W
Maximum output 40W/1m
Luminous flux 4800lumens
Luminaire’s efficiency 120W
Correlated colour temperature 3CCT
3000K, 4000K, 6000K
Lens angle 110
Cri 80
Protection class IP20
Lifespan 50000h
Height 50.0mm
Width 40.0mm
Length 120.0mm
In package 1pc
In box 18pcs
Casing colour black
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20 ~40°C
Certificates CE
Warranty 5 years





An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!

Ceiling lamp Koline K2 1200 black 230V 20-30-40W 4800lm CRI80 110° IP20 3000K, 4000K, 6500K 3CCT

Product code 23037

Supply voltage 230V
Power factor 0.90
Output 20-30-40W
Maximum output 40W/1m
Luminous flux 4800lumens
Correlated colour temperature 3CCT
3000K, 4000K, 6500K
Lens angle 110
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1.5 kg
In package 1pc
In box 9pcs
Casing colour black
No. of switches 30000pcs
Impact resistance IK04
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years



An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!

Ceiling lamp Koline K2 1200 black 230V 40W 4800lm CRI80 110° IP20 3000K, 4000K, 6500K 3CCT

Product code 18119

Supply voltage 230V
Power factor 0.90
Output 40W
Maximum output 40W/1m
Luminous flux 4800lumens
Luminaire’s efficiency 120W
Correlated colour temperature 3CCT
3000K, 4000K, 6500K
Lens angle 110
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1.5 kg
In package 1pc
In box 9pcs
Casing colour black
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years



An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!

Ceiling lamp Koline K2 1200 UGR<19 black 230V 20-30-40W 4600lm CRI80 60° IP20 3000K, 4000K, 6500K 3CCT

Product code 23723

Supply voltage 230V
Power factor 0.90
Output 20-30-40W
Maximum output 40W/1m
Luminous flux 4600lumens
Correlated colour temperature 3CCT
3000K, 4000K, 6500K
Lens angle 60
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1.5 kg
In package 1pc
In box 9pcs
Casing colour black
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years







An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!

Ceiling lamp Koline K2 1200 UGR<19 black 230V 30W 3300lm CRI80 60° IP20 3000K, 4000K, 6500K 3CCT

Product code 18122

Supply voltage 230V
Power factor 0.90
Output 30W
Maximum output 30W/1m
Luminous flux 3300lumens
Luminaire’s efficiency 110W
Correlated colour temperature 3CCT
3000K, 4000K, 6500K
Lens angle 60
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1.5 kg
In package 1pc
In box 9pcs
Casing colour black
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years







An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!

Ceiling lamp Koline K2 1200 UGR<19 white 230V 30W 3600lm CRI80 60° IP20 3000K, 4000K, 6500K 3CCT

Product code 18121

Supply voltage 230V
Power factor 0.90
Output 30W
Maximum output 30W/1m
Luminous flux 3600lumens
Luminaire’s efficiency 120W
Correlated colour temperature 3CCT
3000K, 4000K, 6500K
Lens angle 60
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1.55 kg
In package 1pc
In box 9pcs
Casing colour white
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years



An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!

Ceiling lamp Koline K2 1200 white 230V 20-30-40W 5200lm CRI80 90° IP20 3000K, 4000K, 6500K 3CCT

Product code 24018

Supply voltage 230V
Power factor 0.90
Output 20-30-40W
Maximum output 40W/1m
Luminous flux 5200lumens
Correlated colour temperature 3CCT
3000K, 4000K, 6500K
Lens angle 90
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1.55 kg
In package 1pc
In box 9pcs
Casing colour white
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years



An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!

© LED House OÜ, (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee

Ceiling lamp Koline K2 1200 white 230V 20W 2600lm CRI80 110° IP20 3000K, 4000K, 6500K 3CCT

Product code 18118

Supply voltage 230V
Power factor 0.90
Output 20W
Maximum output 20W/1m
Luminous flux 2600lumens
Luminaire’s efficiency 130W
Correlated colour temperature 3CCT
3000K, 4000K, 6500K
Lens angle 110
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1.55 kg
In package 1pc
In box 9pcs
Casing colour white
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20° - +40°C
Certificates CE
Warranty 5 years



An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!

Ceiling lamp Koline K2 1200 white 230V 40W 4800lm CRI80 110° IP20 3000K, 4000K, 6500K 3CCT

Product code 18120

Supply voltage 230V
Power factor 0.90
Output 40W
Maximum output 40W/1m
Luminous flux 4800lumens
Luminaire’s efficiency 120W
Correlated colour temperature 3CCT
3000K, 4000K, 6500K
Lens angle 110
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1.55 kg
In package 1pc
In box 9pcs
Casing colour white
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years



An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!

Ceiling lamp Koline K2 1200 white 230V 40W 5200lm CRI80 90° IP20 DALI 3000K, 4000K, 6500K 3CCT

Product code 24020 DALI dimmable

Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 40W
Maximum output 40W/1m
Luminous flux 5200lumens
Luminaire’s efficiency 130W
Correlated colour temperature 3CCT
3000K, 4000K, 6500K
Lens angle 90
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1.55 kg
In package 1pc
In box 9pcs
Casing colour white
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years




An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!

Ceiling lamp KOLINE K2 L – extension black 230V 8W 800lm CRI80 110° IP20 3000K, 4000K, 6500K 3CCT

Product code 19077

Supply voltage 230V
Power factor 0.90
Output 8W
Maximum output 8W/1m
Luminous flux 800lumens
Luminaire’s efficiency 100W
Correlated colour temperature 3CCT
3000K, 4000K, 6500K
Lens angle 110
Cri 80
Protection class IP20
Lifespan 50000h
In package 1pc
In box 5pcs
Casing colour black
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20 ~40°C
Certificates CE EMC LVD ROHS
Warranty 5 years




The LED KOLINE K2 connector allows you to link luminaires into various shapes, offering flexible and stylish lighting solutions for any space. Built-in LEDs and a frosted diffuser provide uniform and eye-friendly illumination. A durable aluminum housing and strong polycarbonate ensure long-lasting quality. The light color can be adjusted to warm, neutral, or cool tones as needed. A wide beam angle provides good coverage, and the energy-efficient light source keeps costs low. For safety, LED replacement is permitted only by qualified personnel.

Ceiling lamp KOLINE K2 T – extension black 230V 11W 1100lm CRI80 110° IP20 3000K, 4000K, 6500K 3CCT

Product code 19076

Supply voltage 230V
Power factor 0.90
Output 11W
Maximum output 11W/1m
Luminous flux 1100lumens
Luminaire’s efficiency 100W
Correlated colour temperature 3CCT
3000K, 4000K, 6500K
Lens angle 110
Cri 80
Protection class IP20
Lifespan 50000h
In package 1pc
In box 5pcs
Casing colour black
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20 ~40°C
Certificates CE EMC LVD ROHS
Warranty 5 years




The LED KOLINE K2 connector allows you to link luminaires into various shapes, offering flexible and stylish lighting solutions for any space. Built-in LEDs and a frosted diffuser provide uniform and eye-friendly illumination. A durable aluminum housing and strong polycarbonate ensure long-lasting quality. The light color can be adjusted to warm, neutral, or cool tones as needed. A wide beam angle provides good coverage, and the energy-efficient light source keeps costs low. For safety, LED replacement is permitted only by qualified personnel.

Ceiling lamp KOLINE K2 X – extension black 230V 15W 1500lm CRI80 110° IP20 3000K, 4000K, 6500K 3CCT

Product code 19078

Supply voltage 230V
Power factor 0.90
Output 15W
Maximum output 15W/1m
Rated current 70mA
Luminous flux 1500lumens
Luminaire’s efficiency 100W
Correlated colour temperature 3CCT
3000K, 4000K, 6500K
Lens angle 110
Cri 80
Protection class IP20
Lifespan 50000h
In package 1pc
In box 5pcs
Casing colour black
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20 ~40°C
Certificates CE EMC LVD ROHS
Warranty 5 years



The LED KOLINE K2 connector allows you to link luminaires into various shapes, offering flexible and stylish lighting solutions for any space. Built-in LEDs and a frosted diffuser provide uniform and eye-friendly illumination. A durable aluminum housing and strong polycarbonate ensure long-lasting quality. The light color can be adjusted to warm, neutral, or cool tones as needed. A wide beam angle provides good coverage, and the energy-efficient light source keeps costs low. For safety, LED replacement is permitted only by qualified personnel.

Linear light Linda 5073 1200 MicroPrism black 230V 26W 3250lm CRI80 100° IP20 DALI 3000K, 3500K, 4000K 3CCT

Product code 19149 DALI dimmable

Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 26W
Maximum output 26W/1m
Luminous flux 3250lumens
Luminaire’s efficiency 125W
Correlated colour temperature 3CCT
3000K, 3500K, 4000K
Lens angle 100
Cri 80
Ugr 18
Sdcm - macadam ellipses 6
En62471 1
Protection class IP20
Lifespan 50000h
Height 73.0mm
Width 50.0mm
Length 1200.0mm
In package 1pc
Casing colour black
Casing material aluminium
Power supply BOKE
Work environment indoor use
Certificates CE, RoHS
Warranty 3 years



Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors. Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space. Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Linear light Linda 5073 1200 MicroPrism white 230V 26W 3250lm CRI80 100° IP20 DALI 3000K, 3500K, 4000K 3CCT

Product code 19398 DALI dimmable



Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 26W
Maximum output 26W/1m
Luminous flux 3250lumens
Luminaire’s efficiency 125W
Correlated colour temperature 3CCT
3000K, 3500K, 4000K
Lens angle 100
Cri 80
Ugr 18
Sdcm - macadam ellipses 6
En62471 1
Protection class IP20
Lifespan 50000h
Height 73.0mm
Width 50.0mm
Length 1200.0mm
In package 1pc
Casing colour white
Casing material aluminium
Power supply BOKE
Work environment indoor use
Certificates CE, RoHS
Warranty 3 years

Linear light Linda 5073 1200 MicroPrism white 230V 26W 3380lm 100° IP20 840

Product code 22279



Supply voltage 230V
Power factor 0.90
Output 26W
Maximum output 26W/1m
Luminous flux 3380lumens
Luminaire’s efficiency 130W
Correlated colour temperature pure white 4000K
Lens angle 100
Cri 80
Ugr 18
Sdcm - macadam ellipses 6
En62471 1
Protection class IP20
Lifespan 50000h
Height 73.0mm
Width 50.0mm
Length 1200.0mm
In package 1pc
Casing colour white
Casing material aluminium
Power supply BOKE
Work environment indoor use
Certificates CE, RoHS
Warranty 3 years

Linear light Linda 5073 1500 MicroPrism black 230V 32W 4000lm CRI80 100° IP20 DALI 3000K, 3500K, 4000K 3CCT

Product code 19154 DALI dimmable

Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 32W
Maximum output 32W/1m
Luminous flux 4000lumens
Luminaire’s efficiency 125W
Correlated colour temperature 3CCT
3000K, 3500K, 4000K
Lens angle 100
Cri 80
Ugr 18
Sdcm - macadam ellipses 6
En62471 1
Protection class IP20
Lifespan 50000h
Height 73.0mm
Width 50.0mm
Length 1500.0mm
Weight 1.15 kg
In package 1pc
Casing colour black
Casing material aluminium
Power supply BOKE
Work environment indoor use
Certificates CE, RoHS
Warranty 3 years



Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors. Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space. Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

LED luminaire LSLG 1200 UGR white 230V 40W 4800lm 65° IP20 842

Product code 16308

Supply voltage 230V
Output 40W
Maximum output 40W/1m
Luminous flux 4800lumens
Luminaire’s efficiency 120W
Correlated colour temperature pure white 4200K
Lens angle 65
Source of light SANAN LED
Cri 80
Ugr 19
Protection class IP20
Lifespan 50000h
Llmf tm21 L70B50 @25°C 50.000h
Height 70.0mm
Width 50.0mm
Length 1200.0mm
Weight 1.85 kg
Package weight 2 kg
In package 1pc
In box 9pcs
Casing colour white
Casing material aluminium
Polishing matt
No. of switches 30000pcs
Power supply BOKE
Work environment indoor use
Certificates CE
Warranty 5 years




Linear workplace luminaire with low UGR value. This IP20-rated linear luminaire is an ideal choice for home or office environments, providing daylight illumination at a temperature of 4200K. The luminaire comes with a suspension kit. Illuminate your world with LED House professionals - check out our project portfolio here!

LED luminaire Prolumen Barrett 1200 recessed white 230V 36W 3100lm 75° IP20 DALI 940

Product code 17004 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 36W
Maximum output 36W/1m
Luminous flux 3100lumens
Luminaire’s efficiency 86W
Correlated colour temperature pure white 4000K
Lens angle 75
Cri 90
Ugr 22
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70B50 @25°C 50.000h
Height 76.0mm
Width 57.0mm
Length 1212.0mm
In box 6pcs
Casing colour white
Casing material aluminium
Polishing matt
Impact resistance IK06
Work environment indoor use
Certificates CE
Warranty 5 years








Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett 1200 black 230V 36W 3350lm 110° IP20 DALI 930

Product code 16970 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 36W
Maximum output 36W/1m
Luminous flux 3350lumens
Luminaire’s efficiency 93W
Correlated colour temperature warm white 3000K
Lens angle 110
Cri 90
Sdcm - macadam ellipses 3
Protection class IP20
Lifespan 50000h
Llmf tm21 L70B50 @25°C 50.000h
Height 76.0mm
Width 57.0mm
Length 1212.0mm
In box 6pcs
Casing colour black
Casing material aluminium
Polishing matt
Power supply BOKE
Impact resistance IK06
Work environment indoor use
Certificates CE
Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett 1200 black 230V 36W 3600lm 65° IP20 DALI 940

Product code 21926 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 36W
Maximum output 36W/1m
Luminous flux 3600lumens
Luminaire’s efficiency 100W
Correlated colour temperature pure white 4000K
Lens angle 65
Cri 90
Sdcm - macadam ellipses 3
Protection class IP20
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 76.0mm
Width 57.0mm
Length 1212.0mm
In box 6pcs
Casing colour black
Casing material aluminium
Polishing matt
Power supply BOKE
Impact resistance IK06
Work environment indoor use
Certificates CE
Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett 1200 UP/DOWN white 230V 36W 4100lm 110° IP20 DALI 940

Product code 16992 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 36W
Maximum output 36W/1m
Luminous flux 4100lumens
Luminaire’s efficiency 114W
Correlated colour temperature pure white 4000K
Lens angle 110
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70B50 @25°C 50.000h
Height 76.0mm
Width 57.0mm
Length 1212.0mm
In box 6pcs
Casing colour white
Casing material aluminium
Polishing matt
Impact resistance IK06
Work environment indoor use
Certificates CE
Warranty 5 years








Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett 1200 white 230V 36W 3100lm CRI90 110° IP20 DALI 3000K, 4000K, 5700K 3CCT

Product code 17022 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 36W
Maximum output 36W/1m
Luminous flux 3100lumens
Luminaire’s efficiency 86W
Correlated colour temperature 3CCT
3000K, 4000K, 5700K
Lens angle 110
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70B50 @25°C 50.000h
Height 76.0mm
Width 57.0mm
Length 1212.0mm
In box 6pcs
Casing colour white
Casing material aluminium
Polishing matt
Impact resistance IK06
Work environment indoor use
Certificates CE
Warranty 5 years








Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett 1500 black 230V 45W 4673lm CRI90 65° IP20 3000K, 4000K, 5700K 3CCT

Product code 16477

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 45W
Maximum output 45W/1m
Luminous flux 4673lumens
Luminaire’s efficiency 104W
Correlated colour temperature 3CCT
3000K, 4000K, 5700K
Lens angle 65
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 76.0mm
Width 57.0mm
Length 1512.0mm
In box 6pcs
Casing colour black
Casing material aluminium
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

© LED House OÜ, (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee

LED luminaire Prolumen Barrett 1500 UGR19 UP/DOWN white 230V 60W 6000lm 65° IP20 930

Product code 18070

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 60W
Maximum output 60W/1m
Luminous flux 6000lumens
Luminaire’s efficiency 100W
Correlated colour temperature warm white 3000K
Lens angle 65
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 76.0mm
Width 57.0mm
Length 1512.0mm
In box 6pcs
Casing colour white
Casing material aluminium
Power supply BOKE
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett 1500 UP/DOWN black 230V 60W 5300lm 65° IP20 DALI 930

Product code 17043 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 60W
Maximum output 60W/1m
Luminous flux 5300lumens
Luminaire’s efficiency 88W
Correlated colour temperature warm white 3000K
Lens angle 65
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 76.0mm
Width 57.0mm
Length 1512.0mm
In box 6pcs
Casing colour black
Casing material aluminium
Power supply BOKE
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett 1500 UP/DOWN black 230V 60W 6000lm 65° IP20 DALI 940

Product code 22220 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 60W
Maximum output 60W/1m
Luminous flux 6000lumens
Luminaire’s efficiency 100W
Correlated colour temperature pure white 4000K
Lens angle 65
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 76.0mm
Width 57.0mm
Length 1512.0mm
In box 6pcs
Casing colour black
Casing material aluminium
Power supply BOKE
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett 1500 UP/DOWN V black 230V 60W 5400lm 65° IP20 No dim 930

Product code 16511

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 60W
Maximum output 60W/1m
Luminous flux 5400lumens
Luminaire’s efficiency 90W
Correlated colour temperature warm white 3000K
Lens angle 65
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 76.0mm
Width 57.0mm
Length 1512.0mm
In box 6pcs
Casing colour black
Casing material aluminium
Power supply BOKE
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett 1500 white 230V 45W 4573lm CRI90 110° IP20 DALI 3000K, 4000K, 5700K 3CCT

Product code 17016 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 45W
Maximum output 45W/1m
Luminous flux 4573lumens
Luminaire’s efficiency 102W
Correlated colour temperature 3CCT
3000K, 4000K, 5700K
Lens angle 110
Cri 90
Ugr 19
Sdcm - macadam ellipses 3
Protection class IP20
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 76.0mm
Width 57.0mm
Length 1512.0mm
In box 6pcs
Casing colour white
Casing material aluminium
Power supply BOKE
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett 600 black 230V 17W 1500lm 75° IP20 930

Product code 16672

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 17W
Maximum output 17W/1m
Luminous flux 1500lumens
Luminaire’s efficiency 88W
Correlated colour temperature warm white 3000K
Lens angle 75
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 76.0mm
Width 57.0mm
Length 602.0mm
Weight 1.7 kg
Package weight 2.13 kg
In box 6pcs
Casing colour black
Casing material aluminium
Power supply OSRAM
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett 600 white 230V 17W 1500lm 75° IP20 DALI 930

Product code 16971 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 17W
Maximum output 17W/1m
Luminous flux 1500lumens
Luminaire’s efficiency 88W
Correlated colour temperature warm white 3000K
Lens angle 75
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 76.0mm
Width 57.0mm
Length 602.0mm
Weight 1.7 kg
Package weight 2.13 kg
In box 6pcs
Casing colour white
Casing material aluminium
Power supply BOKE
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett 600 white 230V 17W 1500lm 75° IP20 DALI 940

Product code 20464 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 17W
Maximum output 17W/1m
Luminous flux 1500lumens
Luminaire’s efficiency 88W
Correlated colour temperature pure white 4000K
Lens angle 75
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 76.0mm
Width 57.0mm
Length 602.0mm
Weight 1.7 kg
Package weight 2.13 kg
In box 6pcs
Casing colour white
Casing material aluminium
Power supply BOKE
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett 600 white 230V 17W 1500lm CRI90 110° IP20 DALI 3000K, 4000K, 5700K 3CCT

Product code 17017 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 17W
Maximum output 17W/1m
Luminous flux 1500lumens
Luminaire’s efficiency 88W
Correlated colour temperature 3CCT
3000K, 4000K, 5700K
Lens angle 110
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 76.0mm
Width 57.0mm
Length 602.0mm
In box 6pcs
Casing colour white
Casing material aluminium
Power supply BOKE
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years






Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett A 1200 white 230V 36W 3100lm 75° IP20 DALI 940

Product code 20463 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 36W
Maximum output 36W/1m
Luminous flux 3100lumens
Luminaire’s efficiency 86W
Correlated colour temperature pure white 4000K
Lens angle 75
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 76.0mm
Width 57.0mm
Length 1212.0mm
Weight 1.7 kg
Package weight 2.13 kg
In box 6pcs
Casing colour white
Casing material aluminium
Power supply BOKE
Impact resistance IK06
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett A 1200 white 230V 36W 3750lm 75° IP20 DALI 930

Product code 17368 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 36W
Maximum output 36W/1m
Luminous flux 3750lumens
Luminaire’s efficiency 104W
Correlated colour temperature warm white 3000K
Lens angle 75
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 76.0mm
Width 57.0mm
Length 1212.0mm
Weight 1.7 kg
Package weight 2.13 kg
In box 6pcs
Casing colour white
Casing material aluminium
Power supply BOKE
Impact resistance IK06
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett A 1200 white 230V 36W 3750lm 75° IP20 DALI 940

Product code 20462 **DALI dimmable**

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 36W
Maximum output 36W/1m
Luminous flux 3750lumens
Luminaire’s efficiency 104W
Correlated colour temperature pure white 4000K
Lens angle 75
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 76.0mm
Width 57.0mm
Length 1212.0mm
Weight 1.7 kg
Package weight 2.13 kg
In box 6pcs
Casing colour white
Casing material aluminium
Power supply BOKE
Impact resistance IK06
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett A 1500 up-down black 230V 56W 6000lm CRI80 75° IP20 DALI 3000K, 4000K, 5700K 3CCT

Product code 19321 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 56W
Maximum output 56W/1m
Luminous flux 6000lumens
Luminaire’s efficiency 107W
Correlated colour temperature 3CCT
3000K, 4000K, 5700K
Lens angle 75
Cri 80
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 76.0mm
Width 57.0mm
Length 1512.0mm
In box 6pcs
Casing colour black
Casing material aluminium
Power supply BOKE
Impact resistance IK06
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett A 1500 white 230V 45W 3750lm 75° IP20 DALI 930

Product code 17369 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 45W
Maximum output 45W/1m
Luminous flux 3750lumens
Luminaire’s efficiency 83W
Correlated colour temperature warm white 3000K
Lens angle 75
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 76.0mm
Width 57.0mm
Length 1512.0mm
Weight 1.7 kg
Package weight 2.13 kg
In box 6pcs
Casing colour white
Casing material aluminium
Power supply BOKE
Impact resistance IK06
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years








Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Barrett A 600 up-down black 230V 22W 1950lm CRI90 110° IP20 DALI 3000K, 4000K, 5700K 3CCT

Product code 17352 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 22W
Maximum output 22W/1m
Luminous flux 1950lumens
Luminaire’s efficiency 89W
Correlated colour temperature 3CCT
3000K, 4000K, 5700K
Lens angle 110
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 76.0mm
Width 57.0mm
Length 602.0mm
Weight 1.7 kg
Package weight 2.13 kg
In box 6pcs
Casing colour black
Casing material aluminium
Impact resistance IK06
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years



Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Bianca 600 MW white 230V 17W 2349lm CRI80 120° IP44 DALI 3000K, 4000K, 5000K 3CCT

Product code 22405 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 17W
Maximum output 17W/1m
Luminous flux 2349lumens
Luminaire’s efficiency 138W
Correlated colour temperature 3CCT
3000K, 4000K, 5000K
Lens angle 120
Cri 80
Sdcm - macadam ellipses 6
Protection class IP44
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 52.2mm
Width 152.0mm
Length 660.0mm
Weight 1.55 kg
Package weight 1.8 kg
In package 1pc
In box 4pcs
Casing colour white
Casing material polycarbonate
Polishing matt
Power supply BOKE
Work environment indoor use
Operation temperature -20° +40°C
Certificates CE, D, F
Warranty 5 years



High-quality, dimmable ceiling light. DALI Dim technology allows adjusting the light according to preference. 4000K LED lights provide clear and sharp illumination, perfect for lighting stores and other commercial spaces. The high color rendering index CRI90 ensures the accuracy of colors under the light beam. IP44 protection class means the luminaire can be used even in damp conditions. Illuminate your world with the help of LED House professionals - check out our portfolio of projects here!!

LED luminaire Prolumen Bianca S1 1200 white 230V 39W 4742lm 120° IP44 840

Product code 17442

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 39W
Maximum output 39W/1m
Luminous flux 4742lumens
Luminaire’s efficiency 122W
Correlated colour temperature pure white 4000K
Lens angle 120
Source of light OSRAM LED
Cri 80
Sdcm - macadam ellipses 5
Protection class IP44
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 52.0mm
Width 152.0mm
Length 1200.0mm
Casing colour white
Casing material polycarbonate
Polishing matt
Power supply BOKE
Work environment indoor use
Operation temperature -20° - +45°C
Warranty 5 years



Bianca S1 linear light. When used properly, the light is energy-efficient, environmentally friendly, and has a very long lifespan (50,000 hours). Illuminate your world with the help of LED House professionals - check out our project portfolio here!

© LED House OÜ, (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee

LED luminaire Prolumen Bianca S1 1200 white 230V 39W 4742lm 120° IP44 DALI 840

Product code 17448 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 39W
Maximum output 39W/1m
Luminous flux 4742lumens
Luminaire’s efficiency 122W
Correlated colour temperature pure white 4000K
Lens angle 120
Source of light OSRAM LED
Cri 80
Sdcm - macadam ellipses 5
Protection class IP44
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 52.0mm
Width 152.0mm
Length 1200.0mm
Casing colour white
Casing material polycarbonate
Polishing matt
Power supply BOKE
Work environment indoor use
Operation temperature -20° - +45°C
Warranty 5 years



Bianca S1 linear light. When used properly, the light is energy-efficient, environmentally friendly, and has a very long lifespan (50,000 hours). Illuminate your world with the help of LED House professionals - check out our project portfolio here!

LED luminaire Prolumen Bianca white 230V 17W 2349lm CRI80 120° IP44 DALI 3000K, 4000K, 5000K 3CCT

Product code 19066 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 17W
Maximum output 17W/1m
Luminous flux 2349lumens
Luminaire’s efficiency 138W
Correlated colour temperature 3CCT
3000K, 4000K, 5000K
Lens angle 120
Cri 80
Sdcm - macadam ellipses 6
Protection class IP44
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 52.2mm
Width 152.0mm
Length 660.0mm
Weight 1.55 kg
Package weight 1.8 kg
In package 1pc
In box 4pcs
Casing colour white
Casing material polycarbonate
Polishing matt
Power supply BOKE
Work environment indoor use
Operation temperature -20° +40°C
Certificates CE, D, F
Warranty 5 years



High-quality, dimmable ceiling light. DALI Dim technology allows adjusting the light according to preference. 4000K LED lights provide clear and sharp illumination, perfect for lighting stores and other commercial spaces. The high color rendering index CRI90 ensures the accuracy of colors under the light beam. IP44 protection class means the luminaire can be used even in damp conditions. Illuminate your world with the help of LED House professionals - check out our portfolio of projects here!!

Ceiling lamp Prolumen DB106B 1200 white 230V 20W 2200lm CRI90 120° IP44 DALI 3000K, 4000K, 5700K 3CCT

Product code 17353 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 20W
Maximum output 20W/1m
Luminous flux 2200lumens
Luminaire’s efficiency 110W
Correlated colour temperature 3CCT
3000K, 4000K, 5700K
Lens angle 120
Cri 90
Sdcm - macadam ellipses 6
Protection class IP44
Lifespan 50000h
Height 80.0mm
Width 207.0mm
Length 1200.0mm
In package 1pc
In box 6pcs
Casing colour white
Casing material aluminium
Polishing matt
Impact resistance IK08
Work environment indoor use
Operation temperature -20 ~40°C
Certificates CE
Warranty 5 years



High-quality PROLUMEN ship light, possible to install both on the surface and hanging. The light temperature can be set by yourself. There are buttons on the light that allow you to choose between 3000K (warm white), 4000K (daylight), or 5700K cool white light. A high coluor rendering index CRI90 does not distort the true colours of objects under the light beam. Protection class IP44 means that the luminaire can also be used in damp conditions. If you haven't found the perfect light fixture from our product range yet, then browse through the PROLUMEN catalogue as well!

Ceiling lamp Prolumen DB106B 1200 white 40W 4400lm CRI80 120° IP44 0-10V 3000K, 4000K, 5700K 3CCT

Product code 17351 0-10V dimmable

Brand Prolumen
Power factor 0.90
Dimmable 0-10V
Output 40W
Maximum output 40W/1m
Luminous flux 4400lumens
Luminaire’s efficiency 110W
Correlated colour temperature 3CCT
3000K, 4000K, 5700K
Lens angle 120
Cri 80
Sdcm - macadam ellipses 6
Protection class IP44
Lifespan 50000h
Height 80.0mm
Width 208.0mm
Length 1200.0mm
In box 12pcs
Casing colour white
Casing material aluminium
Polishing matt
Impact resistance IK08
Work environment indoor use
Certificates CE
Warranty 5 years



High-quality PROLUMEN ship light, possible to install both on the surface and hanging. The light temperature can be set by yourself. There are buttons on the light that allow you to choose between 3000K (warm white), 4000K (daylight), or 5700K cool white light. A high coluor rendering index CRI90 does not distort the true colours of objects under the light beam. Protection class IP44 means that the luminaire can also be used in damp conditions. If you haven't found the perfect light fixture from our product range yet, then browse through the PROLUMEN catalogue as well!

Ceiling lamp Prolumen DB106B 1500 white 230V 58W 6500lm CRI90 120° IP44 3000K, 4000K, 5700K 3CCT

Product code 18149

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 58W
Maximum output 58W/1m
Luminous flux 6500lumens
Luminaire’s efficiency 112W
Correlated colour temperature 3CCT
3000K, 4000K, 5700K
Lens angle 120
Cri 90
Sdcm - macadam ellipses 6
Protection class IP44
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 80.0mm
Width 207.0mm
Length 1500.0mm
In box 12pcs
Casing colour white
Casing material aluminium
Polishing matt
Impact resistance IK08
Work environment indoor use
Certificates CE
Warranty 5 years



High-quality PROLUMEN ship light, possible to install both on the surface and hanging. The light temperature can be set by yourself. There are buttons on the light that allow you to choose between 3000K (warm white), 4000K (daylight), or 5700K cool white light. A high coluor rendering index CRI90 does not distort the true colours of objects under the light beam. Protection class IP44 means that the luminaire can also be used in damp conditions. If you haven't found the perfect light fixture from our product range yet, then browse through the PROLUMEN catalogue as well!

Ceiling lamp Prolumen DB157 UGR<19 1200 white 230V 40W 4550lm CRI95 80° IP20 3000K, 4000K 2CCT

Product code 18173

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 40W
Maximum output 40W/1m
Rated current 1250mA
Luminous flux 4550lumens
Luminaire’s efficiency 114W
Correlated colour temperature 2CCT
3000K, 4000K
Lens angle 80
Cri 95
Ugr 19
Sdcm - macadam ellipses 3
Protection class IP20
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 59.0mm
Width 120.0mm
Length 1200.0mm
In package 1pc
In box 6pcs
Casing colour white
Casing material aluminium
Impact resistance IK08
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years



Ceiling lamp Prolumen DB157 UGR<19 1500 white 230V 35-50W 6600lm CRI80 80° IP20 3000K, 4000K 2CCT

Product code 23509


Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 35-50W
Maximum output 50W/1m
Rated current 1580mA
Luminous flux 6600lumens
Correlated colour temperature 2CCT 3000K, 4000K
Lens angle 80
Cri 80
Ugr 19
Sdcm - macadam ellipses 3
Protection class IP20
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 59.0mm
Width 120.0mm
Length 1500.0mm
In package 1pc
In box 6pcs
Casing colour white
Casing material aluminium
Impact resistance IK08
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years




Linear light Prolumen Delia UGR 600 black 230V 20W 2000lm CRI90 100° IP20 3000K, 4000K, 5700K 3CCT

Product code 15206

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 20W
Maximum output 20W/1m
Luminous flux 2000lumens
Luminaire’s efficiency 100W
Correlated colour temperature 3CCT
3000K, 4000K, 5700K
Lens angle 100
Cri 90
Ugr 18
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 70.0mm
Width 60.0mm
Length 604.0mm
Weight 1.15 kg
Package weight 1.65 kg
In package 1pc
In box 12pcs
Casing colour black
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years








Black body and square design. Elegant and functional, this minimalist pendant light is an excellent choice for those who appreciate simplicity and modernity in their home decor. With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000h). This luminaire has an ideal color rendering index for workspaces and offices. On some models, the light color is changeable: 3000K, 4000K, 6000K. The luminaire can be successfully installed both surface-mounted and suspended. In both cases, the result is guaranteed to be good. Hanging cables (2 pcs) must be ordered separately. Illuminate your world with LED House professionals - check out our project portfolio here!

Linear light Prolumen Delia UGR19 1200 black 230V 40W 4500lm 100° IP40 DALI 840

Product code 15323 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 40W
Maximum output 40W/1m
Luminous flux 4500lumens
Luminaire’s efficiency 113W
Correlated colour temperature pure white 4000K
Lens angle 100
Cri 80
Ugr 18
Lor 80
Sdcm - macadam ellipses 6
Protection class IP40
Lifespan 50000h
Llmf tm21 L80B50 @25°C 50.000h
Height 70.0mm
Width 60.0mm
Length 1204.0mm
Weight 2.2 kg
Package weight 3 kg
In package 1pc
In box 12pcs
Casing colour black
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years








Black body and square design. Elegant and functional, this minimalist pendant light is an excellent choice for those who appreciate simplicity and modernity in their home decor. With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000h). This luminaire has an ideal color rendering index for workspaces and offices. On some models, the light color is changeable: 3000K, 4000K, 6000K. The luminaire can be successfully installed both surface-mounted and suspended. In both cases, the result is guaranteed to be good. Hanging cables (2 pcs) must be ordered separately. Illuminate your world with LED House professionals - check out our project portfolio here!

Linear light Prolumen Delia UGR19 1200 black 230V 40W 4500lm CRI90 100° IP20 3000K, 4000K, 5700K 3CCT

Product code 15026

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 40W
Maximum output 40W/1m
Luminous flux 4500lumens
Luminaire’s efficiency 113W
Correlated colour temperature 3CCT
3000K, 4000K, 5700K
Lens angle 100
Cri 90
Ugr 18
Lor 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L80B50 @25°C 50.000h
Height 70.0mm
Width 60.0mm
Length 1204.0mm
Weight 2.2 kg
Package weight 3 kg
In package 1pc
In box 12pcs
Casing colour black
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years



Black body and square design. Elegant and functional, this minimalist pendant light is an excellent choice for those who appreciate simplicity and modernity in their home decor. With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000h). This luminaire has an ideal color rendering index for workspaces and offices. On some models, the light color is changeable: 3000K, 4000K, 6000K. The luminaire can be successfully installed both surface-mounted and suspended. In both cases, the result is guaranteed to be good. Hanging cables (2 pcs) must be ordered separately. Illuminate your world with LED House professionals - check out our project portfolio here!

Linear light Prolumen Delia UGR19 1200 white 230V 40W 4500lm CRI80 100° IP20 3000K, 4000K, 5700K 3CCT

Product code 15535

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 40W
Maximum output 40W/1m
Luminous flux 4500lumens
Luminaire’s efficiency 113W
Correlated colour temperature 3CCT
3000K, 4000K, 5700K
Lens angle 100
Cri 80
Ugr 18
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L80B50 @25°C 50.000h
Height 70.0mm
Width 60.0mm
Length 1204.0mm
Weight 2.2 kg
Package weight 3 kg
In package 1pc
In box 12pcs
Casing colour white
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years




White body and square design. Elegant and functional, this minimalist luminaire is an excellent choice for those who appreciate simplicity and modernity in their home decor. This luminaire can be installed as both a pendant light and surface-mounted. With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000 hours). Some models have adjustable light color: 3000K, 4000K, 6000K. The luminaire can be successfully installed both surface-mounted and suspended. In both cases, good results are guaranteed. Suspension cables (2 pcs) must be ordered separately. Illuminate your world with the help of LED House professionals - check out our project portfolio here!

LED luminaire Prolumen Delilah 0,6m white 230V 15W 1400lm 110° IP20 940

© LED House OÜ, (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee

Product code 17051

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 15W
Maximum output 15W/1m
Luminous flux 1400lumens
Luminaire’s efficiency 93W
Correlated colour temperature pure white 4000K
Lens angle 110
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 29.0mm
Width 62.0mm
Length 615.0mm
Installation opening diameter 607x54mm
In box 12pcs
Casing colour white
Casing material aluminium
Polishing matt
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE, RoHS
Warranty 5 years






Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - check out our project portfolio here!Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - check out our project portfolio here!

LED luminaire Prolumen Delilah 1,2m white 230V 30W 3100lm 110° IP20 940

© LED House OÜ, (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee

Product code 17052

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 30W
Maximum output 30W/1m
Luminous flux 3100lumens
Luminaire’s efficiency 103W
Correlated colour temperature pure white 4000K
Lens angle 110
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 29.0mm
Width 62.0mm
Length 1208.0mm
Installation opening diameter 1201x54mm
In box 6pcs
Casing colour white
Casing material aluminium
Polishing matt
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE, RoHS
Warranty 5 years






Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - check out our project portfolio here!Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - check out our project portfolio here!

LED luminaire Prolumen Delilah 1,5m white 230V 37W 3800lm 110° IP20 940

© LED House OÜ, (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee

Product code 17053

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 37W
Maximum output 37W/1m
Luminous flux 3800lumens
Luminaire’s efficiency 103W
Correlated colour temperature pure white 4000K
Lens angle 110
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 29.0mm
Width 62.0mm
Length 1505.0mm
Installation opening diameter 1498x54mm
In box 6pcs
Casing colour white
Casing material aluminium
Polishing matt
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE, RoHS
Warranty 5 years






Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - check out our project portfolio here!Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - check out our project portfolio here!

LED luminaire Prolumen Delilah 2,4m white 230V 60W 6200lm 110° IP20 940

© LED House OÜ, (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee

Product code 16407

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 60W
Maximum output 60W/1m
Luminous flux 6200lumens
Luminaire’s efficiency 103W
Correlated colour temperature pure white 4000K
Lens angle 110
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 29.0mm
Width 62.0mm
Length 2395.0mm
Installation opening diameter 2388x54mm
In box 6pcs
Casing colour white
Casing material aluminium
Polishing matt
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE, RoHS
Warranty 5 years






Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - check out our project portfolio here!Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - check out our project portfolio here!

LED luminaire Prolumen Delilah L-corner 150+150 white 230V 7.5W 650lm 110° IP20 940

Product code 17054

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 7.5W
Maximum output 7.5W/1m
Luminous flux 650lumens
Luminaire’s efficiency 87W
Correlated colour temperature pure white 4000K
Lens angle 110
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 29.0mm
Width 150.0mm
Length 150.0mm
In box 24pcs
Casing colour white
Casing material aluminium
Polishing matt
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE, RoHS
Warranty 5 years






Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - check out our project portfolio here!Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - check out our project portfolio here!

Ceiling lamp Prolumen Delilah white 230V 45W 4300lm 45° IP20 940

Product code 16793

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 45W
Maximum output 45W/1m
Luminous flux 4300lumens
Luminaire’s efficiency 96W
Correlated colour temperature pure white 4000K
Lens angle 45
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 29.0mm
Width 62.0mm
Length 1802.0mm
Package weight 2.68 kg
In package 1pc
In box 6pcs
Casing colour white
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years





Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - check out our project portfolio here!Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - check out our project portfolio here!

LED luminaire Prolumen Dennis 1200 white 230V 40W 4400lm 120° IP20 840

Product code 15353

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 40W
Maximum output 40W/1m
Luminous flux 4400lumens
Luminaire’s efficiency 110W
Correlated colour temperature pure white 4000K
Lens angle 120
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 64.0mm
Width 71.0mm
Length 1203.0mm
In box 12pcs
Casing colour white
Impact resistance IK08
Work environment indoor use
Certificates CE
Warranty 5 years



A classic luminaire for offices, schools, hotels, corridors, etc. Its minimalist design blends seamlessly into various interiors, whether at home, in the office, or in a business environment. Illuminate your world with LED House professionals - check out our project portfolio here!

LED luminaire Prolumen Dennis 1500 white 230V 58W 5850lm 120° IP20 840

Product code 15628

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 58W
Maximum output 58W/1m
Luminous flux 5850lumens
Luminaire’s efficiency 101W
Correlated colour temperature pure white 4000K
Lens angle 120
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 64.0mm
Width 71.0mm
Length 1503.0mm
In box 12pcs
Casing colour white
Impact resistance IK08
Work environment indoor use
Certificates CE
Warranty 5 years



A classic luminaire for offices, schools, hotels, corridors, etc. Its minimalist design blends seamlessly into various interiors, whether at home, in the office, or in a business environment. Illuminate your world with LED House professionals - check out our project portfolio here!

LED luminaire Prolumen EMPIRIO B025S 1500 white 230V 75W 12000lm 90° IP40 840

Product code 15018

Brand Prolumen
Supply voltage 230V
Output 75W
Maximum output 75W/1m
Luminous flux 12000lumens
Luminaire’s efficiency 160W
Correlated colour temperature pure white 4000K
Lens angle 90
Cri 80
Sdcm - macadam ellipses 3
Protection class IP40
Lifespan 50000h
Llmf tm21 L80B10 @25°C 80.000h
Height 72.0mm
Width 65.0mm
Length 1460.0mm
Casing colour white
Casing material aluminium
Power supply OSRAM
Work environment indoor use
Operation temperature -20°C - +45°C
Certificates CE, RoHS
Warranty 5 years



A ceiling light fixture with uniform light distribution that can be installed either flush-mounted or suspended from the ceiling. An ideal light fixture for above desks! 4000K LED lights provide clear and sharp light, perfect for illuminating stores and other commercial spaces. Option to order linear lights with different lenses and power levels: 30°, 60°, 90°, 120°, 2 x 25°. Improve your everyday lighting quality and choose a top-notch lighting solution from the LED house product range! Illuminate your world with LED House professionals - check out our project portfolio here!

Ceiling lamp Prolumen Kalis 1200 white 230V 13W 1400lm 90° IP43 DALI 930

Product code 23463 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 13W
Maximum output 13W/1m
Luminous flux 1400lumens
Luminaire’s efficiency 108W
Correlated colour temperature warm white 3000K
Lens angle 90
Cri 90
Protection class IP43
Lifespan 50000h
Height 75.0mm
Width 37.0mm
Length 1125.0mm
In package 1pc
Casing colour white
Power supply BOKE
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years



Ceiling lamp Prolumen Lidya 1100 up-down white 230V 45W 4700lm CRI80 50° IP20 3000K-4000K 2CCT

Product code 16791

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 45W
Maximum output 45W/1m
Luminous flux 4700lumens
Luminaire’s efficiency 104W
Correlated colour temperature 2CCT 3000K-4000K
Lens angle 50
Cri 80
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 74.0mm
Width 236.0mm
Length 1172.0mm
Package weight 4.8 kg
In package 1pc
In box 2pcs
Casing colour white
Casing material aluminium
Work environment indoor use
Operation temperature -20° - +40°C
Certificates CE, RoHS
Warranty 5 years



Up-down light fixture, ideal for offices and other workspaces. Adjustable light color temperature: 3000K, 4000K. This fixture is suitable for indoor use only, with IP20 protection rating. The light fixture has an ideal color rendering index CRI90 for workspaces and offices. With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000h). Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED House product range!

© LED House OÜ, (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee

Ceiling lamp Prolumen Lidya 1500 up-down white 230V 60W 5400lm CRI90 50° IP20 3000K-4000K 2CCT

Product code 16792

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 60W
Maximum output 60W/1m
Luminous flux 5400lumens
Luminaire’s efficiency 90W
Correlated colour temperature 2CCT 3000K-4000K
Lens angle 50
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 74.0mm
Width 236.0mm
Length 1552.0mm
Package weight 5.9 kg
In package 1pc
In box 2pcs
Casing colour white
Casing material aluminium
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years



Up-down light fixture, ideal for offices and other workspaces. Adjustable light color temperature: 3000K, 4000K. This fixture is suitable for indoor use only, with IP20 protection rating. The light fixture has an ideal color rendering index CRI90 for workspaces and offices. With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000h). Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED House product range!

Linear light Prolumen Linda 5076 1500 UGR□20 with downward light distribution black 230V 43W 5100lm 90° IP20 DALI 830

Product code 19391 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 43W
Maximum output 43W/1m
Luminous flux 5100lumens
Luminaire’s efficiency 119W
Correlated colour temperature warm white 3000K
Lens angle 90
Cri 80
Ugr 20
Sdcm - macadam ellipses 3
Protection class IP20
Lifespan 50000h
Llmf tm21 L80B50 @25°C 75.000h
Height 76.0mm
Width 50.0mm
Length 1440.0mm
In box 6pcs
Casing colour black
Casing material aluminium
Polishing matt
Power supply BOKE
Impact resistance IK06
Work environment indoor use
Operation temperature -20° - +45°C
Certificates CE
Warranty 5 years



Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors. Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space. Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Linear light Prolumen Linda 66D 1200 with downward light distribution black 230V 28W 3600lm 75° IP20 DALI 830

Product code 17751 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 28W
Maximum output 28W/1m
Luminous flux 3600lumens
Luminaire’s efficiency 129W
Correlated colour temperature warm white 3000K
Lens angle 75
Cri 80
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70B50 @25°C 50.000h
Height 75.0mm
Width 56.0mm
Length 1204.0mm
Weight 2.75 kg
In box 6pcs
Casing colour black
Casing material aluminium
Polishing matt
Power supply BOKE
Impact resistance IK06
Work environment indoor use
Operation temperature -20° - +45°C
Certificates CE
Warranty 5 years



Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors. Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space. Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Linear light Prolumen Linda 66D 1200 with downward light distribution black 230V 28W 3800lm 75° IP20 DALI 840

Product code 17750 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 28W
Maximum output 28W/1m
Luminous flux 3800lumens
Luminaire’s efficiency 136W
Correlated colour temperature pure white 4000K
Lens angle 75
Cri 80
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70B50 @25°C 50.000h
Height 75.0mm
Width 56.0mm
Length 1204.0mm
Weight 2.75 kg
In box 6pcs
Casing colour black
Casing material aluminium
Polishing matt
Power supply BOKE
Impact resistance IK06
Work environment indoor use
Operation temperature -20° - +45°C
Certificates CE
Warranty 5 years



Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors. Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space. Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Linear light Prolumen Linda 66D 1200 with downward light distribution white 230V 28W 3800lm 75° IP20 DALI 840

Product code 20672 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 28W
Maximum output 28W/1m
Luminous flux 3800lumens
Luminaire’s efficiency 136W
Correlated colour temperature pure white 4000K
Lens angle 75
Cri 80
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70B50 @25°C 50.000h
Height 75.0mm
Width 56.0mm
Length 1204.0mm
Weight 2.75 kg
In box 6pcs
Casing colour white
Casing material aluminium
Polishing matt
Power supply BOKE
Impact resistance IK06
Work environment indoor use
Operation temperature -20° - +45°C
Certificates CE
Warranty 5 years



Linear light Prolumen Linda 66D 1200 with light distribution up and down + suspension wires. black 230V 40W 5550lm 75° IP20 DALI / PUSH 840

Product code 17741 DALI / PUSH dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI / PUSH
Output 40W
Maximum output 40W/1m
Luminous flux 5550lumens
Luminaire’s efficiency 139W
Correlated colour temperature pure white 4000K
Lens angle 75
Cri 80
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 75.0mm
Width 56.0mm
Length 1204.0mm
Weight 1.7 kg
Package weight 2.13 kg
In box 6pcs
Casing colour black
Casing material aluminium
Power supply BOKE
Impact resistance IK06
Work environment indoor use
Operation temperature -20° - +45°C
Certificates CE
Warranty 5 years



Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors. Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space. Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Linear light Prolumen Linda 66D 1200 with light distribution upwards and downwards + suspension wires. black 230V 40W

5270lm 75° IP20 DALI 8

Product code 17752 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 40W
Maximum output 40W/1m
Luminous flux 5270lumens
Luminaire’s efficiency 132W
Correlated colour temperature warm white 3000K
Lens angle 75
Cri 80
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 75.0mm
Width 56.0mm
Length 1204.0mm
Weight 1.7 kg
Package weight 2.13 kg
In box 6pcs
Casing colour black
Casing material aluminium
Power supply BOKE
Impact resistance IK06
Work environment indoor use
Operation temperature -20° - +45°C
Certificates CE
Warranty 5 years



Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors. Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space. Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Linear light Prolumen Linda 66D 1500 with downward light distribution black 230V 35W 4600lm 75° IP20 DALI 830

Product code 19315 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 35W
Maximum output 35W/1m
Luminous flux 4600lumens
Luminaire’s efficiency 131W
Correlated colour temperature warm white 3000K
Lens angle 75
Cri 80
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70B50 @25°C 50.000h
Height 75.0mm
Width 56.0mm
Length 1504.0mm
In box 6pcs
Casing colour black
Casing material aluminium
Polishing matt
Power supply BOKE
Impact resistance IK06
Work environment indoor use
Operation temperature -20° - +45°C
Certificates CE
Warranty 5 years



Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors. Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space. Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Linear light Prolumen Linda 66D 1500 with light distribution upwards and downwards, UGR<19 + suspension wires. black 230V 49W 6500lm 75° IP2

Product code 18163 **DALI dimmable**

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 49W
Maximum output 49W/1m
Luminous flux 6500lumens
Luminaire’s efficiency 133W
Correlated colour temperature pure white 4000K
Lens angle 75
Cri 80
Ugr 19
Sdcm - macadam ellipses 3
Protection class IP20
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 75.0mm
Width 56.0mm
Length 1504.0mm
Weight 1.7 kg
Package weight 2.13 kg
In box 6pcs
Casing colour black
Casing material aluminium
Power supply BOKE
Impact resistance IK06
Work environment indoor use
Operation temperature -20° - +45°C
Certificates CE
Warranty 5 years



Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors. Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space. Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Linear light Prolumen Linda 900 MicroPrism white 230V 28W 3500lm CRI80 90° IP20 DALI / PUSH 3000K, 3500K, 4000K 3CCT

Product code 21007 DALI / PUSH dimmable



Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI / PUSH
Output 28W
Maximum output 28W/1m
Luminous flux 3500lumens
Luminaire’s efficiency 125W
Correlated colour temperature 3CCT 3000K, 3500K, 4000K
Lens angle 90
Cri 80
Sdcm - macadam ellipses 3
Protection class IP20
Lifespan 50000h
Llmf tm21 L90B10 @25°C 50.000h
Height 76.0mm
Width 50.0mm
Length 906.0mm
In package 1pc
In box 4pcs
Casing colour white
Casing material aluminium
Power supply BOKE
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE, RoHS
Warranty 5 years

Linear light Prolumen Linda C27 1200 with downward light distribution black 230V 30W 4200lm 100° IP20 DALI 840

Product code 17876 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable DALI
Output 30W
Maximum output 30W/1m
Luminous flux 4200lumens
Luminaire’s efficiency 140W
Correlated colour temperature pure white 4000K
Lens angle 100
Cri 80
Ugr 19
Sdcm - macadam ellipses 3
Protection class IP20
Lifespan 160000h
Llmf tm21 L70B50 @25°C 160.000h
Height 55.0mm
Width 50.0mm
Length 1120.0mm
Weight 1.94 kg
In box 6pcs
Casing colour black
Casing material aluminium
Polishing matt
Power supply TRIDONIC
Impact resistance IK08
Work environment indoor use
Operation temperature -20° - +45°C
Certificates CE
Warranty 5 years



Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors. Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space. Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Linear light Prolumen Linda C27 1200 white 230V 30W 3900lm 100° IP20 830

Product code 17909

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 30W
Maximum output 30W/1m
Luminous flux 3900lumens
Luminaire’s efficiency 130W
Correlated colour temperature warm white 3000K
Lens angle 100
Cri 80
Sdcm - macadam ellipses 3
Protection class IP20
Lifespan 160000h
Llmf tm21 L70B50 @25°C 160.000h
Height 55.0mm
Width 50.0mm
Length 1120.0mm
Weight 1.94 kg
In box 6pcs
Casing colour white
Casing material aluminium
Polishing matt
Power supply TRIDONIC
Impact resistance IK08
Work environment indoor use
Operation temperature -20° - +45°C
Certificates CE
Warranty 5 years



Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors. Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space. Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Linear light Prolumen Linde 1200 DALI black 230V 40W 4000lm CRI80 120° IP20 DALI 3000K, 4000K, 6000K 3CCT

Product code 23512 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 40W
Maximum output 40W/1m
Luminous flux 4000lumens
Luminaire’s efficiency 100W
Correlated colour temperature 3CCT
3000K, 4000K, 6000K
Lens angle 120
Cri 80
En62471 1
Protection class IP20
Lifespan 50000h
Height 70.0mm
Width 50.0mm
Length 1200.0mm
In package 1pc
Casing colour black
Power supply BOKE
Work environment indoor use
Certificates CE, RoHS
Warranty 3 years



LED luminaire Prolumen Meena 1200 22-40W white 230V 5600lm CRI80 120° IP44 3000K, 4000K, 5000K 3CCT

Product code 17711

Brand Prolumen
Supply voltage 230V
Luminous flux 5600lumens
Correlated colour temperature 3CCT
3000K, 4000K, 5000K
Lens angle 120
Cri 80
Sdcm - macadam ellipses 3
Protection class IP44
Llmf tm21 L90B10 @25°C 50.000h
Height 55.0mm
Width 140.0mm
Length 1198.0mm
In package 1pc
Casing colour white
Casing material aluminium + plastic
Power supply OSRAM
Operation temperature -20° - +45°C
Certificates CE, RoHS
Warranty 5 years



PROLUMEN Meena linear luminaire with adjustable power levels of 22W/30W/35W/40W. A high-quality linear light suitable for installation in parking garages, large closets, corridors, and warehouses. The Meena luminaire is designed to be very easy to install and maintain. The housing can be opened with a button press, and the suspension cables are adjustable during installation.

© LED House OÜ, (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee

LED luminaire Prolumen Meena 1500 230V 60W 8400lm CRI80 120° IP44 3000K, 4000K, 5000K 3CCT

Product code 17456

Brand Prolumen
Supply voltage 230V
Output 60W
Maximum output 60W/1m
Luminous flux 8400lumens
Luminaire’s efficiency 140W
Correlated colour temperature 3CCT
3000K, 4000K, 5000K
Lens angle 120
Cri 80
Sdcm - macadam ellipses 3
Protection class IP44
Lifespan 100000h
Height 55.0mm
Width 140.0mm
Length 1500.0mm
In package 1pc
Casing material aluminium + plastic
Operation temperature -20° - +45°C
Certificates CE, RoHS
Warranty 5 years



PROLUMEN Meena linear luminaire with adjustable power levels of 22W/30W/35W/40W. A high-quality linear light suitable for installation in parking garages, large closets, corridors, and warehouses. The Meena luminaire is designed to be very easy to install and maintain. The housing can be opened with a button press, and the suspension cables are adjustable during installation.

LED luminaire Prolumen Miina 1200 white 230V 40W 6400lm CRI80 120° IP65 3000K, 4000K, 5000K 3CCT

Product code 17753

Brand Prolumen
Supply voltage 230V
Output 40W
Maximum output 40W/1m
Luminous flux 6400lumens
Luminaire’s efficiency 160W
Correlated colour temperature 3CCT
3000K, 4000K, 5000K
Lens angle 120
Cri 80
Sdcm - macadam ellipses 3
Protection class IP65
Height 54.0mm
Width 102.0mm
Length 1219.0mm
In package 1pc
In box 6pcs
Casing colour white
Casing material aluminium + plastic
Power supply BOKE
Operation temperature -20° - +45°C
Certificates CE, RoHS
Warranty 5 years



PROLUMEN Miina linear light fixture with adjustable color temperature and power levels. A high-quality linear fixture suitable for installation in parking garages, large closets, corridors, and warehouses. The opal glass provides a very wide beam angle, evenly covering a larger area. The Miina fixture is designed for easy installation and maintenance. The color temperature and power are adjustable via a button on the fixture. A motion sensor can also be added to the Miina fixture. Adding the sensor is easy thanks to the openable end cap, where the sensor wires can be connected. With the motion sensor, LED lights become even more energy-efficient and convenient, as the step of turning the light on and off with a switch is eliminated, and the fixture turns off automatically. Trust your lighting project to the experienced team of LED House - let's bring your vision to life!

Ceiling lamp Prolumen Minus 1200 white 230V 19W 1750lm IP40 DALI 930

Product code 23462 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 19W
Maximum output 19W/1m
Luminous flux 1750lumens
Luminaire’s efficiency 92W
Correlated colour temperature warm white 3000K
Cri 90
Protection class IP40
Lifespan 50000h
Height 62.0mm
Width 38.0mm
Length 1125.0mm
In package 1pc
Casing colour white
Power supply BOKE
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years



Ceiling lamp Prolumen Minus 1700 white 230V 29W 2650lm IP40 DALI 930

Product code 23461 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 29W
Maximum output 29W/1m
Luminous flux 2650lumens
Luminaire’s efficiency 91W
Correlated colour temperature warm white 3000K
Cri 90
Protection class IP40
Lifespan 50000h
Height 62.0mm
Width 38.0mm
Length 1685.0mm
In package 1pc
Casing colour white
Power supply BOKE
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years



Linear light Prolumen Retro Force 1500 white 230V 75W 12480lm 120° IP54 840

Product code 17675

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 75W
Maximum output 75W/1m
Luminous flux 12480lumens
Luminaire’s efficiency 166W
Correlated colour temperature pure white 4000K
Lens angle 120
Source of light SAMSUNG LED
Cri 80
Sdcm - macadam ellipses 3
Protection class IP54
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 64.8mm
Width 107.0mm
Length 1460.0mm
In package 1pc
Casing colour white
Power supply BOKE
Impact resistance IK10
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years








PROLUMEN Retro Force industrial luminaire. These LED luminaires are equipped with high-quality components and provide excellent lighting for indoor use. The G-Force luminaire has adjustable power strength, allowing users to customize the brightness themselves. 38W/48W/58W/68W/75W Also available with DALI dimming technology, which allows users to adjust the brightness of the light according to their needs.

© LED House OÜ, (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee

Linear light Prolumen Retro Force 1500 white 230V 75W 12480lm 120° IP54 DALI 840

Product code 17443 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 75W
Maximum output 75W/1m
Luminous flux 12480lumens
Luminaire’s efficiency 166W
Correlated colour temperature pure white 4000K
Lens angle 120
Cri 80
Sdcm - macadam ellipses 3
Protection class IP54
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 64.8mm
Width 107.0mm
Length 1460.0mm
In package 1pc
Casing colour white
Power supply BOKE
Impact resistance IK10
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years



PROLUMEN Retro Force industrial luminaire. These LED luminaires are equipped with high-quality components and provide excellent lighting for indoor use. The G-Force luminaire has adjustable power strength, allowing users to customize the brightness themselves. 38W/48W/58W/68W/75W Also available with DALI dimming technology, which allows users to adjust the brightness of the light according to their needs.

Linear light Prolumen RetroFit white 230V 30-76W 14000lm

CRI80 90° IP20 3000K, 4000K, 5000K 3CCT

Product code 19950

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 30-76W
Maximum output 76W/1m
Luminous flux 14000lumens
Correlated colour temperature 3CCT
3000K, 4000K, 5000K
Lens angle 90
Cri 80
Sdcm - macadam ellipses 3
Protection class IP20
Lifespan 80000h
Llmf tm21 L80B10 @25°C 80.000h
Height 27.5mm
Width 74.0mm
Length 1458.0mm
In package 1pc
Casing colour white
Power supply LIFUD
Impact resistance IK06
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years




The PROLUMEN RetroFit light is an innovative solution that allows for easy and efficient replacement of trunk lights, including models from well-known brands like Zombotel, Veko, Trilux, and Philips, without needing to replace the entire trunk. Easy Installation: The light is designed for simple installation into existing light fixtures, saving time and costs. Energy Efficiency: The PROLUMEN RetroFit light uses the latest LED technology, ensuring energy efficiency and a long service life, reducing ongoing maintenance costs. Customizability: You can choose from different color temperatures to suit the lighting in various spaces—from work environments to retail areas. Quality Guarantee: The light is made from high-quality materials, ensuring durability and reliable performance. Customized Lighting Solutions: The RetroFit light allows for the creation of various lighting solutions tailored to your specific needs and preferences. The PROLUMEN RetroFit light is an ideal choice for those seeking modern and efficient lighting that fits existing structures and provides quality illumination without additional costs.

Ceiling lamp Prolumen SmartGlow Linear 1200 black 230V 36W 4000lm CRI90 100x50° IP20 DIMMABLE 3000K-6500K

Product code 17730 dimmerdatav dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable dimmerdatav
Output 36W
Maximum output 36W/1m
Luminous flux 4000lumens
Luminaire’s efficiency 111W
Correlated colour temperature warm - cold white 3000K - 6500K
Lens angle 100x50
Cri 90
Ugr 6
Sdcm - macadam ellipses 3
Protection class IP20
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 85.0mm
Width 65.0mm
Length 1200.0mm
In package 1pc
Casing colour black
Casing material aluminium
Power supply BOKE
Work environment indoor use
Operation temperature -10 - +30°C
Certificates CE
Warranty 5 years






Ergonomic office light with adjustable color temperature, featuring an aesthetic and compact design that fits into any modern office. SmartGlow illuminates both the desk and the room - the light beam shines both downwards and upwards. The upward-directed light makes the room feel more spacious. The luminaire has an exceptionally good UGR value, meaning the light beam is not uncomfortable for the eyes and glare is minimal. If you want to make your space even more impressive, it is possible to order this luminaire in a connectable version, allowing the linear ceiling light to extend throughout the entire room. In addition to its good looks, SmartGlow is easy to install and control thanks to its patented lockable plug. It can be mounted suspended, surface-mounted, or recessed. As a bonus, it features HCL intelligent control with Casambi, presence, and daylight sensors. Contact our sales team, and we will plan a top-notch lighting solution for your spaces!

Ceiling lamp Prolumen SmartGlow Linear 1500 black 230V 36W 4000lm CRI90 50° IP20 DALI 3000K-6500K

Product code 17772 **DALI dimmable**

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 36W
Maximum output 36W/1m
Luminous flux 4000lumens
Luminaire’s efficiency 111W
Correlated colour temperature warm - cold white 3000K - 6500K
Lens angle 50
Cri 90
Ugr 6
Sdcm - macadam ellipses 3
Protection class IP20
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 85.0mm
Width 65.0mm
Length 1550.0mm
In package 1pc
Casing colour black
Casing material aluminium
Power supply BOKE
Work environment indoor use
Operation temperature -10 - +30°C
Certificates CE
Warranty 5 years





Ergonomic office light with adjustable color temperature, featuring an aesthetic and compact design that fits into any modern office. SmartGlow illuminates both the desk and the room - the light beam shines both downwards and upwards. The upward-directed light makes the room feel more spacious. The luminaire has an exceptionally good UGR value, meaning the light beam is not uncomfortable for the eyes and glare is minimal. If you want to make your space even more impressive, it is possible to order this luminaire in a connectable version, allowing the linear ceiling light to extend throughout the entire room. In addition to its good looks, SmartGlow is easy to install and control thanks to its patented lockable plug. It can be mounted suspended, surface-mounted, or recessed. As a bonus, it features HCL intelligent control with Casambi, presence, and daylight sensors. Contact our sales team, and we will plan a top-notch lighting solution for your spaces!

LED luminaire Prolumen Zennor 1200 frame white 230V IP20

Product code 17710

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Ugr 19
Sdcm - macadam ellipses 3
Protection class IP20
Lifespan 54000h
Llmf tm21 L90B50 @25°C 50.000h
Height 80.0mm
Width 46.0mm
Length 1182.0mm
In package 1pc
Casing colour white
Casing material aluminium
Power supply BOKE
Operation temperature -20° - +45°C
Certificates TUV ENEC, CB, CE, VDE, ROHS
Warranty 5 years



Zennor linear system allows customization of lighting according to specific requirements and room characteristics. The IP20 protection class ensures durability against dust and small amounts of liquid, making them suitable for various indoor spaces, such as offices, shopping malls, or homes. Illuminate your world with LED House professionals - check out our project portfolio here!

LED luminaire Prolumen Zennor 1200 module black 3675lm 20° IP20 830

Product code 22078

Brand Prolumen
Rated current 800mA
Luminous flux 3675lumens
Correlated colour temperature warm white 3000K
Lens angle 20
Cri 80
Ugr 16
Sdcm - macadam ellipses 3
Protection class IP20
Llmf tm21 L80B10 @25°C 50.000h
Length 1164.0mm
Casing colour black
No. of switches 50000pcs
Impact resistance IK02
Work environment indoor use



Zennor is an LED modular light fixture, where different lengths can be used to achieve different power and light output. LED module requires a separate power supply unit or housing with built-in power supply. Illuminate your world with LED House professionals - check out our project portfolio here!

LED luminaire Prolumen Zennor 1200 module black 50W 20° IP20 840

Product code 17393

Brand Prolumen
Output 50W
Maximum output 50W/1m
Correlated colour temperature pure white 4000K
Lens angle 20
Cri 80
Ugr 19
Sdcm - macadam ellipses 3
Protection class IP20
Llmf tm21 L80B10 @25°C 50.000h
Length 1164.0mm
Casing colour black
No. of switches 50000pcs
Impact resistance IK02
Work environment indoor use



Zennor is an LED modular light fixture, where different lengths can be used to achieve different power and light output. LED module requires a separate power supply unit or housing with built-in power supply. Illuminate your world with LED House professionals - check out our project portfolio here!

Accessory Quick straight line splicing accessories silver

Product code 20461



En62471 1
In package 1pc
Casing colour silver
Casing material aluminium
Warranty 3 years