


Ceiling light Koline 1200 black 230V 20W 2400lm 105° IP20 840

Product code 17275

Supply voltage 230V
 Power factor 0.90
 Output 20W
 Luminous flux 2400lumens
 Luminaire's efficiency lm79 120W
 Correlated colour temperature pure white 4000K
 Lens angle 105
 Cri 80
 Protection class IP20
 Lifespan 50000h
 Height 72.8mm
 Width 50.0mm
 Length 1200.0mm
 Weight 1500g
 In package 1pc
 In box 9pcs
 Casing colour black
 No. of switches 30000pcs
 Work environment indoor use
 Operation temperature -20 ~40°C
 Certificates CE
 Warranty 5 years




An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from [the LED house product range!](#)

Ceiling light Koline 1200 black 230V 40W 4800lm 105° IP20 840

Product code 17273

Supply voltage 230V
 Power factor 0.90
 Output 40W
 Luminous flux 4800lumens
 Luminaire's efficiency lm79 120W
 Correlated colour temperature pure white 4000K
 Lens angle 105
 Cri 80
 Protection class IP20
 Lifespan 50000h
 Height 72.8mm
 Width 50.0mm
 Length 1200.0mm
 Weight 1500g
 In package 1pc
 In box 9pcs
 Casing colour black
 No. of switches 30000pcs
 Work environment indoor use
 Operation temperature -20 ~45°C
 Certificates CE
 Warranty 5 years



An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from [the LED house product range!](#)

Ceiling light Koline 1200 white 230V 20W 2600lm 105° IP20 840

Product code 17276

Supply voltage 230V
Power factor 0.90
Output 20W
Luminous flux 2600lumens
Luminaire's efficiency lm79 130W
Correlated colour temperature pure
white 4000K
Lens angle 105
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1550g
In package 1pc
In box 9pcs
Casing colour white
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20° - +40°C
Certificates CE
Warranty 5 years



An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from [the LED house product range!](#)

Ceiling light Koline 1200 white 230V 40W 5200lm 105° IP20 840

Product code 17274

Supply voltage 230V
Power factor 0.90
Output 40W
Luminous flux 5200lumens
Luminaire's efficiency lm79 130W
Correlated colour temperature pure white 4000K
Lens angle 105
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1550g
In package 1pc
In box 9pcs
Casing colour white
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years



An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from [the LED house product range!](#)

Ceiling light Koline K2 1200 black 230V 20W 2600lm CRI80 110° IP20 3000K, 4000K, 6500K WW/DW/CW

Product code 18117

Supply voltage 230V
Power factor 0.90
Output 20W
Luminous flux 2600lumens
Luminaire's efficiency lm79 130W
Correlated colour temperature
WW/DW/CW 3000K, 4000K, 6500K
Lens angle 110
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1500g
In package 1pc
In box 9pcs
Casing colour black
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20 ~40°C
Certificates CE
Warranty 5 years

An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from [the LED house product range!](#)



Ceiling light Koline K2 1200 black 230V 40W 5200lm CRI80 110° IP20 3000K, 4000K, 6500K WW/DW/CW

Product code 18119

Supply voltage 230V
 Power factor 0.90
 Output 40W
 Luminous flux 5200lumens
 Luminaire's efficiency lm79 130W
 Correlated colour temperature
 WW/DW/CW 3000K, 4000K, 6500K
 Lens angle 110
 Cri 80
 Protection class IP20
 Lifespan 50000h
 Height 72.8mm
 Width 50.0mm
 Length 1200.0mm
 Weight 1500g
 In package 1pc
 In box 9pcs
 Casing colour black
 No. of switches 30000pcs
 Work environment indoor use
 Operation temperature -20 ~45°C
 Certificates CE
 Warranty 5 years



An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from [the LED house product range!](#)

Ceiling light Koline K2 1200 UGR<19 black 230V 30W 3600lm 60° IP20 840

Product code 18122

Supply voltage 230V
 Power factor 0.90
 Output 30W
 Luminous flux 3600lumens
 Luminaire's efficiency lm79 120W
 Correlated colour temperature pure white 4000K
 Lens angle 60
 Cri 80
 Protection class IP20
 Lifespan 50000h
 Height 72.8mm
 Width 50.0mm
 Length 1200.0mm
 Weight 1500g
 In package 1pc
 In box 9pcs
 Casing colour black
 No. of switches 30000pcs
 Work environment indoor use
 Operation temperature -20 ~45°C
 Certificates CE
 Warranty 5 years



An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from [the LED house product range!](#)

Ceiling light Koline K2 1200 UGR<19 white 230V 30W 3600lm CRI80 60° IP20 3000K, 4000K, 6500K WW/DW/CW

Product code 18121

Supply voltage 230V
Power factor 0.90
Output 30W
Luminous flux 3600lumens
Luminaire's efficiency lm79 120W
Correlated colour temperature
WW/DW/CW 3000K, 4000K, 6500K
Lens angle 60
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1550g
In package 1pc
In box 9pcs
Casing colour white
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years



An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from [the LED house product range!](#)

Ceiling light Koline K2 1200 white 230V 20W 2600lm CRI80 110° IP20 3000K, 4000K, 6500K WW/DW/CW

Product code 18118

Supply voltage 230V
Power factor 0.90
Output 20W
Luminous flux 2600lumens
Luminaire's efficiency lm79 130W
Correlated colour temperature
WW/DW/CW 3000K, 4000K, 6500K
Lens angle 110
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1550g
In package 1pc
In box 9pcs
Casing colour white
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20° - +40°C
Certificates CE
Warranty 5 years



An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from [the LED house product range!](#)

Ceiling light Koline K2 1200 white 230V 40W 5200lm CRI80 110° IP20 3000K, 4000K, 6500K WW/DW/CW

Product code 18120

Supply voltage 230V
Power factor 0.90
Output 40W
Luminous flux 5200lumens
Luminaire's efficiency lm79 130W
Correlated colour temperature
WW/DW/CW 3000K, 4000K, 6500K
Lens angle 110
Cri 80
Protection class IP20
Lifespan 50000h
Height 72.8mm
Width 50.0mm
Length 1200.0mm
Weight 1550g
In package 1pc
In box 9pcs
Casing colour white
No. of switches 30000pcs
Work environment indoor use
Operation temperature -20 ~45°C
Certificates CE
Warranty 5 years




An evenly distributed light light, which can be installed both on the ceiling and suspended from the ceiling. An ideal luminaire for above desks! This luminaire is suitable for indoor use only, protection class IP20. LED lights provide clear and sharp light, which is ideal for lighting shops and other commercial spaces. Improve the quality of light in your everyday life and choose a top-notch lighting solution from [the LED house product range!](#)

Ceiling light LED House Dallas 1500 CCT black 55W 6000lm CRI90 60° IP20 PUSH 3000K + 4000K warm + day white

Product code 17128 PUSH dimmable

Brand LED House
Dimmable PUSH
Output 55W
Luminous flux 6000lumens
Luminaire's efficiency lm79 109W
Correlated colour temperature warm
+ day white 3000K + 4000K
Lens angle 60
Source of light [REVAL BULB](#)
Cri 90
Protection class IP20
Lifespan 50000h
Llmf tm21 L80B50 @25°C 50.000h
Height 78.0mm
Width 58.0mm
Length 1500.0mm
Casing colour black
Casing material aluminum
Polishing matt
Power supply [LTECH](#)
Work environment indoor use
Warranty 5 years

Adjustable colour temperature and dimmable office light. Ideal desk lamp for work, where you can choose the brightness and suitable light temperature yourself. The luminaire has a prismatic diffuser, which makes working in this light enjoyable and does not strain the eyes. The luminaire is suspended from the ceiling with two cables, and the height of the luminaire can be adjusted. Light distribution is upwards and downwards, and when the colour temperature is changed, it changes both upwards and downwards. Facing downwards is a 3000K LED strip 45W and a 4000K LED strip 45W. Facing upwards is a 3000K + 4000K LED strip 23W. LED strip CRI90. Luminaire control with two buttons located on the housing. The luminaire is manufactured in Estonia! Improve the quality of light in your everyday life and choose a top-notch lighting solution from [the LED house product range!](#)



LED luminaire LSLG 1200 UGR white 230V 40W 4800lm 65° IP20 842

Product code 16308

Supply voltage 230V
 Output 40W
 Luminous flux 4800lumens
 Luminaire's efficiency lm79 120W
 Correlated colour temperature pure white 4200K
 Lens angle 65
 Source of light SANAN LED
 Cri 80
 Ugr 19
 Protection class IP20
 Lifespan 50000h
 Llmf tm21 L70B50 @25°C 50.000h
 Height 70.0mm
 Width 50.0mm
 Length 1200.0mm
 Weight 1850g
 Package weight 2000g
 In package 1pc
 In box 9pcs
 Casing colour white
 Casing material aluminum
 Polishing matt
 No. of switches 30000pcs
 Power supply [BOKE](#)
 Work environment indoor use
 Certificates CE
 Warranty 5 years




Linear workplace luminaire with low UGR value. This IP20-rated linear luminaire is an ideal choice for home or office environments, providing daylight illumination at a temperature of 4200K. The luminaire comes with a suspension kit. Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

LED luminaire LSLG 1500 UGR white 230V 50W 6000lm 65° IP20 842

Product code 16307

Supply voltage 230V
 Output 50W
 Luminous flux 6000lumens
 Luminaire's efficiency lm79 120W
 Correlated colour temperature pure white 4200K
 Lens angle 65
 Source of light SANAN LED
 Cri 80
 Ugr 19
 Protection class IP20
 Lifespan 50000h
 Llmf tm21 L70B50 @25°C 50.000h
 Height 70.0mm
 Width 50.0mm
 Length 1500.0mm
 Weight 2200g
 Package weight 2400g
 In package 1pc
 In box 9pcs
 Casing colour white
 Casing material aluminum
 Polishing matt
 No. of switches 30000pcs
 Power supply [BOKE](#)
 Work environment indoor use
 Certificates CE
 Warranty 5 years



Linear workplace luminaire with low UGR value. This IP20-rated linear luminaire is an ideal choice for home or office environments, providing daylight illumination at a temperature of 4200K. The luminaire comes with a suspension kit. Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

LED luminaire PROLUMEN Barrett 1200 recessed white 230V 36W 3100lm 75° IP20 DALI 940

Product code 17004 DALI dimmable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Dimmable DALI
 Output 36W
 Luminous flux 3100lumens
 Luminaire's efficiency lm79 86W
 Correlated colour temperature pure white 4000K
 Lens angle 75
 Cri 90
 Ugr 22
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Llmf tm21 L70B50 @25°C 50.000h
 Height 76.0mm
 Width 57.0mm
 Length 1212.0mm
 In box 6pcs
 Casing colour white
 Casing material aluminum
 Polishing matt
 Impact resistance IK06
 Work environment indoor use
 Certificates CE
 Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - [check out our portfolio of projects here!!](#)

LED luminaire PROLUMEN Barrett 1200 black 230V 36W 3350lm 110° IP20 DALI 930

Product code 16970 DALI dimmable

Brand [PROLUMEN](#)
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 36W
Luminous flux 3350lumens
Luminaire's efficiency lm79 93W
Correlated colour temperature warm white 3000K
Lens angle 110
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L70B50 @25°C 50.000h
Height 76.0mm
Width 57.0mm
Length 1212.0mm
In box 6pcs
Casing colour black
Casing material aluminum
Polishing matt
Power supply [BOKE](#)
Impact resistance IK06
Work environment indoor use
Certificates CE
Warranty 5 years



Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - [check out our portfolio of projects here!!](#)

LED luminaire PROLUMEN Barrett 1200 UP/DOWN white 230V 36W 4100lm 110° IP20 DALI 940

Product code 16992 DALI dimmable

Brand [PROLUMEN](#)

Supply voltage 230V

Power factor 0.90

Dimmable DALI

Output 36W

Luminous flux 4100lumens

Luminaire's efficiency lm79 114W

Correlated colour temperature pure white 4000K

Lens angle 110

Cri 90

Sdcm - macadam ellipses 6

Protection class IP20

Lifespan 50000h

Llmf tm21 L70B50 @25°C 50.000h

Height 76.0mm

Width 57.0mm

Length 1212.0mm

In box 6pcs

Casing colour white

Casing material aluminum


Polishing matt

Impact resistance IK06

Work environment indoor use

Certificates CE

Warranty 5 years



Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments.

There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - [check out our portfolio of projects here!!](#)

LED luminaire PROLUMEN Barrett 1200 white 230V 36W 3100lm CRI90 110° IP20 DALI 3000K, 4000K, 5700K WW/DW/CW

Product code 17022 DALI dimmable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Dimmable DALI
 Output 36W
 Luminous flux 3100lumens
 Luminaire's efficiency lm79 86W
 Correlated colour temperature
 WW/DW/CW 3000K, 4000K, 5700K
 Lens angle 110
 Cri 90
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Llmf tm21 L70B50 @25°C 50.000h
 Height 76.0mm
 Width 57.0mm
 Length 1212.0mm
 In box 6pcs
 Casing colour white
 Casing material aluminum
 Polishing matt
 Impact resistance IK06
 Work environment indoor use
 Certificates CE
 Warranty 5 years



Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - [check out our portfolio of projects here!!](#)

LED luminaire PROLUMEN Barrett 1500 black 230V 45W 4673lm CRI90 65° IP20 3000K, 4000K, 5700K WW/DW/CW

Product code 16477

Brand [PROLUMEN](#)

Supply voltage 230V

Power factor 0.90

Output 45W

Luminous flux 4673lumens

Luminaire's efficiency lm79 104W

Correlated colour temperature

WW/DW/CW 3000K, 4000K, 5700K

Lens angle 65

Cri 90

Ugr 19

Sdcm - macadam ellipses 6

Protection class IP20

Lifespan 50000h

Height 76.0mm

Width 57.0mm

Length 1512.0mm

In box 6pcs

Casing colour black


Casing material aluminum

Work environment indoor use

Operation temperature -20 ~ 45°C

Certificates CE

Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments.

There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - [check out our portfolio of projects here!!](#)

LED luminaire PROLUMEN Barrett 1500 UGR19 UP/DOWN white 230V 60W 6000lm 65° IP20 930

Product code 18070

Brand [PROLUMEN](#)
Supply voltage 230V
Power factor 0.90
Output 60W
Luminous flux 6000lumens
Luminaire's efficiency lm79 100W
Correlated colour temperature warm
white 3000K
Lens angle 65
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 76.0mm
Width 57.0mm
Length 1512.0mm
In box 6pcs
Casing colour white
Casing material aluminum
Power supply [BOKE](#)
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - [check out our portfolio of projects here!!](#)

LED luminaire PROLUMEN Barrett 1500 UP/DOWN black 230V 60W 5300lm 65° IP20 DALI 930

Product code 17043 DALI dimmable

Brand [PROLUMEN](#)
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 60W
Luminous flux 5300lumens
Luminaire's efficiency lm79 88W
Correlated colour temperature warm
white 3000K
Lens angle 65
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 76.0mm
Width 57.0mm
Length 1512.0mm
In box 6pcs
Casing colour black
Casing material aluminum
Power supply [BOKE](#)
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - [check out our portfolio of projects here!!](#)

LED luminaire PROLUMEN Barrett 1500 UP/DOWN V black 230V 60W 5400lm 65° IP20 930

Product code 16511

Brand [PROLUMEN](#)
Supply voltage 230V
Power factor 0.90
Output 60W
Luminous flux 5400lumens
Luminaire's efficiency lm79 90W
Correlated colour temperature warm
white 3000K
Lens angle 65
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 76.0mm
Width 57.0mm
Length 1512.0mm
In box 6pcs
Casing colour black
Casing material aluminum
Power supply [BOKE](#)
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years



Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - [check out our portfolio of projects here!!](#)

LED luminaire PROLUMEN Barrett 1500 white 230V 45W 4573lm CRI90 110° IP20 DALI 3000K, 4000K, 5700K WW/DW/CW

Product code 17016 DALI dimmable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Dimmable DALI
 Output 45W
 Luminous flux 4573lumens
 Luminaire's efficiency lm79 102W
 Correlated colour temperature
 WW/DW/CW 3000K, 4000K, 5700K
 Lens angle 110
 Cri 90
 Ugr 19
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Height 76.0mm
 Width 57.0mm
 Length 1512.0mm
 In box 6pcs
 Casing colour white
 Casing material aluminum
 Power supply [BOKE](#)
 Work environment indoor use
 Operation temperature -20 ~ 45°C
 Certificates CE
 Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - [check out our portfolio of projects here!!](#)

LED luminaire PROLUMEN Barrett 600 black 230V 17W 1500lm 75° IP20 930

Product code 16672

Brand [PROLUMEN](#)
Supply voltage 230V
Power factor 0.90
Output 17W
Luminous flux 1500lumens
Luminaire's efficiency lm79 88W
Correlated colour temperature warm white 3000K
Lens angle 75
Cri 90
Ugr 19
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 76.0mm
Width 57.0mm
Length 602.0mm
Weight 1700g
Package weight 2133g
In box 6pcs
Casing colour black
Casing material aluminum
Power supply OSRAM
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE
Warranty 5 years



Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - [check out our portfolio of projects here!!](#)

LED luminaire PROLUMEN Barrett 600 white 230V 17W 1500lm 75° IP20 DALI 930

Product code 16971 DALI dimmable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Dimmable DALI
 Output 17W
 Luminous flux 1500lumens
 Luminaire's efficiency lm79 88W
 Correlated colour temperature warm
 white 3000K
 Lens angle 75
 Cri 90
 Ugr 19
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Height 76.0mm
 Width 57.0mm
 Length 602.0mm
 Weight 1700g
 Package weight 2133g
 In box 6pcs
 Casing colour white
 Casing material aluminum
 Power supply [BOKE](#)
 Work environment indoor use
 Operation temperature -20 ~ 45°C
 Certificates CE
 Warranty 5 years



Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - [check out our portfolio of projects here!!](#)

LED luminaire PROLUMEN Barrett 600 white 230V 17W 1500lm CRI90 110° IP20 DALI 3000K, 4000K, 5700K WW/DW/CW

Product code 17017 DALI dimmable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Dimmable DALI
 Output 17W
 Luminous flux 1500lumens
 Luminaire's efficiency lm79 88W
 Correlated colour temperature
 WW/DW/CW 3000K, 4000K, 5700K
 Lens angle 110
 Cri 90
 Ugr 19
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Height 76.0mm
 Width 57.0mm
 Length 602.0mm
 In box 6pcs
 Casing colour white
 Casing material aluminum
 Power supply [BOKE](#)
 Work environment indoor use
 Operation temperature -20 ~ 45°C
 Certificates CE
 Warranty 5 years



Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - [check out our portfolio of projects here!!](#)

LED luminaire PROLUMEN Barrett A 1200 white 230V 36W 3750lm 75° IP20 DALI 930

Product code 17368 DALI dimmable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Dimmable DALI
 Output 36W
 Luminous flux 3750lumens
 Luminaire's efficiency lm79 104W
 Correlated colour temperature warm white 3000K
 Lens angle 75
 Cri 90
 Ugr 19
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Height 76.0mm
 Width 57.0mm
 Length 1212.0mm
 Weight 1700g
 Package weight 2133g
 In box 6pcs
 Casing colour white
 Casing material aluminum
 Power supply [BOKE](#)
 Impact resistance IK06
 Work environment indoor use
 Operation temperature -20 ~ 45°C
 Certificates CE
 Warranty 5 years




Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - [check out our portfolio of projects here!!](#)

LED luminaire PROLUMEN Barrett A 1500 white 230V 45W 3750lm 75° IP20 DALI 930

Product code 17369 DALI dimmable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Dimmable DALI
 Output 45W
 Luminous flux 3750lumens
 Luminaire's efficiency lm79 83W
 Correlated colour temperature warm
 white 3000K
 Lens angle 75
 Cri 90
 Ugr 19
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Height 76.0mm
 Width 57.0mm
 Length 1512.0mm
 Weight 1700g
 Package weight 2133g
 In box 6pcs
 Casing colour white
 Casing material aluminum
 Power supply [BOKE](#)
 Impact resistance IK06
 Work environment indoor use
 Operation temperature -20 ~ 45°C
 Certificates CE
 Warranty 5 years



Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - [check out our portfolio of projects here!!](#)

LED luminaire PROLUMEN Barrett A 600 up-down black 230V 22W 1950lm CRI90 110° IP20 DALI 3000K, 4000K, 5700K WW/DW/CW

Product code 17352 DALI dimmable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Dimmable DALI
 Output 22W
 Luminous flux 1950lumens
 Luminaire's efficiency lm79 89W
 Correlated colour temperature
 WW/DW/CW 3000K, 4000K, 5700K
 Lens angle 110
 Cri 90
 Ugr 19
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Height 76.0mm
 Width 57.0mm
 Length 602.0mm
 Weight 1700g
 Package weight 2133g
 In box 6pcs
 Casing colour black
 Casing material aluminum
 Impact resistance IK06
 Work environment indoor use
 Operation temperature -20 ~ 45°C
 Certificates CE
 Warranty 5 years



Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)! This luminaire with IP20 protection class is an ideal choice for home or office environments. There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs. This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K). Illuminate your world with LED House professionals - [check out our portfolio of projects here!!](#)

LED luminaire PROLUMEN Bianca S1 1200 white 230V 39W 4742lm 120° IP44 840

Product code 17442

Brand [PROLUMEN](#)
Supply voltage 230V
Power factor 0.90
Output 39W
Luminous flux 4742lumens
Luminaire's efficiency lm79 122W
Correlated colour temperature pure white 4000K
Lens angle 120
Source of light OSRAM LED
Cri 80
Sdcm - macadam ellipses 5
Protection class IP44
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 52.0mm
Width 152.0mm
Length 1200.0mm
Casing colour white
Casing material polycarbonate
Polishing matt
Power supply [BOKE](#)
Work environment indoor use
Operation temperature -20° - +45°C
Warranty 5 years



Bianca S1 linear light. When used properly, the light is energy-efficient, environmentally friendly, and has a very long lifespan (50,000 hours). Illuminate your world with the help of LED House professionals - check out our project portfolio here!

LED luminaire PROLUMEN Bianca S1 1200 white 230V 39W 5400lm 120° IP44 DALI 840

Product code 17448 DALI dimmable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Dimmable DALI
 Output 39W
 Luminous flux 5400lumens
 Luminaire's efficiency lm79 138W
 Correlated colour temperature pure white 4000K
 Lens angle 120
 Source of light OSRAM LED
 Cri 80
 Sdcm - macadam ellipses 5
 Protection class IP44
 Lifespan 50000h
 Llmf tm21 L80B10 @25°C 50.000h
 Height 52.0mm
 Width 152.0mm
 Length 1200.0mm
 Casing colour white
 Casing material polycarbonate
 Polishing matt
 Power supply [BOKE](#)
 Work environment indoor use
 Operation temperature -20° - +45°C
 Warranty 5 years



Bianca S1 linear light. When used properly, the light is energy-efficient, environmentally friendly, and has a very long lifespan (50,000 hours). Illuminate your world with the help of LED House professionals - check out our project portfolio here!

Ceiling light PROLUMEN Clara 1200 V white 40W 4400lm CRI90 120° IP44 0-10V 3000K, 4000K, 5700K WW/DW/CW

Product code 17351 0-10V dimmable

Brand [PROLUMEN](#)
Power factor 0.90
Dimmable 0-10V
Output 40W
Luminous flux 4400lumens
Luminaire's efficiency lm79 110W
Correlated colour temperature
WW/DW/CW 3000K, 4000K, 5700K
Lens angle 120
Cri 90
Sdcm - macadam ellipses 6
Protection class IP44
Lifespan 50000h
Height 80.0mm
Width 208.0mm
Length 1200.0mm
In box 12pcs
Casing colour white
Casing material aluminum
Polishing matt
Impact resistance IK08
Work environment indoor use
Certificates CE
Warranty 5 years



High-quality PROLUMEN ship light, possible to install both on the surface and hanging. The light temperature can be set by yourself. There are buttons on the light that allow you to choose between 3000K (warm white), 4000K (daylight), or 5700K cool white light. A high colour rendering index CRI90 does not distort the true colours of objects under the light beam. Protection class IP44 means that the luminaire can also be used in damp conditions. If you haven't found the perfect light fixture from our product range yet, then browse through the [PROLUMEN catalogue](#) as well!

**Ceiling light PROLUMEN Clara 1200 white 230V 20W 2200lm
CRI90 120° IP44 DALI 3000K, 4000K, 5700K WW/DW/CW**

Product code 17353 DALI dimmable

Brand [PROLUMEN](#)

Supply voltage 230V

Power factor 0.90

Dimmable DALI

Output 20W

Luminous flux 2200lumens

Luminaire's efficiency lm79 110W

Correlated colour temperature

WW/DW/CW 3000K, 4000K, 5700K

Lens angle 120

Cri 90

Sdcm - macadam ellipses 6

Protection class IP44

Lifespan 50000h

Height 80.0mm

Width 207.0mm

Length 1200.0mm

In package 1pc

In box 6pcs

Casing colour white

Casing material aluminum

Polishing matt

Impact resistance IK08

Work environment indoor use

Operation temperature -20 ~40°C

Certificates CE

Warranty 5 years




High-quality PROLUMEN ship light, possible to install both on the surface and hanging. The light temperature can be set by yourself. There are buttons on the light that allow you to choose between 3000K (warm white), 4000K (daylight), or 5700K cool white light. A high colour rendering index CRI90 does not distort the true colours of objects under the light beam.

Protection class IP44 means that the luminaire can also be used in damp conditions. If you haven't found the perfect light fixture from our product range yet, then browse through the [PROLUMEN catalogue](#) as well!

LED luminaire PROLUMEN DB158B 1500 Linkable, Opal diffuser white 230V 40W 4000lm CRI80 110° IP20 3000K, 4000K, 5700K WW/DW/CW

Product code 18071

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Output 40W
 Luminous flux 4000lumens
 Luminaire's efficiency lm79 100W
 Correlated colour temperature WW/DW/CW 3000K, 4000K, 5700K
 Lens angle 110
 Cri 80
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Llmf tm21 L70B50 @25°C 50.000h
 Height 70.0mm
 Width 59.0mm
 Length 1500.0mm
 Weight 1960g
 In box 6pcs
 Casing colour white
 Casing material aluminum
 Polishing matt
 Power supply [LIFUD](#)
 Impact resistance IK06
 Work environment indoor use
 Certificates CE
 Warranty 5 years



LED luminaire PROLUMEN DB66A 1200 white 230V 36W 3800lm CRI80 120° IP20 3000K, 4000K, 5700K WW/DW/CW

Product code 16028

Brand [PROLUMEN](#)
Supply voltage 230V
Power factor 0.90
Output 36W
Luminous flux 3800lumens
Luminaire's efficiency lm79 106W
Correlated colour temperature
WW/DW/CW 3000K, 4000K, 5700K
Lens angle 120
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Lmf tm21 L70B50 @25°C 50.000h
Height 75.0mm
Width 56.0mm
Length 1204.0mm
Weight 2750g
In box 6pcs
Casing colour white
Casing material aluminum
Polishing matt
Power supply [LIFUD](#)
Impact resistance IK06
Work environment indoor use
Certificates CE
Warranty 5 years

Perfect for office or workplace lighting. Some models also feature ship lighting. The PROLUMEN DB66A series offers versatile options for lighting projects. These high-quality luminaires with uniform light distribution allow for customizable lighting according to preference. DB66A provides powerful illumination that meets high standards. Available in various wattages ranging from 36W to 60W and brightness from 3800lm to 6200lm, ensuring adequate lighting in different spaces and environments. The luminaires are equipped with high-quality LEDs, providing stable light and a high color rendering index (CRI90), which helps maintain the natural color of objects. Additionally, you can choose from different color temperatures - 3000K, 4000K, and 5700K, from warm white to cool white light. PROLUMEN DB66A luminaires are ideal for both indoor and commercial buildings. In addition, UP/DOWN versions are available, providing light both upwards and downwards, ensuring uniform illumination of the space. All PROLUMEN DB66A luminaires come with IP20 protection class, ensuring their durability and suitability for various indoor environments. Additionally, DALI versions are available, allowing precise control of lighting as needed. Mounting cables are not included, but you can find all the necessary accessories from LED house in the [accessories category](#)!



LED luminaire PROLUMEN DB66A 1200 white 230V 36W 3800lm CRI90 120° IP20 DALI 3000K, 4000K, 5700K WW/DW/CW

Product code 16180 DALI dimmable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Dimmable DALI
 Output 36W
 Luminous flux 3800lumens
 Luminaire's efficiency lm79 106W
 Correlated colour temperature
 WW/DW/CW 3000K, 4000K, 5700K
 Lens angle 120
 Cri 90
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Lmf tm21 L70B50 @25°C 50.000h
 Height 75.0mm
 Width 56.0mm
 Length 1204.0mm
 Weight 2750g
 In box 6pcs
 Casing colour white
 Casing material aluminum
 Polishing matt
 Power supply [LIFUD](#)
 Impact resistance IK06
 Work environment indoor use
 Certificates CE
 Warranty 5 years

Perfect for office or workplace lighting. Some models also feature ship lighting. The PROLUMEN DB66A series offers versatile options for lighting projects. These high-quality luminaires with uniform light distribution allow for customizable lighting according to preference. DB66A provides powerful illumination that meets high standards. Available in various wattages ranging from 36W to 60W and brightness from 3800lm to 6200lm, ensuring adequate lighting in different spaces and environments. The luminaires are equipped with high-quality LEDs, providing stable light and a high color rendering index (CRI90), which helps maintain the natural color of objects. Additionally, you can choose from different color temperatures - 3000K, 4000K, and 5700K, from warm white to cool white light. PROLUMEN DB66A luminaires are ideal for both indoor and commercial buildings. In addition, UP/DOWN versions are available, providing light both upwards and downwards, ensuring uniform illumination of the space. All PROLUMEN DB66A luminaires come with IP20 protection class, ensuring their durability and suitability for various indoor environments. Additionally, DALI versions are available, allowing precise control of lighting as needed. Mounting cables are not included, but you can find all the necessary accessories from LED house in the [accessories category](#)!



LED luminaire PROLUMEN DB66A 1500 white 230V 42W 4500lm CRI80 120° IP20 3000K, 4000K, 5700K WW/DW/CW

Product code 16029

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Output 42W
 Luminous flux 4500lumens
 Luminaire's efficiency lm79 107W
 Correlated colour temperature
 WW/DW/CW 3000K, 4000K, 5700K
 Lens angle 120
 Cri 80
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Llmf tm21 L70B50 @25°C 50.000h
 Height 75.0mm
 Width 56.0mm
 Length 1504.0mm
 In box 6pcs
 Casing colour white
 Casing material aluminum
 Polishing matt
 Impact resistance IK06
 Work environment indoor use
 Certificates CE
 Warranty 5 years

Perfect for office or workplace lighting. Some models also feature ship lighting. The PROLUMEN DB66A series offers versatile options for lighting projects. These high-quality luminaires with uniform light distribution allow for customizable lighting according to preference. DB66A provides powerful illumination that meets high standards. Available in various wattages ranging from 36W to 60W and brightness from 3800lm to 6200lm, ensuring adequate lighting in different spaces and environments. The luminaires are equipped with high-quality LEDs, providing stable light and a high color rendering index (CRI90), which helps maintain the natural color of objects. Additionally, you can choose from different color temperatures - 3000K, 4000K, and 5700K, from warm white to cool white light. PROLUMEN DB66A luminaires are ideal for both indoor and commercial buildings. In addition, UP/DOWN versions are available, providing light both upwards and downwards, ensuring uniform illumination of the space. All PROLUMEN DB66A luminaires come with IP20 protection class, ensuring their durability and suitability for various indoor environments. Additionally, DALI versions are available, allowing precise control of lighting as needed. Mounting cables are not included, but you can find all the necessary accessories from LED house in the [accessories category](#)!



LED luminaire PROLUMEN DB74 1500 Bianca white 230V 50W 4900lm 120° IP44 DALI 840

Product code 16988 DALI dimmable

Brand [PROLUMEN](#)
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 50W
Luminous flux 4900lumens
Luminaire's efficiency lm79 98W
Correlated colour temperature pure white 4000K
Lens angle 120
Cri 80
Sdcm - macadam ellipses 6
Protection class IP44
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 63.0mm
Width 171.0mm
Length 1495.0mm
Weight 3520g
Package weight 4150g
In package 1pc
In box 4pcs
Casing colour white
Casing material polycarbonate
Polishing matt
Power supply [BOKE](#)
Work environment indoor use
Operation temperature -20° +40°C
Certificates CE, D, F
Warranty 5 years



High-quality, dimmable ceiling light. DALI Dim technology allows adjusting the light according to preference. 4000K LED lights provide clear and sharp illumination, perfect for lighting stores and other commercial spaces. The high color rendering index CRI90 ensures the accuracy of colors under the light beam. IP44 protection class means the luminaire can be used even in damp conditions. Illuminate your world with the help of LED House professionals - [check out our portfolio of projects here!!](#)

LED luminaire PROLUMEN DB74 600 Bianca white 230V 17W 1800lm 120° IP44 DALI 940

Product code 16987 DALI dimmable

Brand [PROLUMEN](#)
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 17W
Luminous flux 1800lumens
Luminaire's efficiency lm79 106W
Correlated colour temperature pure white 4000K
Lens angle 120
Cri 90
Sdcm - macadam ellipses 6
Protection class IP44
Lifespan 50000h
Llmf tm21 L80B10 @25°C 50.000h
Height 63.0mm
Width 171.0mm
Length 595.0mm
Weight 1550g
Package weight 1800g
In package 1pc
In box 12pcs
Casing colour white
Casing material polycarbonate
Polishing matt
Power supply [BOKE](#)
Work environment indoor use
Operation temperature -20° +40°C
Certificates CE, D, F
Warranty 5 years





High-quality, dimmable ceiling light. DALI Dim technology allows adjusting the light according to preference. 4000K LED lights provide clear and sharp illumination, perfect for lighting stores and other commercial spaces. The high color rendering index CRI90 ensures the accuracy of colors under the light beam. IP44 protection class means the luminaire can be used even in damp conditions. Illuminate your world with the help of LED House professionals - [check out our portfolio of projects here!!](#)

Linear Light PROLUMEN Delia UGR 600 black 230V 20W 2000lm CRI90 100° IP20 3000K, 4000K, 5700K WW/DW/CW

Product code 15206

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Output 20W
 Luminous flux 2000lumens
 Luminaire's efficiency lm79 100W
 Correlated colour temperature WW/DW/CW 3000K, 4000K, 5700K
 Lens angle 100
 Cri 90
 Ugr 18
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Height 70.0mm
 Width 60.0mm
 Length 604.0mm
 Weight 1150g
 Package weight 1650g
 In package 1pc
 In box 12pcs
 Casing colour black
 Casing material aluminum
 Work environment indoor use
 Certificates CE, RoHS
 Warranty 5 years





Black body and square design. Elegant and functional, this minimalist pendant light is an excellent choice for those who appreciate simplicity and modernity in their home decor. With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000h). This luminaire has an ideal color rendering index for workspaces and offices. On some models, the light color is changeable: 3000K, 4000K, 6000K. The luminaire can be successfully installed both surface-mounted and suspended. In both cases, the result is guaranteed to be good. [Hanging cables](#) (2 pcs) must be ordered separately. Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

Linear Light PROLUMEN Delia UGR19 1200 black 230V 40W 4500lm 100° IP40 DALI 840

Product code 15323 DALI dimmable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Dimmable DALI
 Output 40W
 Luminous flux 4500lumens
 Luminaire's efficiency lm79 113W
 Correlated colour temperature pure white 4000K
 Lens angle 100
 Cri 80
 Ugr 18
 Lor 80
 Sdcm - macadam ellipses 6
 Protection class IP40
 Lifespan 50000h
 Llmf tm21 L80B50 @25°C 50.000h
 Height 70.0mm
 Width 60.0mm
 Length 1204.0mm
 Weight 2200g
 Package weight 3000g
 In package 1pc
 In box 12pcs
 Casing colour black
 Casing material aluminum
 Work environment indoor use
 Certificates CE, RoHS
 Warranty 5 years





Black body and square design. Elegant and functional, this minimalist pendant light is an excellent choice for those who appreciate simplicity and modernity in their home decor. With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000h). This luminaire has an ideal color rendering index for workspaces and offices. On some models, the light color is changeable: 3000K, 4000K, 6000K. The luminaire can be successfully installed both surface-mounted and suspended. In both cases, the result is guaranteed to be good. [Hanging cables](#) (2 pcs) must be ordered separately. Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

Linear Light PROLUMEN Delia UGR19 1200 black 230V 40W 4500lm CRI90 100° IP20 3000K, 4000K, 5700K WW/DW/CW

Product code 15026

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Output 40W
 Luminous flux 4500lumens
 Luminaire's efficiency lm79 113W
 Correlated colour temperature WW/DW/CW 3000K, 4000K, 5700K
 Lens angle 100
 Cri 90
 Ugr 18
 Lor 80
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Llmf tm21 L80B50 @25°C 50.000h
 Height 70.0mm
 Width 60.0mm
 Length 1204.0mm
 Weight 2200g
 Package weight 3000g
 In package 1pc
 In box 12pcs
 Casing colour black
 Casing material aluminum
 Work environment indoor use
 Certificates CE, RoHS
 Warranty 5 years



Black body and square design. Elegant and functional, this minimalist pendant light is an excellent choice for those who appreciate simplicity and modernity in their home decor. With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000h). This luminaire has an ideal color rendering index for workspaces and offices. On some models, the light color is changeable: 3000K, 4000K, 6000K. The luminaire can be successfully installed both surface-mounted and suspended. In both cases, the result is guaranteed to be good. [Hanging cables](#) (2 pcs) must be ordered separately. Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

Linear Light PROLUMEN Delia UGR19 1200 black 230V 40W 4500lm CRI90 100° IP20 TRIAC 3000K, 4000K, 5700K WW/DW/CW

Product code 15460 TRIAC dimmable

Brand [PROLUMEN](#)

Supply voltage 230V

Power factor 0.90

Dimmable TRIAC

Output 40W

Luminous flux 4500lumens

Luminaire's efficiency lm79 113W

Correlated colour temperature

WW/DW/CW 3000K, 4000K, 5700K

Lens angle 100

Cri 90

Ugr 18

Lor 80

Sdcm - macadam ellipses 6

Protection class IP20

Lifespan 50000h

Llmf tm21 L80B50 @25°C 50.000h

Height 70.0mm

Width 60.0mm

Length 1204.0mm

Weight 2200g

Package weight 3000g

In package 1pc

In box 12pcs


Casing colour black

Casing material aluminum

Work environment indoor use

Certificates CE, RoHS

Warranty 5 years




Black body and square design. Elegant and functional, this minimalist pendant light is an excellent choice for those who appreciate simplicity and modernity in their home decor. With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000h). This luminaire has an ideal color rendering index for workspaces and offices. On some models, the light color is changeable: 3000K, 4000K, 6000K. The luminaire can be successfully installed both surface-mounted and suspended. In both cases, the result is guaranteed to be good. [Hanging cables](#) (2 pcs) must be ordered separately. Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

Linear Light PROLUMEN Delia UGR19 1200 white 230V 40W 4500lm CRI80 100° IP20 3000K, 4000K, 5700K WW/DW/CW

Product code 15535

Brand [PROLUMEN](#)
Supply voltage 230V
Power factor 0.90
Output 40W
Luminous flux 4500lumens
Luminaire's efficiency lm79 113W
Correlated colour temperature
WW/DW/CW 3000K, 4000K, 5700K
Lens angle 100
Cri 80
Ugr 18
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Llmf tm21 L80B50 @25°C 50.000h
Height 70.0mm
Width 60.0mm
Length 1204.0mm
Weight 2200g
Package weight 3000g
In package 1pc
In box 12pcs
Casing colour white
Casing material aluminum
Work environment indoor use
Certificates CE, RoHS
Warranty 5 years



White body and square design. Elegant and functional, this minimalist luminaire is an excellent choice for those who appreciate simplicity and modernity in their home decor. This luminaire can be installed as both a pendant light and surface-mounted. With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000 hours). Some models have adjustable light color: 3000K, 4000K, 6000K. The luminaire can be successfully installed both surface-mounted and suspended. In both cases, good results are guaranteed. [Suspension cables](#) (2 pcs) must be ordered separately. Illuminate your world with the help of LED House professionals - [check out our project portfolio here!](#)

**LED luminaire PROLUMEN Delilah 0,6m white 230V 15W 1400lm
110° IP20 940**

Product code 17051

Brand [PROLUMEN](#)
Supply voltage 230V
Power factor 0.90
Output 15W
Luminous flux 1400lumens
Luminaire's efficiency lm79 93W
Correlated colour temperature pure white 4000K
Lens angle 110
Cri 90
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 29.0mm
Width 62.0mm
Length 615.0mm
Installation opening diameter 607x54mm
In box 12pcs
Casing colour white
Casing material aluminum
Polishing matt
Work environment indoor use
Operation temperature -20 ~ 45°C
Certificates CE, RoHS
Warranty 5 years

Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - [check out our project portfolio here!](#) Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - [check out our project portfolio here!](#)



LED luminaire PROLUMEN Delilah 1,2m white 230V 30W 3100lm

110° IP20 940

Product code 17052

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Output 30W
 Luminous flux 3100lumens
 Luminaire's efficiency lm79 103W
 Correlated colour temperature pure white 4000K
 Lens angle 110
 Cri 90
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Height 29.0mm
 Width 62.0mm
 Length 1208.0mm
 Installation opening diameter 1201x54mm
 In box 6pcs
 Casing colour white
 Casing material aluminum
 Polishing matt
 Work environment indoor use
 Operation temperature -20 ~ 45°C
 Certificates CE, RoHS
 Warranty 5 years

Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - [check out our project portfolio here!](#)



LED luminaire PROLUMEN Delilah 1,5m white 230V 37W 3800lm 110° IP20 940

Product code 17053

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Output 37W
 Luminous flux 3800lumens
 Luminaire's efficiency lm79 103W
 Correlated colour temperature pure white 4000K
 Lens angle 110
 Cri 90
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Height 29.0mm
 Width 62.0mm
 Length 1505.0mm
 Installation opening diameter 1498x54mm
 In box 6pcs
 Casing colour white
 Casing material aluminum
 Polishing matt
 Work environment indoor use
 Operation temperature -20 ~ 45°C
 Certificates CE, RoHS
 Warranty 5 years

Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - [check out our project portfolio here!](#) Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - [check out our project portfolio here!](#)



LED luminaire PROLUMEN Delilah 2,4m white 230V 60W 6200lm

110° IP20 940

Product code 16407

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Output 60W
 Luminous flux 6200lumens
 Luminaire's efficiency lm79 103W
 Correlated colour temperature pure white 4000K
 Lens angle 110
 Cri 90
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Height 29.0mm
 Width 62.0mm
 Length 2395.0mm
 Installation opening diameter 2388x54mm
 In box 6pcs
 Casing colour white
 Casing material aluminum
 Polishing matt
 Work environment indoor use
 Operation temperature -20 ~ 45°C
 Certificates CE, RoHS
 Warranty 5 years

Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - [check out our project portfolio here!](#) Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - [check out our project portfolio here!](#)



LED luminaire PROLUMEN Delilah L-corner 150+150 white 230V 7.5W 650lm 110° IP20 940

Product code 17054

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Output 7.5W
 Luminous flux 650lumens
 Luminaire's efficiency lm79 87W
 Correlated colour temperature pure white 4000K
 Lens angle 110
 Cri 90
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Height 29.0mm
 Width 150.0mm
 Length 150.0mm
 In box 24pcs
 Casing colour white
 Casing material aluminum
 Polishing matt
 Work environment indoor use
 Operation temperature -20 ~ 45°C
 Certificates CE, RoHS
 Warranty 5 years

Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - [check out our project portfolio here!](#)



Ceiling light PROLUMEN Delilah white 230V 45W 4300lm 45° IP20 940

Product code 16793

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Output 45W
 Luminous flux 4300lumens
 Luminaire's efficiency lm79 96W
 Correlated colour temperature pure white 4000K
 Lens angle 45
 Cri 90
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Height 29.0mm
 Width 62.0mm
 Length 1802.0mm
 Package weight 2683g
 In package 1pc
 In box 6pcs
 Casing colour white
 Casing material aluminum
 Work environment indoor use
 Certificates CE, RoHS
 Warranty 5 years

Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - [check out our project portfolio here!](#) Extendable linear recessed luminaire that allows for creating light games according to preference. Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas. The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan. Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90). Illuminate your world with LED House professionals - [check out our project portfolio here!](#)



LED luminaire PROLUMEN Dennis 1200 white 230V 40W 4400lm 120° IP20 840

Product code 15353

Brand [PROLUMEN](#)
Supply voltage 230V
Power factor 0.90
Output 40W
Luminous flux 4400lumens
Luminaire's efficiency lm79 110W
Correlated colour temperature pure
white 4000K
Lens angle 120
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 50000h
Height 64.0mm
Width 71.0mm
Length 1203.0mm
In box 12pcs
Casing colour white
Impact resistance IK08
Work environment indoor use
Certificates CE
Warranty 5 years



A classic luminaire for offices, schools, hotels, corridors, etc. Its minimalist design blends seamlessly into various interiors, whether at home, in the office, or in a business environment. Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

LED luminaire PROLUMEN Dennis 1500 white 230V 58W 5850lm 120° IP20 840

Product code 15628

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Output 58W
 Luminous flux 5850lumens
 Luminaire's efficiency lm79 101W
 Correlated colour temperature pure white 4000K
 Lens angle 120
 Cri 80
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Height 64.0mm
 Width 71.0mm
 Length 1503.0mm
 In box 12pcs
 Casing colour white
 Impact resistance IK08
 Work environment indoor use
 Certificates CE
 Warranty 5 years



A classic luminaire for offices, schools, hotels, corridors, etc. Its minimalist design blends seamlessly into various interiors, whether at home, in the office, or in a business environment. Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

LED luminaire PROLUMEN EMPIRIO B025S 1500 white 230V 75W 12000lm 90° IP40 840

Product code 15018

Brand [PROLUMEN](#)

Supply voltage 230V

Output 75W

Luminous flux 12000lumens

Luminaire's efficiency lm79 160W

Correlated colour temperature pure white 4000K

Lens angle 90

Cri 80

Sdcm - macadam ellipses 3

Protection class IP40

Lifespan 50000h

Llmf tm21 L80B10 @25°C 80.000h

Height 72.0mm

Width 65.0mm

Length 1460.0mm

Casing colour white

Casing material aluminum


Power supply OSRAM

Work environment indoor use

Operation temperature -20°C - +45°C

Certificates CE, RoHS

Warranty 5 years



A ceiling light fixture with uniform light distribution that can be installed either flush-mounted or suspended from the ceiling. An ideal light fixture for above desks! 4000K LED lights provide clear and sharp light, perfect for illuminating stores and other commercial spaces. Option to order linear lights with different lenses and power levels: 30°, 60°, 90°, 120°, 2 x 25°. Improve your everyday lighting quality and choose a top-notch lighting solution from the LED house product range! Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

Ceiling light PROLUMEN Lidya 1100 up-down white 230V 45W 4700lm CRI80 50° IP20 3000K + 4000K warm + day white

Product code 16791

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Output 45W
 Luminous flux 4700lumens
 Luminaire's efficiency lm79 104W
 Correlated colour temperature warm
 + day white 3000K + 4000K
 Lens angle 50
 Cri 80
 Ugr 19
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Height 74.0mm
 Width 236.0mm
 Length 1172.0mm
 Package weight 4800g
 In package 1pc
 In box 2pcs
 Casing colour white
 Casing material aluminum
 Work environment indoor use
 Operation temperature -20° - +40°C
 Certificates CE, RoHS
 Warranty 5 years



Up-down light fixture, ideal for offices and other workspaces. Adjustable light color temperature: 3000K, 4000K. This fixture is suitable for indoor use only, with IP20 protection rating. The light fixture has an ideal color rendering index CRI90 for workspaces and offices. With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000h). Improve the quality of light in your everyday life and choose a top-notch lighting solution from the [LED House product range!](#)

Ceiling light PROLUMEN Lidya 1500 up-down white 230V 60W 5400lm CRI90 50° IP20 3000K + 4000K warm + day white

Product code 16792

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Output 60W
 Luminous flux 5400lumens
 Luminaire's efficiency lm79 90W
 Correlated colour temperature warm
 + day white 3000K + 4000K
 Lens angle 50
 Cri 90
 Ugr 19
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Height 74.0mm
 Width 236.0mm
 Length 1552.0mm
 Package weight 5900g
 In package 1pc
 In box 2pcs
 Casing colour white
 Casing material aluminum
 Work environment indoor use
 Certificates CE, RoHS
 Warranty 5 years



Up-down light fixture, ideal for offices and other workspaces. Adjustable light color temperature: 3000K, 4000K. This fixture is suitable for indoor use only, with IP20 protection rating. The light fixture has an ideal color rendering index CRI90 for workspaces and offices. With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000h). Improve the quality of light in your everyday life and choose a top-notch lighting solution from the [LED House product range!](#)

Linear Light PROLUMEN Linda 66D 1200 with downward light distribution black 230V 28W 3600lm 75° IP20 DALI 830

Product code 17751 DALI dimmable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Dimmable DALI
 Output 28W
 Luminous flux 3600lumens
 Luminaire's efficiency lm79 129W
 Correlated colour temperature warm white 3000K
 Lens angle 75
 Cri 80
 Ugr 19
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Llmf tm21 L70B50 @25°C 50.000h
 Height 75.0mm
 Width 56.0mm
 Length 1204.0mm
 Weight 2750g
 In box 6pcs
 Casing colour black
 Casing material aluminum
 Polishing matt
 Power supply [BOKE](#)
 Impact resistance IK06
 Work environment indoor use
 Operation temperature -20° - +45°C
 Certificates CE
 Warranty 5 years



Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors. Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space. Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Linear Light PROLUMEN Linda 66D 1200 with downward light distribution black 230V 28W 3800lm 75° IP20 DALI 840

Product code 17750 DALI dimmable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Dimmable DALI
 Output 28W
 Luminous flux 3800lumens
 Luminaire's efficiency lm79 136W
 Correlated colour temperature pure white 4000K
 Lens angle 75
 Cri 80
 Ugr 19
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Llmf tm21 L70B50 @25°C 50.000h
 Height 75.0mm
 Width 56.0mm
 Length 1204.0mm
 Weight 2750g
 In box 6pcs
 Casing colour black
 Casing material aluminum
 Polishing matt
 Power supply [BOKE](#)
 Impact resistance IK06
 Work environment indoor use
 Operation temperature -20° - +45°C
 Certificates CE
 Warranty 5 years



Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors. Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space. Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Linear Light PROLUMEN Linda 66D 1200 with light distribution up and down black 230V 40W 5270lm 75° IP20 DALI 830

Product code 17752 DALI dimmable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Dimmable DALI
 Output 40W
 Luminous flux 5270lumens
 Luminaire's efficiency lm79 132W
 Correlated colour temperature warm white 3000K
 Lens angle 75
 Cri 80
 Ugr 19
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Height 75.0mm
 Width 56.0mm
 Length 1204.0mm
 Weight 1700g
 Package weight 2133g
 In box 6pcs
 Casing colour black
 Casing material aluminum
 Power supply [BOKE](#)
 Impact resistance IK06
 Work environment indoor use
 Operation temperature -20° - +45°C
 Certificates CE
 Warranty 5 years



Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors. Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space. Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Linear Light PROLUMEN Linda 66D 1200 with light distribution up and down black 230V 40W 5550lm 75° IP20 DALI 840

Product code 17741 DALI dimmable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Dimmable DALI
 Output 40W
 Luminous flux 5550lumens
 Luminaire's efficiency lm79 139W
 Correlated colour temperature pure white 4000K
 Lens angle 75
 Cri 80
 Ugr 19
 Sdcm - macadam ellipses 6
 Protection class IP20
 Lifespan 50000h
 Height 75.0mm
 Width 56.0mm
 Length 1204.0mm
 Weight 1700g
 Package weight 2133g
 In box 6pcs
 Casing colour black
 Casing material aluminum
 Power supply [BOKE](#)
 Impact resistance IK06
 Work environment indoor use
 Operation temperature -20° - +45°C
 Certificates CE
 Warranty 5 years



Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors. Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space. Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Linear Light PROLUMEN Linda C27 1200 with downward light distribution black 230V 30W 4200lm 100° IP20 DALI 840

Product code 17876 DALI dimmable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.95
 Dimmable DALI
 Output 30W
 Luminous flux 4200lumens
 Luminaire's efficiency lm79 140W
 Correlated colour temperature pure white 4000K
 Lens angle 100
 Cri 80
 Ugr 19
 Sdcm - macadam ellipses 3
 Protection class IP20
 Lifespan 160000h
 Llmf tm21 L70B50 @25°C 160.000h
 Height 55.0mm
 Width 50.0mm
 Length 1120.0mm
 Weight 1940g
 In box 6pcs
 Casing colour black
 Casing material aluminum
 Polishing matt
 Power supply [TRIDONIC](#)
 Impact resistance IK08
 Work environment indoor use
 Operation temperature -20° - +45°C
 Certificates CE
 Warranty 5 years




Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors. Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space. Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Linear Light PROLUMEN Linda C27 1200 white 230V 30W 3900lm 100° IP20 830

Product code 17909

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.95
 Output 30W
 Luminous flux 3900lumens
 Luminaire's efficiency lm79 130W
 Correlated colour temperature warm white 3000K
 Lens angle 100
 Cri 80
 Sdcm - macadam ellipses 3
 Protection class IP20
 Lifespan 160000h
 Llmf tm21 L70B50 @25°C 160.000h
 Height 55.0mm
 Width 50.0mm
 Length 1120.0mm
 Weight 1940g
 In box 6pcs
 Casing colour white
 Casing material aluminum
 Polishing matt
 Power supply [TRIDONIC](#)
 Impact resistance IK08
 Work environment indoor use
 Operation temperature -20° - +45°C
 Certificates CE
 Warranty 5 years



Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors. Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space. Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

LED luminaire PROLUMEN Meena 1200 white 230V 40W 5600lm CRI80 120° IP44 3000K, 4000K, 5000K WW/DW/CW

Product code 17711

Brand [PROLUMEN](#)

Supply voltage 230V

Output 40W

Luminous flux 5600lumens

Luminaire's efficiency lm79 140W

Correlated colour temperature

WW/DW/CW 3000K, 4000K, 5000K

Lens angle 120

Cri 80

Sdcm - macadam ellipses 3

Protection class IP44

Lmf tm21 L90B10 @25°C 50.000h

Height 55.0mm

Width 140.0mm

Length 1198.0mm

In package 1pc

Casing colour white

Casing material aluminum + plastic

Power supply OSRAM

Operation temperature -20° - +45°C

Certificates CE, RoHS

Warranty 5 years



PROLUMEN Meena [linear luminaire](#) with adjustable power levels of 22W/30W/35W/40W. A high-quality linear light suitable for installation in parking garages, large closets, corridors, and warehouses. The Meena luminaire is designed to be very easy to install and maintain. The housing can be opened with a button press, and the suspension cables are adjustable during installation.

LED luminaire PROLUMEN Meena 1500 230V 60W 8400lm CRI80 120° IP44 3000K, 4000K, 5000K WW/DW/CW

Product code 17456

Brand [PROLUMEN](#)

Supply voltage 230V

Output 60W

Luminous flux 8400lumens

Luminaire's efficiency lm79 140W

Correlated colour temperature

WW/DW/CW 3000K, 4000K, 5000K

Lens angle 120

Cri 80

Sdcm - macadam ellipses 3

Protection class IP44

Lifespan 100000h

Height 55.0mm

Width 140.0mm

Length 1500.0mm

In package 1pc

Casing material aluminum + plastic

Operation temperature -20° - +45°C

Certificates CE, RoHS

Warranty 5 years



PROLUMEN Meena [linear luminaire](#) with adjustable power levels of 22W/30W/35W/40W. A high-quality linear light suitable for installation in parking garages, large closets, corridors, and warehouses. The Meena luminaire is designed to be very easy to install and maintain. The housing can be opened with a button press, and the suspension cables are adjustable during installation.

LED luminaire PROLUMEN Miina 1200 white 230V 40W 6400lm CRI80 120° IP65 3000K, 4000K, 5000K WW/DW/CW

Product code 17753

Brand [PROLUMEN](#)
 Supply voltage 230V
 Output 40W
 Luminous flux 6400lumens
 Luminaire's efficiency lm79 160W
 Correlated colour temperature
 WW/DW/CW 3000K, 4000K, 5000K
 Lens angle 120
 Cri 80
 Sdcm - macadam ellipses 3
 Protection class IP65
 Height 54.0mm
 Width 102.0mm
 Length 1219.0mm
 In package 1pc
 In box 6pcs
 Casing colour white
 Casing material aluminum + plastic
 Power supply [BOKE](#)
 Operation temperature -20° - +45°C
 Certificates CE, RoHS
 Warranty 5 years

PROLUMEN Miina linear light fixture with adjustable color temperature and power levels. A high-quality linear fixture suitable for installation in parking garages, large closets, corridors, and warehouses. The opal glass provides a very wide beam angle, evenly covering a larger area. The Miina fixture is designed for easy installation and maintenance. The color temperature and power are adjustable via a button on the fixture. A motion sensor can also be added to the Miina fixture. Adding the sensor is easy thanks to the openable end cap, where the sensor wires can be connected. With the motion sensor, LED lights become even more energy-efficient and convenient, as the step of turning the light on and off with a switch is eliminated, and the fixture turns off automatically. Trust your lighting project to the experienced team of LED House - [let's bring your vision to life!](#)



Linear Light PROLUMEN Retro Force 1500 white 230V 75W 12480lm 120° IP54 840

Product code 17675

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Output 75W
 Luminous flux 12480lumens
 Luminaire's efficiency lm79 166W
 Correlated colour temperature pure white 4000K
 Lens angle 120
 Source of light [SAMSUNG LED](#)
 Cri 80
 Sdcm - macadam ellipses 3
 Protection class IP54
 Lifespan 100000h
 Llmf tm21 L80B10 @25°C 100.000h
 Height 64.8mm
 Width 107.0mm
 Length 1460.0mm
 In package 1pc
 Casing colour white
 Power supply [BOKE](#)
 Impact resistance IK10
 Work environment indoor use
 Certificates CE, RoHS
 Warranty 5 years



PROLUMEN Retro Force industrial luminaire. These LED luminaires are equipped with high-quality components and provide excellent lighting for indoor use. The G-Force luminaire has adjustable power strength, allowing users to customize the brightness themselves. 38W/48W/58W/68W/75W Also available with DALI dimming technology, which allows users to adjust the brightness of the light according to their needs.

Linear Light PROLUMEN Retro Force 1500 white 230V 75W 12480lm 120° IP54 DALI 840

Product code 17443 DALI dimmable

Brand [PROLUMEN](#)

Supply voltage 230V

Power factor 0.90

Dimmable DALI

Output 75W

Luminous flux 12480lumens

Luminaire's efficiency lm79 166W

Correlated colour temperature pure white 4000K

Lens angle 120

Cri 80

Sdcm - macadam ellipses 3

Protection class IP54

Lifespan 100000h

Llmf tm21 L80B10 @25°C 100.000h

Height 64.8mm

Width 107.0mm

Length 1460.0mm

In package 1pc

Casing colour white

Power supply [BOKE](#)

Impact resistance IK10

Work environment indoor use

Certificates CE, RoHS

Warranty 5 years




PROLUMEN Retro Force industrial luminaire. These LED luminaires are equipped with high-quality components and provide excellent lighting for indoor use. The G-Force luminaire has adjustable power strength, allowing users to customize the brightness themselves. 38W/48W/58W/68W/75W Also available with DALI dimming technology, which allows users to adjust the brightness of the light according to their needs.

Ceiling light PROLUMEN SmartGlow Linear 1200 black 230V 36W 4000lm CRI90 100/50° IP20 DIMMABLE 3000-6500K WARM

TO COLD

Product code 17730 DIMMABLE
dimnable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Dimmable DIMMABLE
 Output 36W
 Luminous flux 4000lumens
 Luminaire's efficiency lm79 111W
 Correlated colour temperature WARM
 TO COLD 3000-6500K
 Lens angle 100/50
 Cri 90
 Ugr 6
 Sdcm - macadam ellipses 3
 Protection class IP20
 Lifespan 50000h
 Llmf tm21 L80B10 @25°C 50.000h
 Height 85.0mm
 Width 65.0mm
 Length 1200.0mm
 In package 1pc
 Casing colour black
 Casing material aluminum
 Power supply [BOKE](#)
 Work environment indoor use
 Operation temperature -10 - +30°C
 Certificates CE
 Warranty 5 years




Ergonomic office light with adjustable color temperature, featuring an aesthetic and compact design that fits into any modern office. SmartGlow illuminates both the desk and the room - the light beam shines both downwards and upwards. The upward-directed light makes the room feel more spacious. The luminaire has an exceptionally good UGR value, meaning the light beam is not uncomfortable for the eyes and glare is minimal. If you want to make your space even more impressive, it is possible to order this luminaire in a connectable version, allowing the linear ceiling light to extend throughout the entire room. In addition to its good looks, SmartGlow is easy to install and control thanks to its patented lockable plug. It can be mounted suspended, surface-mounted, or recessed. As a bonus, it features HCL intelligent control with Casambi, presence, and daylight sensors. Contact our sales team, and we will plan a top-notch lighting solution for your spaces!

Ceiling light PROLUMEN SmartGlow Linear 1500 black 230V 36W 4000lm CRI90 50° IP20 DALI 3000-6500K WARM TO COLD

Product code 17772 DALI dimmable

Brand [PROLUMEN](#)
 Supply voltage 230V
 Power factor 0.90
 Dimmable DALI
 Output 36W
 Luminous flux 4000lumens
 Luminaire's efficiency lm79 111W
 Correlated colour temperature WARM
 TO COLD 3000-6500K
 Lens angle 50
 Cri 90
 Ugr 6
 Sdcm - macadam ellipses 3
 Protection class IP20
 Lifespan 50000h
 Llmf tm21 L80B10 @25°C 50.000h
 Height 85.0mm
 Width 65.0mm
 Length 1550.0mm
 In package 1pc
 Casing colour black
 Casing material aluminum
 Power supply [BOKE](#)
 Work environment indoor use
 Operation temperature -10 - +30°C
 Certificates CE
 Warranty 5 years



Ergonomic office light with adjustable color temperature, featuring an aesthetic and compact design that fits into any modern office. SmartGlow illuminates both the desk and the room - the light beam shines both downwards and upwards. The upward-directed light makes the room feel more spacious. The luminaire has an exceptionally good UGR value, meaning the light beam is not uncomfortable for the eyes and glare is minimal. If you want to make your space even more impressive, it is possible to order this luminaire in a connectable version, allowing the linear ceiling light to extend throughout the entire room. In addition to its good looks, SmartGlow is easy to install and control thanks to its patented lockable plug. It can be mounted suspended, surface-mounted, or recessed. As a bonus, it features HCL intelligent control with Casambi, presence, and daylight sensors. Contact our sales team, and we will plan a top-notch lighting solution for your spaces!

LED luminaire PROLUMEN Zennor 1200 frame white 230V IP20

Product code 17710

Brand [PROLUMEN](#)
Supply voltage 230V
Power factor 0.95
Ugr 19
Sdcm - macadam ellipses 3
Protection class IP20
Lifespan 54000h
Llmf tm21 L90B50 @25°C 50.000h
Height 80.0mm
Width 46.0mm
Length 1182.0mm
In package 1pc
Casing colour white
Casing material aluminum
Power supply [BOKE](#)
Operation temperature -20° - +45°C
Certificates TUV ENEC, CB, CE, VDE, ROHS
Warranty 5 years



Zennor linear system allows customization of lighting according to specific requirements and room characteristics. The IP20 protection class ensures durability against dust and small amounts of liquid, making them suitable for various indoor spaces, such as offices, shopping malls, or homes. Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

LED luminaire PROLUMEN Zennor 1200 module black 50W 20° IP20 840

Product code 17393

Brand [PROLUMEN](#)

Output 50W

Correlated colour temperature pure white 4000K

Lens angle 20

Cri 80

Ugr 19

Sdcm - macadam ellipses 3

Protection class IP20

Llmf tm21 L80B10 @25°C 50.000h

Length 1164.0mm

Casing colour black

No. of switches 50000pcs

Impact resistance IK02

Work environment indoor use



Zennor is an LED modular light fixture, where different lengths can be used to achieve different power and light output. LED module requires a separate power supply unit or housing with built-in power supply. Illuminate your world with LED House professionals - [check out our project portfolio here!](#)