Signal amplifier 3x4A 12-24V 288W IP20

Product code 12669

Supply voltage 12-24V
Output 288W
Maximum output 288W/1m
Rated current 12000mA
Protection class IP20
Height 24.0mm
Width 64.0mm
Length 105.0mm
Weight 100 g
Casing material aluminium
Work environment indoor use
Certificates CE



Receiver LTECH F4-3A 12A 5-24V

Product code 14039

Brand LTECH
Supply voltage 5-24V
Maximum output 288W/1m
Rated current 12000mA
Height 20.0mm
Width 33.0mm
Length 125.0mm
Weight 60 g
Operation temperature -30℃~55℃
Warranty 5 years

5V 60W 12V 144W 24V 288W



Receiver LTECH F4-5A 20A 5-24V

Product code 14038



Brand LTECH
Supply voltage 5-24V
Rated current 20000mA
Height 30.0mm
Width 44.0mm
Length 175.0mm
Weight 150 g
Work environment indoor use
Operation temperature -30℃~55°C
Certificates CE, RoHS
Warranty 3 years

5V 100W 12V 240W 24V 480W

Receiver LTECH LT M4 4x5A 5-24V 480W

Product code 13702



Brand LTECH
Supply voltage 5-24V
Output 480W
Maximum output 480W/1m
Rated current 20000mA
Height 30.0mm
Width 44.0mm
Length 175.0mm
Weight 125 g
Operation temperature -30℃~55°C
Certificates CE, RoHS
Warranty 3 years

Receiver SKYDANCE 12-24V DC 6CH CV0 Junction box 12-24V IP20

Product code 17789

Brand SKYDANCE
Supply voltage 12-24V
Output voltage 24V
Maximum output 60W/1m
Rated current 2500mA
Protection class IP20
Lifespan 50000h
Height 18.0mm
Width 55.5mm
Length 54.0mm
In package 1pc
Work environment indoor use
Operation temperature -30° - +45°C
Certificates CE, RoHS
Warranty 5 years



Receiver SKYDANCE DA1DT6 1x15A 12-24V IP20 DALI

Product code 16983 **DALI dimmable**

Brand SKYDANCE
Supply voltage 12-24V
Dimmable DALI
Output voltage 12-24V
Maximum output 360W/1m
Rated current 15000mA
Protection class IP20
Height 27.0mm
Width 45.0mm
Length 175.0mm
Work environment indoor use
Operation temperature -30~55°C
Certificates CE
Warranty 5 years



Receiver SKYDANCE DA4-M DT6/DT8 4x5A 12-24V IP20 DALI

Product code 16401 DALI dimmable

Brand SKYDANCE
Supply voltage 12-24V
Dimmable DALI
Output voltage 12-24V
Maximum output 480W/1m
Rated current 20000mA
Protection class IP20
Height 27.0mm
Width 45.0mm
Length 175.0mm
Work environment indoor use
Operation temperature -30~55°C
Certificates CE
Warranty 5 years



Receiver SKYDANCE DA4-T DT6/DT8 4x5A 12-48V IP20 DALI

Product code 23469 DALI dimmable

Brand SKYDANCE
Supply voltage 12-48V
Dimmable DALI
Output voltage 12-48V
Maximum output 960W/1m
Rated current 20000mA
Protection class IP20
Height 26.0mm
Width 50.0mm
Length 94.0mm
Package weight 97 g
Work environment indoor use
Operation temperature -30~55°C
Certificates CE
Warranty 5 years



Controller SKYDANCE DMX512 SPI Controller DS 5-24V IP20 RF

Product code 15833 RF dimmable

Brand SKYDANCE
Supply voltage 5-24V
Dimmable RF
Protection class IP20
Height 67.0mm
Width 48.0mm
Length 110.0mm
Weight 98 g
Package weight 129 g
In package 1pc
Casing material plastic
Work environment indoor use
Operation temperature -30~55°C
Certificates CE
Warranty 5 years



Controller SKYDANCE DMX512 SPI Controller DS-L 5-24V RF

Product code 15830 RF dimmable

Brand SKYDANCE
Supply voltage 5-24V
Dimmable RF
In package 1pc
Casing material plastic
Work environment indoor use
Operation temperature -30~55°C
Battery CR2032
Certificates CE
Warranty 5 years



Controller SKYDANCE Dual SPI Controller ES-D(WT) 5-24V IP20

Product code 18254

Brand SKYDANCE
Supply voltage 5-24V
Protection class IP20
Height 23.0mm
Width 50.0mm
Length 170.0mm
In package 1pc
Casing material plastic
Work environment indoor use
Operation temperature -30° - +55°C
Certificates CE
Warranty 5 years



Receiver SKYDANCE S3 3x1A RGB 230V IP20 RF

Product code 16647 RF dimmable

Brand SKYDANCE
Supply voltage 230V
Dimmable RF
Output voltage 230V
Maximum output 720W/1m
Rated current 3000mA
Protection class IP20
Height 27.0mm
Width 45.0mm
Length 175.0mm
Weight 117 g
Package weight 136 g
Casing material plastic
Work environment indoor use
Operation temperature -30° - +55°C
Certificates CE
Warranty 5 years



Receiver SKYDANCE S3(WT) 3x1A RGB RF/Wifi 230V IP20 RF / WIFI

Product code 17781 **RF / WIFI**
dimmable

Brand SKYDANCE
Supply voltage 230V
Dimmable RF / WIFI
Output voltage 230V
Maximum output 720W/1m
Rated current 3200mA
Protection class IP20
Height 27.0mm
Width 45.0mm
Length 175.0mm
Work environment indoor use
Operation temperature -30° - +55°C
Certificates CE, RoHS, emc, LVD, RED
Warranty 5 years



Receiver SKYDANCE V1 8A 5-36V IP20 PUSH / RF

Product code 15762 **PUSH / RF**
dimmable

Brand SKYDANCE
Supply voltage 5-36V
Dimmable PUSH / RF
Output voltage 5-36V
Maximum output 288W/1m
Rated current 8000mA
Protection class IP20
Height 18.0mm
Width 33.0mm
Length 97.0mm
Casing material plastic
Work environment indoor use
Operation temperature -30~55°C
Certificates CE
Warranty 5 years

5-36VDC 8A*1CH 5V-40W 12V-96W
24V-192W 36V-288W



Receiver SKYDANCE V1-WPM 5A 12-24V IP67 RF

Product code 22979 RF dimmable

Brand SKYDANCE
Supply voltage 12-24V
Dimmable RF
Output voltage 12-24V
Maximum output 120W/1m
Rated current 5000mA
Protection class IP67
Height 29.0mm
Width 35.0mm
Length 87.0mm
Casing material plastic
Work environment indoor use
Operation temperature -30~55°C
Certificates CE
Warranty 5 years



Receiver SKYDANCE V2 10A CCT 12-24V IP20 RF

Product code 16361 RF dimmable

Brand SKYDANCE
Supply voltage 12-24V
Dimmable RF
Output voltage 12-24V
Maximum output 240W/1m
Rated current 10000mA
Protection class IP20
Height 18.0mm
Width 33.0mm
Length 97.0mm
Weight 38 g
Package weight 49 g
In package 1pc
Casing material plastic
Work environment indoor use
Operation temperature -30~55°C
Certificates CE
Warranty 5 years



Receiver SKYDANCE V3 3x4A RGB 12-24V IP20 RF

Product code 16646 RF dimmable

Brand SKYDANCE
Supply voltage 12-24V
Dimmable RF
Output voltage 12-24V
Maximum output 288W/1m
Rated current 12000mA
Protection class IP20
Height 18.0mm
Width 33.0mm
Length 97.0mm
Weight 38 g
Package weight 49 g
Casing material plastic
Work environment indoor use
Operation temperature -30~55°C
Certificates CE
Warranty 5 years

RGB controller 12-24VDC 4A*3CH
12V-144W 24V-288



Receiver SKYDANCE V4-WPS 4x5A 12-36V IP67 RF

Product code 16859 RF dimmable

Brand SKYDANCE
Supply voltage 12-36V
Dimmable RF
Output voltage 12-36V
Maximum output 480W/1m
Rated current 20000mA
Protection class IP67
Height 34.0mm
Width 57.0mm
Length 153.0mm
Package weight 492 g
Casing material plastic
Work environment indoor / outdoor use
Operation temperature -30~55°C
Certificates CE
Warranty 5 years

RF controller for controlling various LED strips, supports DIM/RGB/RGBW/CCT remotes.
12-36VDC 5A*4CH 12V-240W
24V-480W 36V-720W



Controller SKYDANCE WiFi & RF Dimmer DA-ML(WT) 230V IP20 DALI

Product code 18046 **DALI dimmable**

Brand SKYDANCE
Supply voltage 230V
Dimmable DALI
Rated current 150mA
Protection class IP20
Height 25.0mm
Width 38.0mm
Length 140.0mm
Weight 85 g
Work environment indoor use
Operation temperature -20~55°C
Certificates CE
Warranty 5 years



This smart lighting control device allows you to control DALI lights via WiFi and RF. It can also be used as a DALI system power supply. The device connects to the Tuya Smart app, enabling you to turn lights on and off, change colors, adjust brightness and color temperature, set timers, and even sync lighting with music. It supports various lighting modes, including smooth and jump transitions, and is compatible with all DALI-standard products. Additionally, it can be controlled via an RF remote or a regular switch, allowing you to turn lights on/off and adjust brightness.

Receiver SKYDANCE WT-SPI 8A for pixel LED 5-24V IP20 RF / WIFI

Product code 17191 **RF / WIFI**
dimmable

Brand SKYDANCE
Supply voltage 5-24V
Dimmable RF / WIFI
Output voltage 5-24V
Maximum output 192W/1m
Rated current 8000mA
Protection class IP20
Height 27.0mm
Width 43.0mm
Length 120.0mm
Package weight 66 g
Work environment indoor use
Operation temperature -30~55°C
Certificates CE
Warranty 5 years

WIFI/RF LED digital strip controller.
Compatible with the Tuya APP.



Receiver SKYDANCE WT1 2x5A 12-24V IP20 RF / WIFI

Product code 19690 **RF / WIFI**
dimmable

Brand SKYDANCE
Supply voltage 12-24V
Dimmable RF / WIFI
Output voltage 12-24V
Maximum output 240W/1m
Rated current 10000mA
Protection class IP20
Height 20.0mm
Width 38.0mm
Length 114.0mm
Casing material plastic
Work environment indoor use
Operation temperature -30~55°C
Certificates CE
Warranty 5 years



Receiver SKYDANCE WT5 5x3A 12-24V IP20 RF / WIFI

Product code 15794 **RF / WIFI dimmable**

Brand SKYDANCE
Supply voltage 12-24V
Dimmable RF / WIFI
Output voltage 12-24V
Maximum output 360W/1m
Rated current 15000mA
Protection class IP20
Height 20.0mm
Width 38.0mm
Length 114.0mm
Casing material plastic
Work environment indoor use
Operation temperature -30~55°C
Certificates CE
Warranty 5 years



Receiver SKYDANCE WZ5 5x3A ZigBee 12-24V IP20 RF

Product code 16520 **RF dimmable**

Brand SKYDANCE
Supply voltage 12-24V
Dimmable RF
Output voltage 12-24V
Maximum output 360W/1m
Rated current 15000mA
Protection class IP20
Height 20.0mm
Width 38.0mm
Length 114.0mm
Casing material plastic
Work environment indoor use
Operation temperature -30~55°C
Certificates CE
Warranty 5 years

