

## Valguspult DMX Split 4 Splitter 20W (LH3709)

tootekood: LH3709  
toide: 230V  
võimsus: 20W  
kõrgus: 80mmmm  
laius: 190mmmm  
pikkus: 325mmmm  
kaal: 3g  
garantii: 2 aastat



3-pin or 5-pin XLR connector

## Valguspult EUROLITE DMX LED Operator 2 controller (LH3497)

tootekood: LH3497  
toide: 230V  
kaal: 1g  
garantii: 2 aastat



## Valguspult EUROLITE DMX LED Operator 4 controller (LH3250)

tootekood: LH3250  
toide: 230V  
garantii: 2 aastat

50 control channels only suitable for matching LED effects 4 LED parcans can be controlled individually Select color mode for choosing single colors Internal programs Auto mode for running all programs Sound-control via built-in microphone or RCA input Pause function Blackout function LCD and control LEDs display current operating mode Program select fader for selecting the internal programs Speed fader for adjusting the program speed Strobe-effect with adjustable speed Additional fogger button for direct control of a DMX smoke machine (CH-49/50) Designed for standing operation, optional installation is customer's choice Power supply via enclosed power unit



## Valguspult EUROLITE DMX LED Operator IR2DMX + IR RC IP20 (LH3820)

tootekood: LH3820  
 toide: 230V  
 kaitseklass: IP20  
 kõrgus: 35mmmm  
 laius: 100mmmm  
 pikkus: 110mmmm  
 kaal: 300g  
 garantii: 2 aastat

DMX controller for LED devices with infrared receiver Including matching EUROLITE IR remote Inexpensive solution for controlling LED effects with 5-channel standard DMX protocol or KLS spotlight sets via an infrared 4 LED parcans, one KLS light set and one LED BAR can be controlled at the same time Functions: static colors, automatic color change, internal programs, strobe effect, Master/Slave 47 control channels 3-pin XLR DMX output Control in stand-alone mode and DMX programming Sound-control via built-in microphone Adjustable microphone sensitivity via remote control



## Valguspult FD-12 DMX (LH3252)

tootekood: LH3252  
 toide: 230V  
 garantii: 2 aastat

12 channel faders with LED Fade time fader with LED for adjusting the step time Master fader with LED for adjusting the total output level Speed fader for adjusting the program-speed Flash button per channel and master-flash LED display of all modes 4 freely programmable programs with up to 84 steps each Controller comes with 4 pre-programmed chasers The programs and chasers can be called up individually or combined (CH1-2-3-4-PR-1-2-3-4) Dimmer: manual control of the channels via sliders Full On: all channels can be switched on together Blackout function Program speed adjustable via speed fader or tap sync button Sound-control via external signal or integrated microphone Only for professional use Sound to light via 6.3 mm jack Power supply via included power unit



## Valguspult FD-8 DMX (LH3251)

tootekood: LH3251  
toide: 230V  
garantii: 2 aastat

8 channel faders with LED Fade time fader with LED for adjusting the step time Master fader with LED for adjusting the total output level Speed fader for adjusting the program-speed Flash button per channel and master-flash LED display of all modes 4 freely programmable programs with up to 84 steps each Controller comes with 4 pre-programmed chasers The programs and chasers can be called up individually or combined (CH1-2-3-4-PR-1-2-3-4) Dimmer: manual control of the channels via sliders Full On: all channels can be switched on together Blackout function Program speed adjustable via speed fader or tap sync button Sound-control via external signal or integrated microphone Sound to light via 6.3 mm jack Power supply via included power unit or 9 V battery included in the delivery Only for professional use



## Valguspult Martin Lightjockey Universal USB/DMX Interface (LH2892)

tootekood: LH2892  
LEDi eluiga: 50000h  
garantii: 2 aastat



## Valguspult QuickDMX Wireless transmitter/receiver IP20 (LH3760)

tootekood: LH3760  
toide: 230V  
kaitseklass: IP20  
kõrgus: 75mmmm  
laius: 100mmmm  
pikkus: 212mmmm  
garantii: 2 aastat



- Compact DMX transmitter/receiver for the wireless transmission of up to 512 DMX channels
- DMX input and output, 3-pin XLR
- Auto-switching transceiver
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transmitters and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- Operating range up to 400 m (with line-of-sight)
- Simultaneous operation of up to 6 transmitters, thus control of 3072 DMX channels (6 DMX universes) possible
- 1 to 512 QuickDMX receivers can be controlled by each transmitter
- Plug & Play: quick and easy setup with one operating button for connecting/disconnecting QuickDMX units
- LED indication for functions
- Micro USB port; PSU included
- 2.4 GHz ISM band - license-free worldwide