

Valguspult CLX-16 DMX (LH3253)

tootekood: LH3253
toide: 230V
garantii: 2 aastat

8 channel-faders with LED 8 channels switchable via Latch-buttons Fade Time button for adjusting the step time Master-fader with LED for adjusting the total output level Audio-control with LED for adjusting the music sensitivity Speed-control for adjusting the program-speed Flash-button per channel and master-flash (Full On-button) LED-display of all modes 30 freely programmable programs Dimmer: Manual control of the channels via sliders Full On: all channels can be switched on together Program speed adjustable via speed-fader or Tap Sync-button Sound-control via external signal or integrated microphone Sound to light via RCA socket Foot switch connection via 9-pin Sub-D socket Power supply via included power unit



Valguspult CP-512 MST Controller 16 bit (LH3710)

tootekood: LH3710
toide: 230V
kõrgus: 83mmmm
laius: 265mmmm
pikkus: 483mmmm
garantii: 2 aastat

- 512 control channels for 16 projectors with up to 32 channels
- 16-bit resolution for fine Pan/Tilt movements
- Projector library with up to 255 entries
- 64 programs
- 64 records
- 64 preset scenes, 64 preset macros
- 10 selectable languages
- Mirror movement direction can be inverted
- Copy function for scenes, programs and records
- 99 chasers definable, one chaser per program
- Blackout function
- Sound control via built-in microphone or audio input
- Security code operation
- Operating hour meter
- USB port for firmware updates (available in the download section)
- Rack installation with 6 U



Valguspult DMX Split 4 Splitter 20W (LH3709)

tootekood: LH3709
toide: 230V
võimsus: 20W
kõrgus: 80mmmm
laius: 190mmmm
pikkus: 325mmmm
kaal: 3g
garantii: 2 aastat



3-pin or 5-pin XLR connector

Valguspult EUROLITE DMX LED Operator 2 controller (LH3497)

tootekood: LH3497
toide: 230V
kaal: 1g
garantii: 2 aastat



Valguspult EUROLITE DMX LED Operator 4 controller (LH3250)

tootekood: LH3250
toide: 230V
garantii: 2 aastat

50 control channels only suitable for matching LED effects 4 LED parcans can be controlled individually Select color mode for choosing single colors Internal programs Auto mode for running all programs Sound-control via built-in microphone or RCA input Pause function Blackout function LCD and control LEDs display current operating mode Program select fader for selecting the internal programs Speed fader for adjusting the program speed Strobe-effect with adjustable speed Additional fogger button for direct control of a DMX smoke machine (CH-49/50) Designed for standing operation, optional installation is customer's choice Power supply via enclosed power unit



Valguspult EUROLITE DMX LED Operator IR2DMX + IR RC IP20 (LH3820)

tootekood: LH3820
toide: 230V
kaitseklass: IP20
kõrgus: 35mmmm
laius: 100mmmm
pikkus: 110mmmm
kaal: 300g
garantii: 2 aastat

DMX controller for LED devices with infrared receiver Including matching EUROLITE IR remote Inexpensive solution for controlling LED effects with 5-channel standard DMX protocol or KLS spotlight sets via an infrared 4 LED parcans, one KLS light set and one LED BAR can be controlled at the same time Functions: static colors, automatic color change, internal programs, strobe effect, Master/Slave 47 control channels 3-pin XLR DMX output Control in stand-alone mode and DMX programming Sound-control via built-in microphone Adjustable microphone sensitivity via remote control



Valguspult FD-12 DMX (LH3252)

tootekood: LH3252
toide: 230V
garantii: 2 aastat

12 channel faders with LED Fade time fader with LED for adjusting the step time Master fader with LED for adjusting the total output level Speed fader for adjusting the program-speed Flash button per channel and master-flash LED display of all modes 4 freely programmable programs with up to 84 steps each Controller comes with 4 pre-programmed chasers The programs and chasers can be called up individually or combined (CH1-2-3-4-PR-1-2-3-4) Dimmer: manual control of the channels via sliders Full On: all channels can be switched on together Blackout function Program speed adjustable via speed fader or tap sync button Sound-control via external signal or integrated microphone Only for professional use Sound to light via 6.3 mm jack Power supply via included power unit



Valguspult FD-8 DMX (LH3251)

tootekood: LH3251
toide: 230V
garantii: 2 aastat

8 channel faders with LED Fade time fader with LED for adjusting the step time Master fader with LED for adjusting the total output level Speed fader for adjusting the program-speed Flash button per channel and master-flash LED display of all modes 4 freely programmable programs with up to 84 steps each Controller comes with 4 pre-programmed chasers The programs and chasers can be called up individually or combined (CH1-2-3-4-PR-1-2-3-4) Dimmer: manual control of the channels via sliders Full On: all channels can be switched on together Blackout function Program speed adjustable via speed fader or tap sync button Sound-control via external signal or integrated microphone Sound to light via 6.3 mm jack Power supply via included power unit or 9 V battery included in the delivery Only for professional use



Valguspult Martin Lightjockey Universal USB/DMX Interface (LH2892)

tootekood: LH2892
LEDi eluiga: 50000h
garantii: 2 aastat



Valguspult QuickDMX Wireless transmitter/receiver IP20 (LH3760)

tootekood: LH3760
toide: 230V
kaitseklass: IP20
kõrgus: 75mmmm
laius: 100mmmm
pikkus: 212mmmm
garantii: 2 aastat



- Compact DMX transmitter/receiver for the wireless transmission of up to 512 DMX channels
- DMX input and output, 3-pin XLR
- Auto-switching transceiver
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transmitters and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- Operating range up to 400 m (with line-of-sight)
- Simultaneous operation of up to 6 transmitters, thus control of 3072 DMX channels (6 DMX universes) possible
- 1 to 512 QuickDMX receivers can be controlled by each transmitter
- Plug & Play: quick and easy setup with one operating button for connecting/disconnecting QuickDMX units
- LED indication for functions
- Micro USB port; PSU included
- 2.4 GHz ISM band - license-free worldwide